according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaForce®-300 Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.

Karczunkowska 89 02-871 Warszawa

Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com

responsible for the SDS

1.4 Emergency telephone number

112

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Acute toxicity, Category 4 H312: Harmful in contact with skin.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure if inhaled.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Date of last issue: 10.08.2023

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H312 + H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged

or repeated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other igni-

tion source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust or mist.

P264 Wash skin thoroughly after handling.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

#### Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023



# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)			
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 60 - < 80			
isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1A; H220 >= 1 - < 2				
Substances with a workplace exposure limit :						
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1A; H220	>= 20 - < 25			
butane	106-97-8 203-448-7 01-2119474691-32- XXXX	Flam. Gas 1A; H220	>= 10 - < 20			

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Date of last issue: 10.08.2023

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** Cough

> Respiratory disorder **Excessive lachrymation**

Erythema Headache **Dermatitis** Skin disorders

See Section 11 for more detailed information on health effects

and symptoms.

Risks irritant effects

Harmful in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

#### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media Water spray jet

Dry powder Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023

Further information : Use water spray to cool unopened containers.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

Country PL 100000010874

5 / 17

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023

areas and containers exposure and temperatures over 50 °C. Do not open by force

or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label

precautions. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake		ficant uptake	
	through the skin, Indicative			-
		STEL	100 ppm	2000/39/EC
			442 mg/m3	
		NDS	100 mg/m3	PL OEL
	Further information: Skin			
		NDSch	200 mg/m3	PL OEL
propane	74-98-6	NDS	1.800 mg/m3	PL OEL
butane	106-97-8	NDS	1.900 mg/m3	PL OEL
		NDSch	3.000 mg/m3	PL OEL

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Date of last issue: 10.08.2023

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm). breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers).

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

**SECTION 9: Physical and chemical properties** 

9.1 Information on basic physical and chemical properties

Physical state aerosol

Appearance Aerosol containing a liquefied gas

Colour various

Odour solvent-like

Melting point/range / Freezing : No data available

point

No data available Boiling point/boiling range

Flammability : Extremely flammable aerosol.

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : 7,0 %(V)

per flammability limit

Lower explosion limit / Lower flammability limit : 1,1 %(V)

Country PL 100000010874

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0

Date of last issue: 10.08.2023

Sika®

2.0 Print Date 11.03.2024

Flash point : < 0 °C

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

**Viscosity** 

Viscosity, dynamic : not determined

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 8300 hPa

Density : ca. 0,70 g/cm3 (20 °C)

Bulk density : Not applicable

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Date of last issue: 10.08.2023

### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Harmful in contact with skin or if inhaled.

#### **Components:**

#### reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

### Respiratory sensitisation

Not classified due to lack of data.

### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

Country PL 100000010874

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023

#### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified due to lack of data.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox-

icity)

NOEC: > 1,3 mg/l

Exposure time: 56 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 1,17 mg/l Exposure time: 7 d

Species: Daphnia (water flea)

### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0

Date of last issue: 10.08.2023



### 12.6 Endocrine disrupting properties

### **Product:**

The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

### Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

#### Components:

#### propane:

20-year global warming potential: 0,072 100-year global warming potential: 0,02 500-year global warming potential: 0,006

Atmospheric lifetime: 0,036 yr Radiative efficiency: 0 Wm2ppb

Further information: Miscellaneous compounds

#### butane:

20-year global warming potential: 0,022 100-year global warming potential: 0,006 500-year global warming potential: 0,002

Atmospheric lifetime: 0,019 yr Radiative efficiency: 0 Wm2ppb

Further information: Miscellaneous compounds

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023



local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : UN 1950 IMDG : UN 1950 IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

**ADR** : 2 2.1

**IMDG** : 2.1 **IATA** : 2.1

14.4 Packing group

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation


Labels : Flammable Gas

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Date of last issue: 10.08.2023



# 14.5 Environmental hazards

Environmentally hazardous no

**IMDG** 

Marine pollutant no

IATA (Passenger)

Environmentally hazardous no

IATA (Cargo)

Environmentally hazardous no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

**REACH Information:** All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Date of last issue: 10.08.2023

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

,

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 91,92% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 92% w/w

### Other regulations:

75/324/EEC

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Date of last issue: 10.08.2023

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Revision Date: 09.03.2024 Version 2.0 Print Date 11.03.2024

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### Full text of H-Statements

H220	:	Extremely flammable gas.
H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolong

ged or repeated

exposure if inhaled.

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Date of last issue: 10.08.2023

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

PL OEL : Ordinance of the Minister of Family, Labour and Social Policy

of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the work-

place (Dz.U 2018 pos 1286, with later amendments)

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

PL OEL / NDS : Maximal Admissible Concentration

PL OEL / NDSch : Maximal Admissible Temporary Concentration

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

**Further information** 

Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

according to Regulation (EC) No. 1907/2006

# SikaForce®-300 Primer

Print Date 11.03.2024

Revision Date: 09.03.2024 Version 2.0 F
Date of last issue: 10.08.2023

Calculation method	H332	Acute Tox. 4
Calculation method	H312	Acute Tox. 4
Calculation method	H315	Skin Irrit. 2
Calculation method	H319	Eye Irrit. 2
Calculation method	H335	STOT SE 3
Calculation method	H373	STOT RE 2
Calculation method	H412	Aquatic Chronic 3

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

PL / EN