

Revision Date: 31.10.2023 Date of last issue: - Version 2.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikaflex<sup>®</sup>-228

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

#### 1.4 Emergency telephone number

112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Specific target organ toxicity - repeated exposure, Category 2, Central nervous system	H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
		H373	May cause damage to organs (Central nerv- ous system) through prolonged or repeated

## Sikaflex<sup>®</sup>-228



Revision Date: 31.10.2023 Version 2.0 Prir Date of last issue: -

exposure if inhaled.

Precautionary statements :	<b>Prevention:</b> P260 P284	Do not breathe mist or vapours. In case of inadequate ventilation wear respir- atory protection.
	Response:	
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
	Disposal:	
	P501	Dispose of contents/container in accordance with local regulation.

#### Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 4,4'-methylenediphenyl diisocyanate aromatic polyisocyanate m-tolylidene diisocyanate

#### **Additional Labelling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 31.10.2023 Date of last issue: -

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
Hydrocarbons, C9-C12, n- alkanes, isoalkanes, cyclics, aro- matics (2-25%)	Not Assigned 919-446-0 265-185-4 01-2119458049-33- XXXX [corresponding group CAS 64742-82- 1]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - < 2,5

## Sikaflex<sup>®</sup>-228

Print Date 05.02.2024

Revision Date: 31.10.2023 Date of last issue: - Version 2.0

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	>= 0,1 - < 0,5
aromatic polyisocyanate	53317-61-6 Not Assigned	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0,1 - < 0,5

## Sikaflex<sup>®</sup>-228

Print Date 05.02.2024

Revision Date: 31.10.2023	
Date of last issue: -	

Version 2.0

m-tolylidene diisocyanate	26471-62-5 247-722-4 01-2119454791-34- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 	>= 0,0025 - < 0,025
Substances with a workplace expos			
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 2,5 - < 5

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water.

<b>Jika</b> ®
Print Date 05.02.2024

Revision Date: 31.10.2023	Version 2.0	ļ
Date of last issue: -		

Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	<ul> <li>Asthmatic appearance Allergic reactions See Section 11 for more detailed information on health effec and symptoms.</li> </ul>
Risks	: sensitising effects
	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
	May cause damage to organs through prolonged or repeated exposure if inhaled.

Treatment : 7	Treat symptomatically.
---------------	------------------------

#### **SECTION 5: Firefighting measures**

<b>5.1 Extinguishing media</b> Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.
SECTION 6: Accidental release	se i	neasures

# 6.1 Personal precautions, protective equipment and emergency procedures Personal precautions : Use personal protective equipment. Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
---------------------------	---	---

Print Date 05.02.2024

Revision Date: 31.10.2023 Version 2.0 Date of last issue: -

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

	Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).
			For personal protection see section 8.
			Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
			Smoking, eating and drinking should be prohibited in the application area.
			Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage,	incl	luding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any

## **SECTION 8: Exposure controls/personal protection**

use.

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

#### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikaflay® 228

## Sikaflex<sup>®</sup>-228

Print Date 05.02.2024

Revision Date: 31.10.2023 Date of last issue: -

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
Titanium dioxide (> 10 μm)	13463-67-7	NDS (inhalable fraction)	10 mg/m3	PL OEL		
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake					
		through the skin, Indicative				
		STEL	100 ppm 442 mg/m3	2000/39/EC		
		NDS	100 mg/m3	PL OEL		
	Further information: Skin					
		NDSch	200 mg/m3	PL OEL		
Hydrocarbons, C9-C12, n-alkanes, isoal- kanes, cyclics, aromatics (2-25%)	Not Assigned	NDS	300 mg/m3	PL OEL		
		NDSch	900 mg/m3	PL OEL		
4,4'-methylenediphenyl diisocyanate	101-68-8	NDS	0,03 mg/m3	PL OEL		
· · ·		NDSch	0,09 mg/m3	PL OEL		
m-tolylidene diisocyanate	26471-62-5	NDS	0,007 mg/m3	PL OEL		
		NDSch	0,021 mg/m3	PL OEL		

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed

## Sikaflex<sup>®</sup>-228

Print Date 05.02.2024

Revision Date: 31.10.2023 Date of last issue: - Version 2.0

respirator complying with an approved standard if a risk assessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice	: Do not flush into surface water or sanitary	v sewer system.
----------------	---	-----------------

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Appearance	:	paste
Colour	:	various
Odour	:	characteristic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit /		
Lower flammability limit	:	No data available
	:	
Lower flammability limit	:	65 °C

## Sikaflex<sup>®</sup>-228



Revision Date: 31.10.2023 Date of last issue: -	Version 2.0	Print Date 05.02.2024
рН	: Not applicable substance/mixture is non-soluble (in water)	
Viscosity		
Viscosity, dynamic	: Not applicable	
Viscosity, kinematic	: > 7 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,27 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information		
No data available		

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Print Date 05.02.2024

Revision Date: 31.10.2023 Date of last issue: - Version 2.0

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### **Components:**

#### reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

#### 4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method
aromatic polyisocyanate:		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
m-tolylidene diisocyanate:		
Acute inhalation toxicity	:	LC50 (Rat): 0,107 mg/l Exposure time: 4 h Test atmosphere: vapour
		Acute toxicity estimate: 0,107 mg/l Test atmosphere: vapour Method: Calculation method

#### Skin corrosion/irritation

Not classified due to lack of data.

Components:

Hydrocarbons,	, C9-C12, n-alkanes,	isoalkanes, cyclics,	aromatics (2-25%):
---------------	----------------------	----------------------	--------------------

Assessment	:	Repeated exposure may cause skin dryness or cracking.
Result	:	Repeated exposure may cause skin dryness or cracking.

## Sikaflex<sup>®</sup>-228

Revision Date: 31.10.2023 Date of last issue: - Version 2.0



#### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### **Respiratory sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

## STOT - single exposure

Not classified due to lack of data.

#### STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

#### Aspiration toxicity

Not classified due to lack of data.

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox-	:	NOEC: > 1,3 mg/l
icity)		Exposure time: 56 d
		Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : NOEC: 1,17 mg/l

Print Date 05.02.2024

Revision Date: 31.10.2023 Date of last issue: - Version 2.0

aquatic invertebrates (Chron-	Exposure time: 7 d
ic toxicity)	Species: Daphnia (water flea)

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### **12.6 Endocrine disrupting properties**

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	

#### Product:

Additional ecological infor- : There is no data available for this product. mation

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

 The generation of waste should be avoided or minimized wherever possible.
 Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 Avoid dispersal of spilled material and runoff and contact with



Revision Date: 31.10.2023 Date of last issue: -		Version 2.0	Print Date 05.02.2024
		soil, waterways, drains and sewers.	
European Waste Catalogue	:	08 04 09* waste adhesives and sealants co solvents or other dangerous substances	ontaining organic
Contaminated packaging	:	15 01 10* packaging containing residues of by dangerous substances	or contaminated

#### **SECTION 14: Transport information**

14.1 UN number or ID number		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		
Not regulated as a dangerous good		
14.6 Special precautions for use	r	
Not applicable		ording to IMO instruments

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## Sikaflex<sup>®</sup>-228



Revision Date: 31.10.2023 Date of last issue: -	Version	2.0	Print Date 05.02.2024
International Chemical Weapons Schedules of Toxic Chemicals a		:	Not applicable
REACH Information:	All substances contair - registered by our ups - registered by us, and - excluded from the re - exempted from the re	strea d/or gula	am suppliers, and/or tion, and/or
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
			4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) m-tolylidene diisocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)
REACH - Candidate List of Subs Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances sub (Annex XIV)	ject to authorisation	:	Not applicable
Regulation (EC) No 1005/2009 c plete the ozone layer	on substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on p tants (recast)	ersistent organic pollu-	:	Not applicable
Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving da		nent	t and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 3% w/w

## Sikaflex<sup>®</sup>-228

Print Date 05.02.2024

Revision Date: 31.10.2023 Date of last issue: - Version 2.0

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3% w/w

#### Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Version 2.0



Revision Date: 31.10.2023 Date of last issue: -

> Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### Full text of H-Statements

ŀ	1226	:	Flammable liquid and vapour.
ŀ	H304	:	May be fatal if swallowed and enters airways.
ŀ	H312	:	Harmful in contact with skin.
ŀ	H315	:	Causes skin irritation.
ŀ	H317	:	May cause an allergic skin reaction.
ŀ	H319	:	Causes serious eye irritation.
ŀ	1330	:	Fatal if inhaled.
ŀ	1332	:	Harmful if inhaled.
H	1334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
ŀ	1335	:	May cause respiratory irritation.
ŀ	H336	:	May cause drowsiness or dizziness.
ŀ	H351	:	Suspected of causing cancer.
ŀ	1372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.
ŀ	1373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
ŀ	H411	:	Toxic to aquatic life with long lasting effects.
ŀ	H412	:	Harmful to aquatic life with long lasting effects.
F	Full text of other abbreviatio	ns	
ŀ	Acute Tox.	:	Acute toxicity
ŀ	Aquatic Chronic	:	Long-term (chronic) aquatic hazard
ŀ	Asp. Tox.	:	Aspiration hazard
(	Carc.	:	Carcinogenicity
E	Eye Irrit.	:	Eye irritation
F	-lam. Liq.	:	Flammable liquids
F	Resp. Sens.	:	Respiratory sensitisation
S	Skin Irrit.	:	Skin irritation

## Sikaflex<sup>®</sup>-228

Data of last issue:	Revision Date: 31.10.2023
Date of last issue	Date of last issue: -



Version 2.0

Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first
	list of indicative occupational exposure limit values
PL OEL	: Ordinance of the Minister of Family, Labour and Social Policy
	of 12 June 2018 concerning the highest allowable concentra-
	tions and levels of the agents harmful for health in the work-
	place (Dz.U 2018 pos 1286, with later amendments)
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
PL OEL / NDS	: Maximal Admissible Concentration
PL OEL / NDSch	: Maximal Admissible Temporary Concentration
ADR	: European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL	: International Convention for the Prevention of Pollution from
a =-	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
0.410	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative
Further information	

## Classification of the mixture:Classification procedure:Resp. Sens. 1H334Calculation methodSTOT RE 2H373Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

## Sikaflex<sup>®</sup>-228

Revision Date: 31.10.2023 Date of last issue: - Version 2.0



## 

PL/EN