Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Primer MB Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

| Company name of supplier | : Sika Poland Spółka z o.o. |
|--------------------------|-----------------------------|
| | Karczunkowska 89 |
| | 02-871 Warszawa |
| Telephone | : +48 22 27 28 700 |
| Telefax | : +48 22 27 28 800 |
| E-mail address of person | : EHS@pl.sika.com |
| responsible for the SDS | |

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| Acute toxicity, Category 4 | H302: Harmful if swallowed. |
|---|--|
| Acute toxicity, Category 4 | H332: Harmful if inhaled. |
| Skin corrosion, Sub-category 1B | H314: Causes severe skin burns and eye damage. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Long-term (chronic) aquatic hazard, Cat- egory 3 | H412: Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Revision Date: 18.11.2023 Da



| evision Date: 18.11.2023 Pate of last issue: 08.03.2023 | | Ve | ersion 2.0 | Print Date 05.02.2 |
|--|---|-------------------------------------|---|--|
| Signal word | : | Danger | | |
| Hazard statements | : | H302 + H332 H314 H317 H412 | Harmful if swallowed or if inhaled Causes severe skin burns and e May cause an allergic skin react Harmful to aquatic life with long fects. | ye damage. ion. |
| Supplemental Hazard Statements | : | EUH071 | Corrosive to the respiratory tract | |
| Precautionary statements | : | Prevention: | | |
| | | P261 P273 P280 | Avoid breathing mist or vapours. Avoid release to the environmen Wear protective gloves/ protective eye protection/ face protection. | ıt. |
| | | Response: | | |
| | | P303 + P361 + F | P353 IF ON SKIN (or hair): Take ately all contaminated clothing. F with water. | |
| | | P304 + P340 + F | 2310 IF INHALED: Remove per air and keep comfortable for brea mediately call a POISON CENTI | athing. Im- |
| | | P305 + P351 + F | | e cautiously Remove con- to do. Con- |

Version 2.0

Hazardous components which must be listed on the label:

benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) Amines, polyethylenepoly-, tetraethylenepentamine fraction 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 18.11.2023 Date of last issue: 08.03.2023



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--|---|---|--------------------------|
| benzyl alcohol | 100-51-6 202-859-9 01-2119492630-38- XXXX | Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l | >= 40 - < 60 |
| 3-aminomethyl-3,5,5- trimethylcyclohexylamine | 2855-13-2 220-666-8 01-2119514687-32- XXXX | Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 | >= 10 - < 20 |
| m-phenylenebis(methylamine) | 1477-55-0 216-032-5 01-2119480150-50- XXXX | Acute Tox. 4; H302 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l | >= 10 - < 20 |


Sika[®] Primer MB Part B

Revision Date: 18.11.2023 Date of last issue: 08.03.2023

2,4,6-

<= 15 %

Version 2.0



Acute oral toxicity:

910 mg/kg

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attenda | nce. |
|-------------------------|--|------|
| If inhaled | Move to fresh air. Consult a physician after significant exposure. | |
| In case of skin contact | Take off contaminated clothing and shoes immediat Wash off with soap and plenty of water. Immediate medical treatment is necessary as untrea | |



Sika[®] Primer MB Part B



| wounds from corrosion of the skin heal | |
|---|--|
| ty. | slowly and with difficul- |
| Small amounts splashed into eyes can sue damage and blindness. In the case of contact with eyes, rinse in of water and seek medical advice. Continue rinsing eyes during transport of Remove contact lenses. Keep eye wide open while rinsing. | mmediately with plenty |
| : Do not induce vomiting without medical Rinse mouth with water. Do not give milk or alcoholic beverages Never give anything by mouth to an une | 5. |
| nd effects, both acute and delayed | |
| : Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed inform and symptoms. | nation on health effects |
| Health injuries may be delayed. corrosive effects sensitising effects Harmful if swallowed or if inhaled. | |
| May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns. Corrosive to the respiratory tract. | |
| | sue damage and blindness. In the case of contact with eyes, rinse in of water and seek medical advice. Continue rinsing eyes during transport of Remove contact lenses. Keep eye wide open while rinsing. Do not induce vomiting without medical Rinse mouth with water. Do not give milk or alcoholic beverages Never give anything by mouth to an unerstand effects, both acute and delayed Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed inform and symptoms. Health injuries may be delayed. corrosive effects Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns. |

4.3 indication of any immediate medical attention and special treatment needed

| Treatment : T | Freat symptomatically. |
|---------------|------------------------|
|---------------|------------------------|

SECTION 5: Firefighting measures

| 5.1 Extinguishing media Suitable extinguishing media | : | In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for |
|---|----|---|
| 5.2 Special hazards arising from t | he | extinction. |
| Hazardous combustion prod- ucts | : | No hazardous combustion products are known |



5.3 Advice for firefighters

| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. |
|--|---|--|
| Further information | : | Standard procedure for chemical fires. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, protect | tive | e equipment and emergency procedures | | |
|--|------|---|--|--|
| Personal precautions | : | Use personal protective equipment. Deny access to unprotected persons. | | |
| 6.2 Environmental precautions | | | | |
| Environmental precautions | : | Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. | | |
| 6.3 Methods and material for containment and cleaning up | | | | |
| Methods for cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). | | |

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | : | Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products |
|---|---|---|
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |
| Hygiene measures | : | Handle in accordance with good industrial hygiene and safety |

Sika[®] Primer MB Part B



Revision Date: 18.11.2023 Date of last issue: 08.03.2023

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

| Requirements for storage areas and containers | : | Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations. |
|---|---|--|
| Further information on stor- age stability | : | No decomposition if stored and applied as directed. |
| 7.3 Specific end use(s) Specific use(s) | : | Consult most current local Product Data Sheet prior to any |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters * | Basis * |
|----------------|----------|----------------------------------|---------------------------|---------|
| benzyl alcohol | 100-51-6 | NDS | 240 mg/m3 | PL OEL |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

use.

Personal protective equipment

| Eye/face protection | : | Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection. |
|--------------------------|---|--|
| Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. |
| | | Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, |

Sika[®] Primer MB Part B

Print Date 05.02.2024

| Revision Date: 18.11.2023 |
|--------------------------------|
| Date of last issue: 08.03.2023 |

| | long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. | | |
|---------------------------------|--|--|--|
| Respiratory protection : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas. | | |
| Environmental exposure controls | | | |
| General advice : | Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. | | |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state Colour | : | liquid light yellow |
|---|-----|------------------------|
| Odour | : | amine-like |
| Melting point/range / Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper/lower flammability or e | axe | losive limits |
| Upper explosion limit / Up- per flammability limit | • | |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Flash point | : | > 101 °C |

Sika[®] Primer MB Part B

Revision Date: 18.11.2023 Date of last issue: 08.03.2023



| | | Method: closed cup |
|--|---|------------------------------|
| Auto-ignition temperature | : | ca. 420 °C |
| Decomposition temperature | : | No data available |
| рН | : | > 11 Concentration: 100 % |
| Viscosity | | |
| Viscosity, dynamic | : | ca. 12 mPa.s (20 °C) |
| Viscosity, kinematic | : | > 7 - < 20,5 mm2/s (40 °C) |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Partition coefficient: n- octanol/water | : | No data available |
| Vapour pressure | : | 0,07 hPa |
| Density | : | ca. 1,018 g/cm3 (20 °C) |
| Relative vapour density | : | No data available |
| Particle characteristics | : | No data available |
| | | |

Version 2.0

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Print Date 05.02.2024

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0

10.4 Conditions to avoid

Conditions to avoid

: No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or if inhaled.

Components:

| benzyl alcohol: | | | | |
|---|------|---|--|--|
| Acute oral toxicity | : | LD50 Oral (Rat): 1.620 mg/kg | | |
| | | Acute toxicity estimate: 1.620 mg/kg Method: Calculation method | | |
| Acute inhalation toxicity | : | LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist | | |
| | | Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method | | |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine: | | | | |
| Acute oral toxicity | : | Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008 | | |
| | | LD50 Oral (Rat): 1.030 mg/kg | | |
| Acute inhalation toxicity | : | LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist | | |
| Acute dermal toxicity | : | LD50 Dermal (Rabbit): > 2.000 mg/kg | | |
| | | LD50 (Rabbit): > 2.000 - 5.000 mg/kg | | |
| m-phenylenebis(methylami | ne): | | | |
| Acute oral toxicity | : | LD50 Oral (Rat): 930 mg/kg | | |

Sika[®] Primer MB Part B

Revision Date: 18.11.2023

Date of last issue: 08.03.2023

3 Version 2.0



| | Acute toxicity estimate: 930 mg/kg Method: Calculation method |
|--------------------------------|--|
| Acute inhalation toxicity | : LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract. |
| | Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method |
| Acute dermal toxicity | : LD50 Dermal (Rat): > 3.100 mg/kg |
| Amines, polyethylenepoly-, te | etraethylenepentamine fraction: |
| | : LD50 Oral (Rat): 1.716 mg/kg |
| | Acute toxicity estimate: 1.716 mg/kg Method: Calculation method |
| Acute dermal toxicity | : LD50 Dermal (Rat): 1.465 mg/kg |
| | Acute toxicity estimate: 1.465 mg/kg Method: Calculation method |
| 2,4,6-tris(dimethylaminometh | yl)phenol: |
| Acute oral toxicity | : LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 |
| 2,2,4(or 2,4,4)-trimethylhexan | e-1,6-diamine: |
| Acute oral toxicity | : LD50 Oral (Rat): 910 mg/kg |
| | Acute toxicity estimate: 910 mg/kg Method: Calculation method |
| Skin corrosion/irritation | |
| Causes severe burns. | |
| Components: | |
| 2,4,6-tris(dimethylaminometh | |
| Species | : Rabbit |
| Assessment Method | : Corrosive : OECD Test Guideline 404 |
| Assessment | : irritating |
| Remarks | : Annex VI - Harmonised REGULATION (EC) No 1272/2008 |
| | |

Sika[®] Primer MB Part B

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0



Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

| Species Assessment | - | Rabbit Causes serious eye damage. |
|-----------------------|---|---|
| Assessment Remarks | | irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008 |

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0



SECTION 12: Ecological information

| 12.1 Toxicity | | | | | | |
|--|---|--|--|--|--|--|
| Components: | | | | | | |
| benzyl alcohol: | | | | | | |
| Toxicity to fish : | LC50 (Fish): > 100 mg/l Exposure time: 96 h | | | | | |
| Toxicity to daphnia and other : aquatic invertebrates | EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h | | | | | |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine: | | | | | | |
| Toxicity to algae/aquatic : plants | ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h | | | | | |
| | NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h | | | | | |
| m-phenylenebis(methylamine): | | | | | | |
| Toxicity to fish : | LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h | | | | | |
| Toxicity to daphnia and other : aquatic invertebrates | EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h | | | | | |
| 2,4,6-tris(dimethylaminomethyl |)phenol: | | | | | |
| Toxicity to algae/aquatic : plants | EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l Exposure time: 72 h | | | | | |
| 2,2,4(or 2,4,4)-trimethylhexane- | 1.6-diamine: | | | | | |
| Toxicity to algae/aquatic : plants | | | | | | |
| Toxicity to fish (Chronic tox- : icity) | LC50: 174 mg/l Exposure time: 48 h Species: Leuciscus idus (Golden orfe) | | | | | |
| 12.2 Persistence and degradability No data available | | | | | | |
| 12.3 Bioaccumulative potential No data available | | | | | | |

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0



12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

| Assessment | : The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|----------------------------|---|
| 12.7 Other adverse effects | |

Product:

| Additional ecological infor- : mation | An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects. |
|---------------------------------------|---|
| | Harmful to aquatic life with long lasting effects. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| Product | : | The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |
|--------------------------|---|---|
| European Waste Catalogue | : | 08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances |
| Contaminated packaging | : | 15 01 10* packaging containing residues of or contaminated by dangerous substances |
| | | |

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0



SECTION 14: Transport information

| 14.1 UN number or ID number | | |
|---|---|---|
| ADR | : | UN 1760 |
| IMDG | : | UN 1760 |
| ΙΑΤΑ | : | UN 1760 |
| 14.2 UN proper shipping name | | |
| ADR | : | CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine)) |
| IMDG | : | CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine)) |
| ΙΑΤΑ | : | Corrosive liquid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine)) |
| 14.3 Transport hazard class(es) | | |
| | | Class Subsidiary risks |
| ADR | : | 8 |
| IMDG | : | 8 |
| ΙΑΤΑ | : | 8 |
| 14.4 Packing group | | |
| ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code | : | II C9 80 8 (E) |
| IMDG Packing group Labels EmS Code | : | II 8 F-A, S-B |
| IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels | : | 855 Y840 II Corrosive |
| IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) | : | 851 Y840 |

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0



Packing group Ш ÷ Labels Corrosive 14.5 Environmental hazards ADR Environmentally hazardous no IMDG Marine pollutant no IATA (Passenger) Environmentally hazardous no IATA (Cargo) Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 75, 3 REACH - Candidate List of Substances of Very High : None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-: Not applicable

Sika[®] Primer MB Part B

Print Date 05.02.2024

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0

plete the ozone layer

| Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast) | : | Not applicable |
|--|---|----------------|
| Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals | : | Not applicable |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

| Volatile organic compounds | | Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 48% w/w |
|----------------------------|--|--|
| | | Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 48% w/w |

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Sika[®] Primer MB Part B



Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| H302 | : | Harmful if swallowed. | | | | | |
|----------------------------------|---|--|--|--|--|--|--|
| H312 | : | Harmful in contact with skin. | | | | | |
| H314 | : | Causes severe skin burns and eye damage. | | | | | |
| H317 | : | May cause an allergic skin reaction. | | | | | |
| H318 | : | Causes serious eye damage. | | | | | |
| H319 | : | Causes serious eye irritation. | | | | | |
| H332 | : | Harmful if inhaled. | | | | | |
| H411 | : | Toxic to aquatic life with long lasting effects. | | | | | |
| H412 | : | Harmful to aquatic life with long lasting effects. | | | | | |
| Full text of other abbreviations | | | | | | | |
| Acute Tox. | | Acute toxicity | | | | | |
| | • | | | | | | |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard | | | | | |
| Eve Dam. | : | Serious eve damage | | | | | |

Sika[®] Primer MB Part B

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Print Date 05.02.2024

Version 2.0

| Eye Irrit. Skin Corr. Skin Sens. PL OEL | | Eye irritation Skin corrosion Skin sensitisation Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentra- tions and levels of the agents harmful for health in the work- place (Dz.U 2018 pos 1286, with later amendments) |
|--|---|---|
| PL OEL / NDS | : | Maximal Admissible Concentration |
| ADR | : | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| CAS | | Chemical Abstracts Service |
| DNEL | : | Derived no-effect level |
| EC50 | : | Half maximal effective concentration |
| GHS | : | Globally Harmonized System |
| ΙΑΤΑ | : | International Air Transport Association |
| IMDG | : | International Maritime Code for Dangerous Goods |
| LD50 | : | Median lethal dosis (the amount of a material, given all at |
| | | once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation |
| | | period) |
| MARPOL | - | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |
| PBT | : | Persistent, bioaccumulative and toxic |
| PNEC | : | Predicted no effect concentration |
| REACH | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency |
| SVHC | : | Substances of Very High Concern |
| vPvB | : | Very persistent and very bioaccumulative |

Further information

| Classification of the | Classification procedure: | |
|-----------------------|---------------------------|--------------------|
| Acute Tox. 4 | H302 | Calculation method |
| Acute Tox. 4 | H332 | Calculation method |
| Skin Corr. 1B | H314 | Calculation method |
| Eye Dam. 1 | H318 | Calculation method |
| Skin Sens. 1 | H317 | Calculation method |
| Aquatic Chronic 3 | H412 | Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

П

Sika[®] Primer MB Part B

Revision Date: 18.11.2023 Date of last issue: 08.03.2023 Version 2.0



Changes as compared to previous version !

PL/EN