

Revision Date: 06.01.2024 Date of last issue: - Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaBond[®]-54 Parquet

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

: Sika Poland Spółka z o.o.
Karczunkowska 89
02-871 Warszawa
: +48 22 27 28 700
: +48 22 27 28 800
: EHS@pl.sika.com

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Additional Labelling

EUH208	Contains 4,4'-methylenediphenyl diisocyanate, m-tolylidene diisocyanate,
	Hardener LI (Isophoronedialdimine), Hardener LH (1,6-Hexanedialdimine).
	May produce an allergic reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SikaBond[®]-54 Parquet

Print Date 05.02.2024

Revision Date: 06.01.2024 Date of last issue: - Version 2.0

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponents			
Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		
Urea,N,N"-(methylenedi-4,1-	77703-56-1	Aquatic Chronic 4;	>= 2,5 - < 5
phenylene)bis[N'-butyl-	416-600-4	H413	
	01-0000016345-72-		
	XXXX		
Hardener LI (Isophoronedial-	932742-30-8	Skin Sens. 1B; H317	>= 0,5 - < 1
dimine)	700-071-4	Aquatic Chronic 3;	
	01-2119880654-28-	H412	
	XXXX		
Hardener LH (1,6-	613222-52-9	Eye Dam. 1; H318	>= 0,5 - < 1
Hexanedialdimine)	479-930-8	Skin Sens. 1B; H317	
,	01-2119880653-30-	STOT SE 3; H335	
	XXXX	(Respiratory system)	

Revision Date: 06.01.2024 Date of last issue: - Version 2.0



4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334	< 0,1
		Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373	
		specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	
		Acute toxicity esti- mate Acute inhalation tox-	
		icity (dust/mist): 1,5 mg/l	
m-tolylidene diisocyanate	26471-62-5 247-722-4 01-2119454791-34- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H314 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412	>= 0,025 - < 0,1
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (vapour): 0,107 mg/l	



Revision Date: 06.01.2024 Date of last issue: - Version 2.0

Substances with a workplace exposure limit :		
103-23-1	>= 5 - < 10	
203-090-1		
01-2119439699-19-		
XXXX		
	103-23-1 203-090-1 01-2119439699-19-	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	No hazards which require special first aid measures.	
If inhaled	:	Move to fresh air.	
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.	
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.	
4.2 Most important symptoms and effects, both acute and delayed			
Symptoms	:	See Section 11 for more detailed information on health effects and symptoms.	
Risks	:	No known significant effects or hazards.	

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media	In case of fire, use water/water spray/water jet/carbon diox-
Suitable extinguishing media :	ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from the Hazardous combustion prod- : ucts	e substance or mixture No hazardous combustion products are known

Jika ®
Print Date 05.02.2024

Revision Date: 06.01.2024	Version 2.0	Print Date 05.02.2024
Date of last issue: -		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protect Personal precautions		e equipment and emergency procedures For personal protection see section 8.
6.2 Environmental precautions Environmental precautions	:	No special environmental precautions required.
6.3 Methods and material for co	ntai	nment and cleaning up
Methods for cleaning up	:	Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	For personal protection see section 8. No special handling advice required. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	When using do not eat or drink. When using do not smoke.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Advice on common storage	:	No special restrictions on storage with other products.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.

Sika ®
Print Date 05.02.2024

Revision Date: 06.01.2024	Version 2.0	Print Date 05.02.2
Date of last issue: -		

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
bis(2-ethylhexyl) adipate	103-23-1	NDS	400 mg/m3	PL OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	NDS	0,03 mg/m3	PL OEL
		NDSch	0,09 mg/m3	PL OEL
m-tolylidene diisocyanate	26471-62-5	NDS	0,007 mg/m3	PL OEL
		NDSch	0,021 mg/m3	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment					
Eye/face protection	:	Safety glasses			
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.			
		Butyl rubber/nitrile rubber gloves (> 0,1 mm) Recommended: Butyl rubber/nitrile rubber gloves.			
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.			
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.			

Print Date 05.02.2024

Revision Date: 06.01.2024 Date of last issue: - Version 2.0

Environmental exposure controls

General advice

: No special environmental precautions required.

°C)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste brown
Odour	:	slight
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable
Viscosity Viscosity, dynamic	:	ca. 26.000 mPa.s (20
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

Print Date 05.02.2024

Revision Date: 06.01.2024	
Date of last issue: -	

Solubility/ioc)

Version 2.0

Water solubility	: insoluble
Partition coefficient: n- octanol/water	: No data available
Vapour pressure	: 0,01 hPa
Density	: ca. 1,3 g/cm3 (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Print Date 05.02.2024

Revision Date: 06.01.2024 Date of last issue: - Version 2.0

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

<u>components:</u>		
Urea,N,N"-(methylenedi-4,1-	phe	enylene)bis[N'-butyl-:
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402
Hardener LI (Isophoronedia	ldiı	nine):
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
4,4'-methylenediphenyl diisc	су	anate:
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method
m-tolylidene diisocyanate:		
Acute inhalation toxicity	:	LC50 (Rat): 0,107 mg/l Exposure time: 4 h Test atmosphere: vapour
		Acute toxicity estimate: 0,107 mg/l Test atmosphere: vapour Method: Calculation method
bis(2-ethylhexyl) adipate:		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,7 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Revision Date: 06.01.2024 Date of last issue: - Version 2.0



Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l
		Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l



Revision Date: 06.01.2024 Date of last issue: -		Version 2.0	Print Date 05.02
aquatic invertebrates		Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater gree 100 mg/l Exposure time: 72 h	en alga)): >
Hardener LI (Isophoronedia	aldiı	mine):	
Toxicity to fish		LC50 (Fish): 87,2 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae) Exposure time: 72 h): 180,4 mg/l
bis(2-ethylhexyl) adipate:			
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 500 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Scenedesmus quadricauda (Green algae) Exposure time: 72 h)): > 500 mg/l
12.2 Persistence and degradabil No data available	ity		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	sse	ssment	
Product:			
Assessment	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher.	: (PBT), or
12.6 Endocrine disrupting prope	ertie	s	
Product:			
Assessment	:	The substance/mixture does not contain componered to have endocrine disrupting properties acc REACH Article 57(f) or Commission Delegated re (EU) 2017/2100 or Commission Regulation (EU)	ording to egulation

levels of 0.1% or higher.

Print Date 05.02.2024

Revision Date: 06.01.2024 Date of last issue: - Version 2.0

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		



Revision Date: 06.01.2024 Date of last issue: -

Version 2.0

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards Not regulated as a danger	ous go	od
14.6 Special precautions for Not applicable	user	
14.7 Maritime transport in bu Not applicable for product		-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

	 registered by our upstream suppliers, and/or registered by us, and/or excluded from the regulation, and/or exempted from the registration. 		
REACH - Restrictions on the m the market and use of certain of mixtures and articles (Annex X	langerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered Number on list 75

All substances contained in our Products are

4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) m-tolylidene diisocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

considered:

REACH - Candidate List of Substances of Very High : None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation : Not applicable (Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-: Not applicable

SikaBond[®]-54 Parquet

Print Date 05.02.2024

Revision Date: 06.01.2024 Date of last issue: - Version 2.0

plete the ozone layer

of dangerous chemicals

Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import	:	Not applicable

-

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

SikaBond[®]-54 Parquet



Revision Date: 06.01.2024 Date of last issue: - Version 2.0

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	 May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

SikaBond®-54 Parquet

Revision Date: 06.01.2024 Date of last issue: - Version 2.0



Full text of other abb	previations
------------------------	-------------

Acute Tox. :	Acute toxicity
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Carc. :	Carcinogenicity
Eye Dam. :	Serious eye damage
Eye Irrit. :	Eye irritation
Resp. Sens. :	Respiratory sensitisation
Skin Irrit. :	Skin irritation
Skin Sens. :	Skin sensitisation
STOT RE :	Specific target organ toxicity - repeated exposure
STOT SE :	Specific target organ toxicity - single exposure
PL OEL :	Ordinance of the Minister of Family, Labour and Social Policy
•	of 12 June 2018 concerning the highest allowable concentra-
	tions and levels of the agents harmful for health in the work-
	place (Dz.U 2018 pos 1286, with later amendments)
PL OEL / NDS :	Maximal Admissible Concentration
PL OEL / NDSch :	Maximal Admissible Concentration Maximal Admissible Temporary Concentration
ADR :	European Agreement concerning the International Carriage of
ADIX .	Dangerous Goods by Road
CAS :	Chemical Abstracts Service
DNEL :	Derived no-effect level
EC50 :	Half maximal effective concentration
GHS :	Globally Harmonized System
IATA :	International Air Transport Association
IMDG :	International Maritime Code for Dangerous Goods
LD50 :	Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50 :	Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL :	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL :	Occupational Exposure Limit
PBT :	Persistent, bioaccumulative and toxic
PNEC :	Predicted no effect concentration
REACH :	Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC :	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

Further information

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

SikaBond[®]-54 Parquet

Revision Date: 06.01.2024 Date of last issue: - Version 2.0



PL/EN