

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.
Karczunkowska 89
02-871 Warszawa
Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com
responsible for the SDS

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 4	H413: May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878


Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H302 + H332 Harmful if swallowed or if inhaled. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H413 May cause long lasting harmful effects to aquatic life.
Supplemental Hazard Statements	:	EUH071 Corrosive to the respiratory tract.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Sika-Adduct PPDXAF-P (epoxy amine adduct, polymer)
benzyl alcohol
m-phenylenebis(methylamine)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Sika-Adduct PPDXAF-P (epoxy amine adduct, polymer)	3058684-94-6 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 40 - < 60
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg	>= 25 - < 40
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity estimate Acute oral toxicity: 930 mg/kg Acute inhalation toxicity (dust/mist): 1,34 mg/l	>= 5 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

ethanol	64-17-5 200-578-6 01-2119457610-43-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 <hr/> specific concentration limit Eye Dam. 2; H319 >= 50 %	>= 2,5 - < 5
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 <hr/> Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg	>= 2,5 - < 5
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12-XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns. Corrosive to the respiratory tract. Health injuries may be delayed. corrosive effects sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: Water High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	: Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion products	: No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.
Further information	: Use water spray to cool unopened containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Recommended storage temperature : > 5 - < 30 °C
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
benzyl alcohol	100-51-6	NDS	240 mg/m ³	PL OEL
ethanol	64-17-5	NDS	1.900 mg/m ³	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

- facturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Colour : brown
- Odour : characteristic
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : ca. 150 °C
- Flammability (solid, gas) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

Upper/lower flammability or explosive limits

Upper explosion limit / Up-
per flammability limit : 13 %(V)

Lower explosion limit /
Lower flammability limit : 1,3 %(V)

Flash point : ca. 45 °C
Method: closed cup

Auto-ignition temperature : 436 °C

Decomposition temperature : No data available

pH : ca. 11
Concentration: 100 %

Viscosity

Viscosity, dynamic : ca. 2.500 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-
octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,062 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

Explosives : Not explosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

Metal corrosion rate : Not corrosive to metals

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or if inhaled.

Components:

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

m-phenylenebis(methylamine):

- Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg
Acute toxicity estimate: 930 mg/kg
Method: Calculation method
- Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.
Acute toxicity estimate: 1,34 mg/l
Test atmosphere: dust/mist
Method: Calculation method
- Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

- Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg
Remarks: Harmful if swallowed.
Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Polyoxypropylene diamine:

- Acute oral toxicity : LD50 Oral (Rat): 2.880 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

- Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404
- Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

- Species : Rabbit
Assessment : Causes serious eye damage.
- Assessment : irritating

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h

Polyoxypropylene diamine:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 80 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 2924
IMDG : UN 2924

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025
Date of last issue: -

Version 1.1

Print Date 28.03.2025

IATA : UN 2924

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(m-phenylenebis(methylamine), ethanol)

IMDG : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(m-phenylenebis(methylamine), ethanol)

IATA : Flammable liquid, corrosive, n.o.s.
(m-phenylenebis(methylamine), ethanol)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	8
IMDG	: 3	8
IATA	: 3	8

14.4 Packing group

ADR
Packing group : III
Classification Code : FC
Hazard Identification Number : 38
Labels : 3 (8)
Tunnel restriction code : (D/E)

IMDG
Packing group : III
Labels : 3 (8)
EmS Code : F-E, S-C

IATA (Cargo)
Packing instruction (cargo aircraft) : 365
Packing instruction (LQ) : Y342
Packing group : III
Labels : Flammable Liquids, Corrosive

IATA (Passenger)
Packing instruction (passenger aircraft) : 354
Packing instruction (LQ) : Y342
Packing group : III
Labels : Flammable Liquids, Corrosive

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 38,62% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 38,62% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H302	:	Harmful if swallowed.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
PL OEL	:	Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments)
PL OEL / NDS	:	Maximal Admissible Concentration
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H302
Acute Tox. 4	H332
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 4	H413

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-392 ECF (Formerly MTop BC 378 AS) Part B



Revision Date: 21.03.2025

Version 1.1

Print Date 28.03.2025

Date of last issue: -

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

PL / EN