

Version 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikalastic[®]-641

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyuretha

: Polyurethane coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	-

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Cat-	H317: May cause an allergic skin reaction. H412: Harmful to aquatic life with long lasting ef-			
egory 3	fects.			

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 H319 H412	May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting ef-

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic®-6/1

Sikalastic[®]-641



Revision Date: 27.05.2023 Date of last issue: - Version 1.1

Precautionary statements :	Prevention: P261 P273 P280	Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
	Response:	
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
	P337 + P313	If eye irritation persists: Get medical advice/ attention.
	P362 + P364	Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)) Hardener MI (Isophoronedi(morpholinoaldimine)) Isophorondiisocyanate homopolymer 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Pentamethyl piperidylsebacate 4-morpholinecarbaldehyde

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 27.05.2023 Date of last issue: -

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenyl tolyl phosphate MCS	Not Assigned 945-730-9 01-2119511174-52- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 10 - < 20
Hardener MTJ (Polyoxypropylene- tri(morpholinoaldimine))	1379822-00-0 700-879-7 01-2120039480-63- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 5 - < 10
propylene carbonate	108-32-7 203-572-1 01-2119537232-48- XXXX	Eye Irrit. 2; H319	>= 5 - < 10
Hardener MI (Isopho- ronedi(morpholinoaldimine)) Contains: 2,2-Dimethyl-3-(4- morpholinyl)propanal <= 7 %	1217271-02-7 700-584-3 01-2119941782-33- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
Isophorondiisocyanate homopol- ymer Contains: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate <= 0,49 %	53880-05-0 931-312-3 500-125-5 01-2119488734-24- XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 2,5 - < 5
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 2,5

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikalastic[®]-641

Revision Date: 27.05.2023 Date of last issue: -



Versio	n 1	1
1010		

3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411	>= 0,25 - < 0,5
		specific concentration limit Resp. Sens. 1; H334 >= 0.5% Skin Sens. 1; H317 >= 0.5%	
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 0,031 mg/l	
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12- XXXX	Skin Sens. 1; H317	< 1
salicylic acid	69-72-7 200-712-3 01-2119486984-17- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	< 1
		Acute toxicity esti- mate	
		Acute oral toxicity: 891 mg/kg	



Revision Date: 27.05.2023 Date of last issue: - Version 1.1

Substances with a workplace ex	xposure limit :	
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms	and e	ffects, both acute and delayed
Symptoms	:	Allergic reactions Excessive lachrymation See Section 11 for more detailed information on health effects and symptoms.
Risks	:	irritant effects sensitising effects
		May cause an allergic skin reaction. Causes serious eye irritation.
4.3 Indication of any immediate	e mec	lical attention and special treatment needed
Treatment	:	Treat symptomatically.



 Revision Date: 27.05.2023
 Version 1.1
 Print Date 05.02.20

 Date of last issue:

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth-
	ma, allergies, chronic or recurrent respiratory disease should



Revision Date: 27.05.2023 Date of last issue: -	Version 1.1	Print Date 05.02
	not be employed in any process in which the used. Smoking, eating and drinking should be pr plication area. Follow standard hygiene measures when he products	ohibited in the ap-
Advice on protection against fire and explosion	Normal measures for preventive fire protect	xtion.
Hygiene measures	 Handle in accordance with good industrial practice. When using do not eat or drink. V smoke. Wash hands before breaks and at 	Vhen using do not
7.2 Conditions for safe storage, ir	cluding any incompatibilities	
Requirements for storage areas and containers	 Keep container tightly closed in a dry and y place. Containers which are opened must sealed and kept upright to prevent leakage ance with local regulations. 	be carefully re-
Further information on stor- age stability	: No decomposition if stored and applied as	directed.
7.3 Specific end use(s)		
Specific use(s)	: Consult most current local Product Data Sl use.	neet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	NDS (inhalable fraction)	10 mg/m3	PL OEL
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC
	Further inform	ation: Identifies the	possibility of signi	ficant uptake
	through the sk		. , ,	
		TWA	50 ppm 275 mg/m3	2000/39/EC
		NDS	260 mg/m3	PL OEL
	Further inform	ation: Skin		
		NDSch	520 mg/m3	PL OEL
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	NDS	0,04 mg/m3	PL OEL

Print Date 05.02.2024

Revision Date: 27.05.2023 Date of last issue: - Version 1.1

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment					
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.				
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.				
Environmental exposure controls					
General advice :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic[®]-641

Print Date 05.02.2024

Revision Date: 27.05.2023 Date of last issue: -	Version 1.1	Print Date 05.02.2024
Physical state Colour	: liquid : dark grey	
Odour	: mild	
Melting point/range / Freezing point	: No data available	
Boiling point/boiling range	: No data available	
Flammability (solid, gas)	: No data available	
Upper/lower flammability or	xplosive limits	
Upper explosion limit / Up- per flammability limit	: No data available	
Lower explosion limit / Lower flammability limit	: No data available	
Flash point	: 150 °C Method: closed cup	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in water)	
Viscosity		
Viscosity, dynamic	: ca. 4.000 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,04 hPa	
Density	: ca. 1,427 g/cm3 (20 °C)	0/10

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic®-641

Sikalastic[®]-641



Revision Date: 27.05.2023 Date of last issue: - Version 1.1

Relative vapour density	:	No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Diphenyl tolyl phosphate MCS:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

Acute oral toxicity	:	LD50 Oral (Rat): > 2.001 mg/kg
---------------------	---	--------------------------------

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic[®]-641

Print Date 05.02.2024

Revision Date: 27.05.2023	
Date of last issue: -	

Version 1.1

Hardener MI (Isophoronedi(Acute oral toxicity	mo :	rpholinoaldimine)): LD50 Oral (Rat): > 2.001 mg/kg		
2-methoxy-1-methylethyl ac	eta	te:		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg		
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg		
3-isocyanatomethyl-3,5,5-tr	ime	thylcyclohexyl isocyanate:		
Acute oral toxicity	:	LD50 Oral (Rat): 4.814 mg/kg		
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
		Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method		
Acute dermal toxicity	:	LD50 Dermal (Rat): > 7.000 mg/kg		
Pentamethyl piperidylsebac	ate	:		
Acute oral toxicity	:	LD50 Oral (Rat): 3.230 mg/kg		
salicylic acid:		LDEQ Oral (Dat): 801 mallia		
Acute oral toxicity	:	LD50 Oral (Rat): 891 mg/kg		
		Acute toxicity estimate: 891 mg/kg Method: Calculation method		
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg		
Skin corrosion/irritation Not classified based on availa	able	information.		
Components:				
Hardener MI (Isophoronedi(mo	rpholinoaldimine)):		
Method Result	:	Regulation (EC) No. 440/2008, Annex, B.46 Skin irritation		
Serious eye damage/eye irritation Causes serious eye irritation.				
Components:				
Hardener MI (Isophoronedi(morpholinoaldimine)):				
Method	:	OECD Test Guideline 405		
untry PL 10000015982				

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikelastic® 641

Sikalastic[®]-641

Print Date 05.02.2024

Revision Date: 27.05.2023 Date of last issue: - Version 1.1

Result

: Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Hardener MI (Isophoronedi(morpholinoaldimine)):

Method	: Regulation (EC) No. 440/2008, Annex, B.42 (LLNA)	ļ
Result	: May cause sensitisation by skin contact.	

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

2

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikalastic[®]-641



Revision Date: 27.05.2023 Date of last issue: -		Version 1.1	Print Date 05.02.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 45,1 mg/l Exposure time: 48 h	
		NOEC (Daphnia magna (Water flea)): 12,5 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green al mg/l Exposure time: 72 h	gae)): 1,56
Hardener MI (Isophoronedi(r	noi	rpholinoaldimine)):	
		EC50 (Daphnia magna (Water flea)): 40,2 mg/l Exposure time: 48 h	
		NOEC (Daphnia magna (Water flea)): 17,1 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green al Exposure time: 72 h	gae)): 89 mg/l
Pentamethyl piperidylsebaca	ate	:	
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h	
M-Factor (Acute aquatic tox- icity)	:	1	
M-Factor (Chronic aquatic toxicity)	:	1	
12.2 Persistence and degradabili No data available	ty		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	se	ssment	
Product:			
Assessment	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	: (PBT), or

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components consid-



Revision Date: 27.05.2023 Date of last issue: -	Version 1.1	Print Date 05.02.2
	ered to have endocrine disrupting prope REACH Article 57(f) or Commission Del (EU) 2017/2100 or Commission Regulat levels of 0.1% or higher.	egated regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	: An environmental hazard cannot be exc unprofessional handling or disposal. Harmful to aquatic life with long lasting e	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Contaminated packaging	 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.2 UN proper shipping name					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			

Jika ®
Print Date 05.02.2024

Revision Date: 27.05.2023	
Date of last issue: -	

Version 1.1

ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1	afety, health and environmental regulations/legislation EACH - Restrictions on the manufacture, placing on : e market and use of certain dangerous substances, ixtures and articles (Annex XVII)		Specific for the substance or mixture Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
			3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74)
	International Chemical Weapons Convention (CWC) : Schedules of Toxic Chemicals and Precursors		Not applicable
	REACH - Candidate List of Substances of Very High : Concern for Authorisation (Article 59).		None of the components are listed (=> 0.1 %).
	REACH - List of substances subject to authorisation : (Annex XIV)		Not applicable
	Regulation (EC) No 1005/2009 on substances that deplete the ozone layer		Not applicable

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic®_6/1

Sikalastic[®]-641

Print Date 05.02.2024

Revision Date: 27.05.2023
Date of last issue: -

Version 1.1

Regulation (EU) 2019/1021 o tants (recast)	n persistent organic pollu-	:	Not applicable
Regulation (EC) No 649/2012 ment and the Council concerr of dangerous chemicals	•	:	Not applicable
REACH Information:	All substances contair		

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not	app	licable
	~PP	neasie

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 4,98% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 12,03% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Version 1.1



Revision Date: 27.05.2023 Date of last issue: -

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. 2005 Nr. 259, item 2173 with later amendments).

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended).

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450 with later amendments).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Revision Date: 27.05.2023 Date of last issue: - Version 1.1




SECTION 16: Other information

Full text of H-Statements		
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361d	:	Suspected of damaging the unborn child.
H361f	:	Suspected of damaging fertility.
H400	:	Very toxic to aquatic life.
H410		Very toxic to aquatic life with long lasting effects.
H411		Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
	•	namma to aquatio ino with long labiling offorto.
Full text of other abbreviation Acute Tox.	ns	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
•	:	
Aquatic Chronic	÷	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
PL OEL	:	Poland. Occupational exposure limits for airborne toxic sub-
		stances
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
PL OEL / NDS	:	Maximal Admissible Concentration
PL OEL / NDSch	:	Maximal Admissible Temporary Concentration
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	÷	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
	·	once, which causes the death of 50% (one half) of a group of
		test animals)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikalastic[®]-641



Further information

Classification of the	Classification procedure:	
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN

