

Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

2



Revision Date: 26.01.2024 Date of last issue: 22.03.2023	Ve	Print Date 05.02	
Hazard statements :	H302 H314 H317 H412	Harmful if swallowed. Causes severe skin burns and e May cause an allergic skin react Harmful to aquatic life with long fects.	tion.
Precautionary statements :	Prevention:		
,	P261 P273 P280	Avoid breathing mist or vapours Avoid release to the environmer Wear protective gloves/ protective eye protection/ face protection.	nt.
	Response:		
	P303 + P361 + F	P353 IF ON SKIN (or hair): Tak ately all contaminated clothing. I with water.	
	P304 + P340 + F	P310 IF INHALED: Remove per air and keep comfortable for bre mediately call a POISON CENT	athing. Im-
	P305 + P351 + F		e cautiously Remove con- to do. Con-

Hazardous components which must be listed on the label:

Adduct XA-P (epoxy amine adduct, polymer) 3-aminomethyl-3,5,5-trimethylcyclohexylamine N-benzylethylenediamine m-phenylenebis(methylamine)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B

Print Date 05.02.2024

Revision Date: 26.01.2024 Date of last issue: 22.03.2023

Version 2.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	>= 25 - < 40
Adduct XA-P (epoxy amine ad- duct, polymer)	110839-13-9 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 20 - < 25
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 	>= 20 - < 25
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12- XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 10 - < 20
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 3 - < 5



Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0

N-benzylethylenediamine	4152-09-4 223-984-5 01-2120822346-58- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute oral toxicity: 300,03 mg/kg	>= 3 - < 5
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity:	>= 0,25 - < 0,5
		Acute of a toxicity. 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 26.01.2024 Date of last issue: 22.03.2023		Version 2.0	Print Date 05.0
		Continue rinsing eyes during transport to hospita Remove contact lenses. Keep eye wide open while rinsing.	Ι.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	s person.
4.2 Most important symptoms ar	nd (effects, both acute and delayed	
Symptoms	:	Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects	
		Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.	
4.3 Indication of any immediate I	ne	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.



Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0

Keep in suitable, closed containers for disposal.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.			
6.2 Environmental precautions					
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			
6.3 Methods and material for co	ontai	nment and cleaning up			
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).			

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	•	
Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage	, inc	luding any incompatibilities

Revision Date: 26.01.2024 Date of last issue: 22.03.2023		Version 2.0	Print Date 05.02.2024
		ance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and applied as dire	cted.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet use.	prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
benzyl alcohol	100-51-6	NDS	240 mg/m3	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator.

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B

Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0



organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

Information on basic physical	and	I chemical propertie
Physical state Colour	:	liquid colourless
Odour	:	amine-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
	1	a ali ya Umalita
Upper/lower flammability or o Upper explosion limit / Up- per flammability limit	•	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	ca. 8,5 (20 °C)

9.1 Information on basic physical and chemical properties

Print Date 05.02.2024

Revision Date: 26.01.2024
Date of last issue: 22.03.2023

Version 2.0

	Concentration: 100 %
Viscosity	
Viscosity, dynamic	: ca. 225 mPa.s (20 °C)
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n- octanol/water	: No data available
Vapour pressure	: 0,07 hPa
Density	: ca. 1,02 g/cm3 (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions					
Hazardous reactions	:	Stable under recommended storage conditions.			
10.4 Conditions to avoid					
Conditions to avoid	:	No data available			
10.5 Incompatible materials					
Materials to avoid	:	No data available			

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B

Revision Date: 26.01.2024 Date of last issue: 22.03.2023

Acute toxicity

Version 2.0



10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Harmful if swallowed.		
Components:		
benzyl alcohol:		
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
		Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method
Adduct XA-P (epoxy amine	ado	duct, polymer):
Acute oral toxicity	:	LD50 Oral (Rat): 300 - 2.000 mg/kg Method: OECD Test Guideline 423
3-aminomethyl-3,5,5-trimetl	hylc	cyclohexylamine:
Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg
Polyoxypropylene diamine: Acute oral toxicity	:	LD50 Oral (Rat): 2.880 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



ision Date: 26.01.2024 e of last issue: 22.03.2023		Version 2.0	Print Date 0
Acute oral toxicity	:	LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008	
N-benzylethylenediamine:			
Acute oral toxicity	:	LD50 Oral (Rat): > 300 - < 2.000 mg/kg	
		Acute toxicity estimate: 300,03 mg/kg Method: Calculation method	
m-phenylenebis(methylami	ne):		
Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg	
		Acute toxicity estimate: 930 mg/kg Method: Calculation method	
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.	
		Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	:	LD50 Dermal (Rat): > 3.100 mg/kg	
Skin corrosion/irritation Causes severe burns.			
Components:			
2,4,6-tris(dimethylaminome	thyl)phenol:	
Species	:	Rabbit	
Assessment Method	:	Corrosive OECD Test Guideline 404	
	-		
Assessment Remarks	•	irritating Annex VI - Harmonised	
Komano	•	REGULATION (EC) No 1272/2008	
Serious eye damage/eye irr	itati	on	
Causes serious eye damage.			
Components:			
2,4,6-tris(dimethylaminome	thyl)phenol:	
Species	:	Rabbit	
Assessment		Causes serious eye damage.	

Print Date 05.02.2024

Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0

Assessment	:	irritating
Remarks	:	Annex VI - Harmonised
		REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:		
benzyl alcohol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Country PL 10000033452		



Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

	Toxicity to algae/aquatic : plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l
			Exposure time: 72 h
	Polyoxypropylene diamine:		
	Toxicity to algae/aquatic : plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l Exposure time: 72 h
	Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	:	EC50: 80 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
	2,4,6-tris(dimethylaminomethy	yl)	phenol:
	Toxicity to algae/aquatic : plants	:	EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l Exposure time: 72 h
	N-benzylethylenediamine:		
		:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
	Toxicity to daphnia and other : aquatic invertebrates	:	EC50 (calculated) (Daphnia magna (Water flea)): 10 - 100 mg/l Exposure time: 48 h
	Toxicity to algae/aquatic : plants	:	EC50 (Desmodesmus subspicatus (green algae)): 10 - 100 mg/l Exposure time: 72 h
	m-phenylenebis(methylamine):	
	Toxicity to fish :		LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h
	Toxicity to daphnia and other : aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h
12.2	2 Persistence and degradability No data available	/	
12.3	Bioaccumulative potential No data available		
12.4	I Mobility in soil No data available		

Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0



12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:	
Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effe	ts
Product:	
Additional ecologica mation	infor- : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product		The generation of waste should be avoided or minimized wherever possible.
		Empty containers or liners may retain some product residues.
		This material and its container must be disposed of in a safe way.
		Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
		Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

Print Date 05.02.2024

Revision Date: 26.01.2024 Date of last issue: 22.03.2023

Version 2.0

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	UN 2735		
IMDG	:	UN 2735		
ΙΑΤΑ	:	: UN 2735		
14.2 UN proper shipping name				
ADR	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Polyoxypro- pylene diamine)		
IMDG	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Polyoxypro- pylene diamine)		
ΙΑΤΑ	:	Amines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Polyoxypro- pylene diamine)		
14.3 Transport hazard class(es)				
		Class Subsidiary risks		
ADR	:	8		
IMDG	:	8		
ΙΑΤΑ	:	8		
14.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number	:	III C7		
Labels Tunnel restriction code	' : : :			
	:	80 8		
Tunnel restriction code IMDG Packing group Labels EmS Code IATA (Cargo) Packing instruction (cargo aircraft)	:	80 8 (E) III 8 F-A, S-B 856		
Tunnel restriction code IMDG Packing group Labels EmS Code IATA (Cargo) Packing instruction (cargo		80 8 (E) III 8 F-A, S-B		
Tunnel restriction code IMDG Packing group Labels EmS Code IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group		80 8 (E) III 8 F-A, S-B 856 Y841 III		

Print Date 05.02.2024

Revision Date: 26.01.2024 Date of last issue: 22.03.2023

1

Version 2.0

	Packing group Labels	:	III Corrosive
4.5	Environmental hazards		
	ADR Environmentally hazardous	:	no
	IMDG Marine pollutant	:	no
	IATA (Passenger) Environmentally hazardous	:	no
	IATA (Cargo) Environmentally hazardous	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 75, 3 REACH - Candidate List of Substances of Very High : None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-Not applicable

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 26.01.2024	
Date of last issue: 22.03.2023	

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Version 2.0

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 38% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 38% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H314 : H317 : H318 : H319 : H332 : H412 :	Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.			
Full text of other abbreviations				
Acute Tox.:Aquatic Chronic:Eye Dam.:Eye Irrit.:	Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation			

Revision Date: 26.01.2024

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Date of last issue: 22.03.2023			Thin Date 00.
Skin Corr.	:	Skin corrosion	
Skin Sens.	:	Skin sensitisation	
PL OEL	:	Ordinance of the Minister of Family, Lak of 12 June 2018 concerning the highest tions and levels of the agents harmful for place (Dz.U 2018 pos 1286, with later a	allowable concentra- br health in the work-
PL OEL / NDS	:	Maximal Admissible Concentration	,
ADR	:	European Agreement concerning the In Dangerous Goods by Road	ternational Carriage of
CAS	:	Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
ΙΑΤΑ	:	International Air Transport Association	
IMDG	:	International Maritime Code for Danger	ous Goods
LD50	:	Median lethal dosis (the amount of a ma once, which causes the death of 50% (o test animals)	
LC50	:	Median lethal concentration (concentrat air that kills 50% of the test animals dur period)	
MARPOL	:	International Convention for the Preven Ships, 1973 as modified by the Protoco	
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the E and of the Council of 18 December 200 istration, Evaluation, Authorisation and cals (REACH), establishing a European	6 concerning the Reg- Restriction of Chemi-
SVHC	:	Substances of Very High Concern	
vPvB	:	Very persistent and very bioaccumulativ	/e

Version 2.0

Further information

Classification of th	Classification procedure:	
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

Revision Date: 26.01.2024 Date of last issue: 22.03.2023 Version 2.0



PL/EN