

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®] Construction+

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317	May cause an allergic skin reaction.
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.
		P102	Keep out of reach of children.
		Prevention:	
		P261 P280	Avoid breathing mist or vapours. Wear protective gloves.

Sikaflex[®] Construction+

Print Date 30.08.2023

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0

Response:P302 + P352IF ON SKIN: Wash with plenty of water.Disposal:P501Dispose of contents/container in accord.

Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

Hardener LI (Isophoronedialdimine) Pentamethyl piperidylsebacate Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labelling

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not
	breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponenta		1	
Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
			(70 00/00)
	Registration number		
Urea,N,N"-(methylenedi-4,1-	77703-56-1	Aquatic Chronic 4;	>= 2,5 - < 5
phenylene)bis[N'-butyl-	416-600-4	H413	
	01-0000016345-72-		
	XXXX		
Hardener LI (Isophoronedial-	932742-30-8	Skin Sens. 1B; H317	>= 0,1 - < 0,25
dimine)	700-071-4	Aquatic Chronic 3;	
	01-2119880654-28-	H412	
	XXXX		

Sikaflex[®] Construction+

Revision Date: 24.06.2023 Date of last issue: 22.03.2023



Version 3.0

Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
Reaction product of Hexameth- ylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	192526-20-8 924-669-1 01-2120768758-32- XXXX	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 0,1 - < 0,25
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % Acute toxicity estimate	>= 0,025 - < 0,1
		Acute inhalation tox- icity (dust/mist): 0,031 mg/l	
Substances with a workplace expo			
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Sikaflex[®] Construction+



Revision Date: 24.06.2023 Date of last issue: 22.03.2023		Version 3.0	Print Date 30.08.2
		Consult a physician. Show this safety data sheet to the doctor in a	attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure	e.
In case of skin contact	:	Take off contaminated clothing and shoes im Wash off with soap and plenty of water. If symptoms persist, call a physician.	nmediately.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advid Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsc	
2 Most important symptoms a	nd	effects, both acute and delayed	
Symptoms	:	Allergic reactions See Section 11 for more detailed information and symptoms.	on health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction.	
3 Indication of any immediate	me	dical attention and special treatment neede	d
Treatment	:	Treat symptomatically.	
ECTION 5: Firefighting mea	sur	es	
.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water juide/sand/foam/alcohol resistant foam/chemic extinction.	
.2 Special hazards arising fron	n the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are know	wn

5.3 Advice for firefighters

ucts

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

Print Date 30.08.2023

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	tive	equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
6.3 Methods and material for cor	ntaiı	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	Normal measures for preventive fire protection.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, in	cluding any incompatibilities
Requirements for storage areas and containers	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on stor- : No decomposition if stored and applied as directed.

age stability

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0



7.3 Specific end use(s)

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	NDS (inhalable fraction)	10 mg/m3	PL OEL
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	NDS	0,04 mg/m3	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercap- topropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Sikaflex[®] Construction+

Revision Date: 24.06.2023 Date of last issue: 22.03.2023

= 01 1831 1330E. 22.05.2025		
		Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Version 3.0

Environmental exposure controls

General advice : Do

: Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste various
Odour	:	odourless
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available

Sikaflex[®] Construction+

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0



Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	ovn	losivo limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Colubility/ico)		
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,43 g/cm3 (20 °C)
Relative vapour density	:	No data available

Particle characteristics : No data available

9.2 Other information

No data available

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0



SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid :	Avoid moisture.
-----------------------	-----------------

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402

Hardener LI (Isophoronedialdimine):

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity :	LD50 Oral (Rat): 3.230 mg/kg
-----------------------	------------------------------

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Print Date 30.08.2023

Revision Date: 24.06.2023	
Date of last issue: 22.03.2023	

Version 3.0

Dale	01 1851 1550E. 22.03.2023			
			Method: OECD Test Guideline 423	
	Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402	
	3-isocyanatomethyl-3,5,5-trim	net	hvlcvclohexvl isocvanate:	
	Acute oral toxicity :	:	LD50 Oral (Rat): 4.814 mg/kg	
	Acute inhalation toxicity :	:	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
			Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method	
	Acute dermal toxicity :	:	LD50 Dermal (Rat): > 7.000 mg/kg	
	Skin corrosion/irritation Not classified based on availabl	lei	information.	
	Serious eye damage/eye irrita	atio	on	
	Not classified based on availabl	lei	information.	
	Respiratory or skin sensitisat	tio	n	
	Skin sensitisation			
	May cause an allergic skin reac	tio	n.	
	Respiratory sensitisation Not classified based on availabl	lei	information.	
	Germ cell mutagenicity Not classified based on available information.			
	Carcinogenicity			
	Not classified based on available information.			
	Reproductive toxicity			
	Not classified based on available information. STOT - single exposure			
	Not classified based on availabl	le	information.	
	STOT - repeated exposure			
	Not classified based on availabl	lei	information.	
	Aspiration toxicity			
Not classified based on available information. 11.2 Information on other hazards				
11.4				
	Endocrine disrupting properti	ies	5	
	Product:			

Revision Date: 24.06.2023 Date of last issue: 22.03.2023



Version 3.0

Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---

SECTION 12: Ecological information

- 12.1 Toxicity
 - Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h

Hardener LI (Isophoronedialdimine):

Toxicity to fish	:	LC50 (Fish): 87,2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l Exposure time: 72 h

Pentamethyl piperidylsebacate:

Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

Toxicity to fish	: LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
	Exposure time: 96 h
	Method: OECD Test Guideline 203

Sikaflex[®] Construction+



Revision Date: 24.06.2023 Date of last issue: 22.03.2023	Version 3.0	Print Date 30.08.20
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): Exposure time: 48 h Method: OECD Test Guideline 202	: > 100 mg/l
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapita Exposure time: 72 h Method: OECD Test Guideline 201	ata (algae)): > 100 mg/l
12.2 Persistence and degradabili	У	
No data available 12.3 Bioaccumulative potential No data available		
12.4 Mobility in soil No data available		
12.5 Results of PBT and vPvB as	sessment	
Product:		
Assessment	: This substance/mixture contains no of to be either persistent, bioaccumulativery persistent and very bioaccumula 0.1% or higher	ive and toxic (PBT), or
12.6 Endocrine disrupting prope	ties	
Product:		
Assessment	: The substance/mixture does not con ered to have endocrine disrupting pro REACH Article 57(f) or Commission (EU) 2017/2100 or Commission Reg levels of 0.1% or higher.	operties according to Delegated regulation
12.7 Other adverse effects		
Product: Additional ecological infor- mation	: There is no data available for this pro	oduct.
SECTION 13: Disposal consid	erations	
13.1 Waste treatment methods		
Product	 The generation of waste should be a wherever possible. Empty containers or liners may retain This material and its container must way. Dispose of surplus and non-recyclab 	n some product residues. be disposed of in a safe
	waste disposal contractor	יים איטטעניט אים מ ווטפוושפט

waste disposal contractor.

Revision Date: 24.06.2023

Date of last issue: 22.03.2023



Version 3.0

		Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	Not regulated as a dangerous good		
I	MDG	:	Not regulated as a dangerous good		
I	ATA	:	Not regulated as a dangerous good		
14.2	UN proper shipping name				
	ADR	:	Not regulated as a dangerous good		
I	MDG	:	Not regulated as a dangerous good		
I	ATA	:	Not regulated as a dangerous good		
14.3 Transport hazard class(es)					
	ADR	:	Not regulated as a dangerous good		
I	MDG	:	Not regulated as a dangerous good		
I	ATA	:	Not regulated as a dangerous good		
14.4 Packing group					
	ADR	:	Not regulated as a dangerous good		
I	MDG	:	Not regulated as a dangerous good		
I	ATA (Cargo)	:	Not regulated as a dangerous good		
I	ATA (Passenger)	:	Not regulated as a dangerous good		
14.5 Environmental hazards Not regulated as a dangerous good					

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0



SECTION 15: Regulatory information

15.1 Safety, health and environmer REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	nufacture, placing on ngerous substances,	ion :	specific for the substance or mixture Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3	
			1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)	
International Chemical Weapons Schedules of Toxic Chemicals a		:	Not applicable	
REACH - Candidate List of Subs Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).	
REACH - List of substances sub (Annex XIV)	ject to authorisation	:	Not applicable	
Regulation (EC) No 1005/2009 c plete the ozone layer	on substances that de-	:	Not applicable	
Regulation (EU) 2019/1021 on p tants (recast)	ersistent organic pollu-	:	Not applicable	
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals		:	Not applicable	
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	strea I/or gula	am suppliers, and/or ition, and/or	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable				

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

Sikaflex[®] Construction+

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0



(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Sikaflex[®] Construction+

Print Date 30.08.2023

Revision Date: 24.06.2023 Date of last issue: 22.03.2023 Version 3.0

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H361f	:	Suspected of damaging fertility.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbrevia	tions	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
PL OEL	:	Poland. Occupational exposure limits for airborne toxic sub-
		stances
PL OEL / NDS	:	Maximal Admissible Concentration
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration

Full text of H-Statements

Sikaflex[®] Construction+

Revision Date: 24.06.2023 Date of last issue: 22.03.2023



GHS	: Globally Harmonized System
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
РВТ	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Version 3.0

Further information

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN