according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate



Date of last issue: -

Revision Date: 26.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® TC 374 Part A substrate

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.

Karczunkowska 89 02-871 Warszawa

Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com

responsible for the SDS

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - repeated

exposure, Category 2, Lungs

H373: May cause damage to organs through pro-

longed or repeated exposure.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor® TC 374 Part A substrate

Date of last issue: -

Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs (Lungs) through

prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P314 Get medical advice/ attention if you feel un-

well.

P391 Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Poly(oxy-1,4-butanediyl), .alpha.-(oxiranylmethyl)-.omega.-(oxiranylmethoxy)-

Quartz (SiO2) <5µm

Phenol, methylstyrenated

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Reaction mass of isomers of epoxy resin BFDGE

Phenol, styrenated

reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular

weight <= 700)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor® TC 374 Part A substrate

Date of last issue: -

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 25 - < 40
		specific concentration limit Eye Irrit. 2; H319 >= 5 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317	>= 5 - < 10
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.200 mg/kg	
Poly(oxy-1,4-butanediyl), .alpha (oxiranylmethyl)omega (oxiranylmethoxy)-	26951-52-0 608-023-3	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	
Quartz (SiO2) <5μm	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	>= 1 - < 2,5
Phenol, methylstyrenated	68512-30-1 700-960-7 270-966-8 01-2119555274-38- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 1 - < 2,5
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 0,5 - < 1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,5 - < 1		
Phenol, styrenated	Not Assigned 701-443-9 01-2119980970-27- XXXX, 01- 2119979575-18- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,25 - < 0,5		
reaction product: bisphenol F- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5 500-006-8 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,1 - < 0,25		
Substances with a workplace exposure limit :					
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 2,5 - < 5		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Excessive lachrymation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

Erythema **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

Risks Causes skin irritation.

> May cause an allergic skin reaction. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

irritant effects sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
benzyl alcohol	100-51-6	NDS	240 mg/m3	PL OEL
Titanium dioxide (> 10 μm)	13463-67-7	NDS (inhalable	10 mg/m3	PL OEL
		fraction)		
Quartz (SiO2) <5µm	14808-60-7	NDS (respirable	0,1 mg/m3	PL OEL
		fraction)	(Silica)	

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in par-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate



Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour grey

Odour epoxy-like

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit No data available

: > 101 °C Flash point

Method: closed cup

Auto-ignition temperature No data available

Decomposition temperature No data available

pΗ Not applicable

substance/mixture is non-soluble (in water)

Viscosity

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

Viscosity, dynamic : ca. 1.750 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,54 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

Country PL 100000057382

9/18

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate



Date of last issue: -

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Phenol, styrenated:

Acute oral toxicity : LD50 Oral (Rat): 2.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.


Germ cell mutagenicity

Not classified due to lack of data.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate



Date of last issue: -

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Reaction mass of isomers of epoxy resin BFDGE:

: LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Toxicity to fish

Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A substrate



Date of last issue: -

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 2,55 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (algae): 1,8 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains components considered to

be either persistent, bioaccumulative and toxic (PBT), or very

persistent and very bioaccumulative (vPvB)...

12.6 Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082 IMDG : UN 3082 IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (epoxy resin)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

IMDG

Packing group : III

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

Labels : 9

EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passen: 964

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sikafloor® TC 374 Part A substrate

Date of last issue: -

the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

lowing entries should be considered:

Number on list 3

Number on list 75:

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Phenol, methylstyrenated

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 8,97% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 9% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sikafloor® TC 374 Part A substrate

Revision Date: 26.07.2024 Version 1.0 Print Date 26.07.2024

Date of last issue: -

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled. H360F : May damage fertility.

H372 : Causes damage to organs through prolonged or repeated

exposure if inhaled.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity Skin Irrit. : Skin irritation

Skin Sens. : Skin irritation Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

PL OEL : Ordinance of the Minister of Family, Labour and Social Policy

of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the work-

place (Dz.U 2018 pos 1286, with later amendments)

PL OEL / NDS : Maximal Admissible Concentration

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor® TC 374 Part A substrate

Date of last issue: -

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

PL / EN