

Revision Date: 22.03.2023 Date of last issue: - Version 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: SikaCor<sup>®</sup>-299 Airless Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Epoxy coating, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

#### 1.4 Emergency telephone number

112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Sub-category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Revision Date: 22.03.2023 Date of last issue: -		١	/ersion 1.0	Print Date 23.03.20
Signal word	:	Danger		
Hazard statements	:	H302 + H332 H314 H317 H411	Harmful if swallowed or if inl Causes severe skin burns a May cause an allergic skin r Toxic to aquatic life with long	nd eye damage. eaction.
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory	tract.
Precautionary statements	:	Prevention:		
		P273 P280	Avoid release to the environ Wear protective gloves/ prot eye protection/ face protection tection.	ective clothing/
		Response:		
		P303 + P361 +	P353 IF ON SKIN (or hair): ately all contaminated clothi with water.	
		P304 + P340 +	P310 IF INHALED: Remove air and keep comfortable for mediately call a POISON CE	breathing. Im-
		P305 + P351 +		Rinse cautiously es. Remove con- asy to do. Con-
		P391	Collect spillage.	

#### Hazardous components which must be listed on the label:

m-phenylenebis(methylamine) 2-tert-butylphenol cyclohex-1,2-ylenediamine

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

## SikaCor®-299 Airless Part B

Print Date 23.03.2023

Revision Date: 22.03.2023 Date of last issue: - Version 1.0

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		. ,
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 25 - < 40
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	
4,4'-methylenebis[2,6- diethylaniline]	13680-35-8 237-185-4 01-2120752052-66- XXXX	Acute Tox. 4; H302 Aquatic Chronic 2; H411	>= 10 - < 20
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.901 mg/kg	
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071	>= 10 - < 20
		Acute toxicity esti- mate	
		Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	

# SikaCor®-299 Airless Part B



Revision Date: 22.03.2023 Date of last issue: - Version 1.0

2-tert-butylphenol	88-18-6 201-807-2 01-2119971072-42- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 2; H411 Acute toxicity estimate	>= 5 - < 10
		Acute oral toxicity: 300,03 mg/kg Acute dermal toxicity: 700 mg/kg	
cyclohex-1,2-ylenediamine Contains: perhydroazepine <= 0,2 % hexamethylenediamine <= 0,1 % 2-methylpentane-1,5-diamine <= 0,1 %	694-83-7 211-776-7 01-2119976312-37- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Repr. 2; H361	>= 5 - < 10

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water.

Revision Date: 22.03.2023 Date of last issue: - Version 1.0

Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

: Gastrointestinal discomfort
Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms.
: Health injuries may be delayed. corrosive effects sensitising effects
Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
ſ

## **SECTION 5: Firefighting measures**

5.1	Extinguishing media		
	Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



Revision Date: 22.03.2023 Date of last issue: - Version 1.0

Keep in suitable, closed containers for disposal.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protec	tive	equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for con	tair	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

	0			
Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>		
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.		
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.		
7.2 Conditions for safe storage, including any incompatibilities				

Requirements for storage	:	Keep container tightly closed in a dry and well-ventilated
areas and containers		place. Containers which are opened must be carefully re-



Revision Date: 22.03.2023 Date of last issue: -		Version 1.0	Print Date 23.03.2023	
		sealed and kept upright to prevent leakag ance with local regulations.	e. Store in accord-	
Further information on stor- age stability	:	No decomposition if stored and applied as	s directed.	

#### 7.3 Specific end use(s)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
benzyl alcohol	100-51-6	NDS	240 mg/m3	PL OEL
*The above mentioned values are in accordance with the legislation in effect at the date of the re-				

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.	
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.	
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.	
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par-	



Revision Date: 22.03.2023 Date of last issue: - Version 1.0

ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

## Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform
	respective authorities.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid various
Odour	:	amine-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable

substance/mixture is non-soluble (in water)

#### Viscosity

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

## SikaCor<sup>®</sup>-299 Airless Part B



Revision Date: 22.03.2023 Date of last issue: -	Version 1.0	Print Date 23.03.202
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 19,9983 hPa	
Density	: ca. 1 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : No d	ata available
----------------------------	---------------

#### 10.5 Incompatible materials

Materials to avoid : No data available

### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.




Revision Date: 22.03.2023 Date of last issue: - Version 1.0

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

		0 ( )
Acute toxicity		
Harmful if swallowed or if inh	naled.	
Components:		
benzyl alcohol:		
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
		Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method
4,4'-methylenebis[2,6-dieth	nylani	line]:
Acute oral toxicity	:	LD50 Oral (Rat): 1.901 mg/kg
		Acute toxicity estimate: 1.901 mg/kg Method: Calculation method
m-phenylenebis(methylam	ine):	
Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg
		Acute toxicity estimate: 930 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
		Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	LD50 Dermal (Rat): > 3.100 mg/kg
2-tert-butylphenol:		
Acute oral toxicity	:	LD50 Oral (Rat): > 300 - 2.000 mg/kg
		Acute toxicity estimate: 300,03 mg/kg



#### 12.1 Toxicity

# <u>Components:</u> benzyl alcohol:

Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h





Revision Date: 22.03.2023 Date of last issue: - Version 1.0

### m-phenylenebis(methylamine):

Toxicity to fish	:	LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### **12.6 Endocrine disrupting properties**

No data available

#### 12.7 Other adverse effects

#### Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Revision Date: 22.03.2023 Date of last issue: -	Version 1.0	Print Date 23.03.20
European Waste Catalogue	: 08 01 11* waste paint and varnish con vents or other dangerous substances	taining organic sol-
Contaminated packaging	: 15 01 10* packaging containing residue by dangerous substances	es of or contaminated

## **SECTION 14: Transport information**

14.1 UN	I number or ID number			
AD	R	:	UN 1760	
IMI	DG	:	UN 1760	
ΙΑΙ	ΓA	:	UN 1760	
14.2 UN	I proper shipping name			
AD	R	:		hylamine), 2-tert-butylphenol, 4,4'-
IMI	DG	:	CORROSIVE LIQUID (m-phenylenebis(metl methylenebis[2,6-diet	hylamine), 2-tert-butylphenol, 4,4'-
ΓΑΙ	ΓA	:	Corrosive liquid, n.o.s. (m-phenylenebis(methylamine), 2-tert-butylphenol, 4,4'- methylenebis[2,6-diethylaniline])	
14.3 Tra	ansport hazard class(es)			
			Class	Subsidiary risks
AD	R	:	8	
IMI	DG	:	8	
IAI	ΓA	:	8	
14.4 Pa	cking group			
Cla Ha Lat	R cking group assification Code zard Identification Number pels nnel restriction code		II C9 80 8 (E)	
Lat	DG cking group pels iS Code	:	ll 8 F-A, S-B	

: Alkalis

## IATA (Cargo)

Remarks



 Revision Date: 22.03.2023
 Version 1.0

 Date of last issue: Packing instruction (cargo : 855 aircraft)

Packing instruction (LQ) Packing group Labels	:	Y840 II Corrosive
IATA (Passenger) Packing instruction (passen- ger aircraft)	:	851
Packing instruction (LQ) Packing group Labels	:	Y840 II Corrosive

#### 14.5 Environmental hazards

ADR Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo)		

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legisla	tion s	specific for the substance or mixture
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).



Revision Date: 22.03.2023 Date of last issue: - Version 1.0

REACH - List of substances subject to authorisation (Annex XIV)		Not applicable		
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer		Not applicable		
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)		Not applicable		
REACH Information:	All substances contained - registered by our upstre - registered by us, and/or - excluded from the regul - exempted from the regis	eam suppliers, and/or r lation, and/or		
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS				
Volatile organic compounds :	(VOCV)	for volatile organic compounds nds (VOC) content: 29,91% w/w		
		24 November 2010 on industrial Illution prevention and control)		

#### Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Volatile organic compounds (VOC) content: 39,15% w/w

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

## SikaCor<sup>®</sup>-299 Airless Part B

Print Date 23.03.2023

Revision Date: 22.03.2023 Date of last issue: - Version 1.0

1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. 2005 Nr. 259, item 2173 with later amendments).

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended).

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450 with later amendments).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Revision Date: 22.03.2023 Date of last issue: - Version 1.0



### **SECTION 16: Other information**

H302 H311 H312 H314 H317 H318 H319 H332 H335 H361 H411 H412		Harmful if swallowed. Toxic in contact with skin. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
PL OEL	:	Poland. Occupational exposure limits for airborne toxic sub-
		stances
PL OEL / NDS	÷	Maximal Admissible Concentration
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	÷	International Maritime Code for Dangerous Goods
LD50	÷	Median lethal dosis (the amount of a material, given all at
	-	once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern

# SikaCor®-299 Airless Part B



Revision Date: 22.03.2023 Date of last issue: - Version 1.0

VPVB
------

: Very persistent and very bioaccumulative

Further information		
Classification of the m	ixture:	Classification procedure:
Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method
Skin Corr. 1A	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN