

Revision Date: 10.08.2023 Date of last issue: - Version 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikaflex<sup>®</sup>-621

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person responsible for the SDS	: EHS@pl.sika.com

#### 1.4 Emergency telephone number

112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H317 H412

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

# Sikaflex<sup>®</sup>-621



Revision Date: 10.08.2023 Date of last issue: - Version 1.0

P261	Avoid breathing mist or vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

#### Hazardous components which must be listed on the label:

Hexamethylene-1,6-diisocyanate homopolymer Pentamethyl piperidylsebacate Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane 4,4'-methylenediphenyl diisocyanate

#### Additional Labelling

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not
	breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# Sikaflex<sup>®</sup>-621



Revision Date: 10.08.2023 Date of last issue: -

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N"-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
Hexamethylene-1,6-diisocyanate homopolymer Contains: hexamethylene-di-isocyanate <= 0,3 %	28182-81-2 931-274-8 01-2119485796-17- XXXX	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	>= 0,5 - < 1
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 0,5
Reaction product of Hexameth- ylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	192526-20-8 924-669-1 01-2120768758-32- XXXX	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 0,1 - < 0,25

# Sikaflex<sup>®</sup>-621

Print Date 10.08.2023

Revision Date: 10.08.2023	
Date of last issue: -	

Version 1.0

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX sure limit : 103-23-1 203-090-1 01-2119439699-19-	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 $\overline{}$ specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % $\overline{}$ Acute toxicity estimate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	< 0,1 >= 2,5 - < 5
titanium dioxide; [in powder form	XXXX 13463-67-7		>= 2,5 - < 5
containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 μm]	236-675-5 01-2119489379-17- XXXX		

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.

# Sikaflex<sup>®</sup>-621



Revision Date: 10.08.2023 Date of last issue: -		Version 1.0	Print Date 10.08.2
In case of skin contact	:	Take off contaminated clothing and shoes immed Wash off with soap and plenty of water. If symptoms persist, call a physician.	liately.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	person.
4.2 Most important symptoms	s and e	effects, both acute and delayed	
Symptoms	:	Allergic reactions See Section 11 for more detailed information on I and symptoms.	nealth effects
Risks	:	sensitising effects	
Risks	:	sensitising effects May cause an allergic skin reaction.	
	: te meo :	-	
<b>4.3 Indication of any immedia</b> Treatment	:	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically.	
<ul> <li>4.3 Indication of any immedia</li> <li>Treatment</li> <li>SECTION 5: Firefighting media</li> </ul>	:	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically.	
<ul> <li>4.3 Indication of any immedia</li> <li>Treatment</li> <li>SECTION 5: Firefighting media</li> </ul>	easur	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically.	
<ul> <li>4.3 Indication of any immedia Treatment</li> <li>SECTION 5: Firefighting media</li> <li>5.1 Extinguishing media Suitable extinguishing med</li> </ul>	: <b>easur</b> lia :	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically. es In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
<ul> <li>4.3 Indication of any immedia Treatment</li> <li>SECTION 5: Firefighting media Suitable extinguishing media</li> <li>5.2 Special hazards arising free</li> </ul>	: easur lia : om the	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically. es In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
<ul> <li>4.3 Indication of any immedia Treatment</li> <li>SECTION 5: Firefighting media Suitable extinguishing media</li> <li>5.1 Extinguishing media</li> <li>Suitable extinguishing media</li> <li>Hazardous combustion production production</li> </ul>	: easur lia : om the	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically. es In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction. e substance or mixture	
<ul> <li>4.3 Indication of any immedia Treatment</li> <li>SECTION 5: Firefighting media Suitable extinguishing media Suitable extinguishing med</li> <li>5.2 Special hazards arising free Hazardous combustion pro- ucts</li> </ul>	: easur lia : om the	May cause an allergic skin reaction. dical attention and special treatment needed Treat symptomatically. es In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction. e substance or mixture No hazardous combustion products are known	owder for

#### 6.1 Personal precautions, protective equipment and emergency procedures

1 / 1			0 71	
Personal precautions	:	Use personal pr	otective equipment.	
		Deny access to	unprotected persons.	

Print Date 10.08.2023

Revision Date: 10.08.2023 Date of last issue: - Version 1.0

#### **6.2 Environmental precautions**

Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

## 6.3 Methods and material for containment and cleaning up

Methods for	cleaning up
-------------	-------------

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

	Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.



Revision Date: 10.08.2023 Date of last issue: -

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
bis(2-ethylhexyl) adipate	103-23-1	NDS	400 mg/m3	PL OEL
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	13463-67-7	NDS (inhalable fraction)	10 mg/m3	PL OEL
Hexamethylene-1,6-diisocyanate homo- polymer	28182-81-2	NDS	0,04 mg/m3	PL OEL
	Further information: Skin			
		NDSch	0,08 mg/m3	PL OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	NDS	0,03 mg/m3	PL OEL
***		NDSch	0,09 mg/m3	PL OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercap- topropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Sikaflex<sup>®</sup>-621



Version 1.0	Print Date 10.08.2
: Safety glasses with side-shields co Eye wash bottle with pure water	onforming to EN166
: Chemical-resistant, impervious glo proved standard must be worn at a chemical products. Reference num facturer specifications.	all times when handling
Suitable for short time use or prote Butyl rubber/nitrile rubber gloves (> Contaminated gloves should be re Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	> 0,1 mm)
<ul> <li>Protective clothing (e.g. Safety sho long-sleeved working clothing, long and protective boots are additional and stirring work.</li> </ul>	g trousers). Rubber aprons
<ul> <li>In case of inadequate ventilation w Respirator selection must be based exposure levels, the hazards of the ing limits of the selected respirator organic vapor filter (Type A) A1: &lt; 1000 ppm; A2: &lt; 5000 ppm; Ensure adequate ventilation. This exhaust extraction or by general ve ods for determining inhalation expo ticular to the mixing / stirring area. to keep the concentrations under the limits then respiration protection m</li> </ul>	d on known or anticipated e product and the safe work- A3: < 10000 ppm can be achieved by local entilation. (EN 689 - Meth- osure). This applies in par- In case this is not sufficent he occupational exposure
	<ul> <li>Safety glasses with side-shields of Eye wash bottle with pure water</li> <li>Chemical-resistant, impervious gloproved standard must be worn at a chemical products. Reference numfacturer specifications.</li> <li>Suitable for short time use or prote Butyl rubber/nitrile rubber gloves (Contaminated gloves should be resuitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time &gt;30 min.</li> <li>Protective clothing (e.g. Safety should be readed by the second start of the selected respirator selection must be base exposure levels, the hazards of the ing limits of the selected respirator organic vapor filter (Type A) A1: &lt; 1000 ppm; A2: &lt; 5000 ppm; Ensure adequate ventilation. This exhaust extraction or by general verticular to the mixing / stirring area. to keep the concentrations under the selected terminant of the selec</li></ul>

### Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste various
Odour	:	odourless
Melting point/range / Freezing point	:	No data available

Sikaflex<sup>®</sup>-621



Revision Date: 10			Version 1.0	Print Date 10.08.2
Date of last issue				
Boiling poin	t/boiling range	:	No data available	
Flammabilit	y (solid, gas)	:	No data available	
Upper/lowe	er flammability or	exp	losive limits	
	xplosion limit / Up- mability limit	• :	No data available	
	xplosion limit / ammability limit	:	No data available	
Flash point		:	> 101 °C Method: closed cup	
Auto-ignition	n temperature	:	No data available	
Decomposit	ion temperature	:	No data available	
рН		:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity				
•	v, dynamic	:	ca. 150 mPa.s (20 °C)	
Viscosity	v, kinematic	:	No data available	
Solubility(i	es)			
Water so	blubility	:	insoluble	
Partition coe octanol/wate		:	No data available	
Vapour pres	ssure	:	0,01 hPa	
Density		:	ca. 1,29 g/cm3 (20 °C)	
Relative var	oour density	:	No data available	
Particle cha	racteristics	:	No data available	

<b>Jika</b> ®
Print Date 10.08.2023

Revision Date: 10.08.2023 Date of last issue: - Version 1.0

# 9.2 Other information

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### **Components:**

#### Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401			
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402			
Hexamethylene-1,6-diisocyanate homopolymer:					
Acute oral toxicity	:	LD50 Oral (Rat): > 2.500 mg/kg			

Acute inhalation toxicity	: LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
	methed: Expert Judgement

Sikaflex<sup>®</sup>-621

Print Date 10.08.2023

ision Date: 10.08.2023 e of last issue: -		Version 1.0	Print Date 10.08.20
	-	Acute toxicity estimate: 1,5 mg/l Fest atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: 1	_D50 Dermal (Rat): > 2.000 mg/kg	
Pentamethyl piperidylseba	cate:		
Acute oral toxicity	: 1	_D50 Oral (Rat): 3.230 mg/kg	
Reaction product of Hexan ysilane:	nethyle	ene diisocyanate, oligomers with Merc	aptopropyltrimethox-
Acute oral toxicity		_D50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423	
Acute dermal toxicity		LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402	
4,4'-methylenediphenyl dii	socya	nate:	
Acute oral toxicity		_D50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401	
Acute inhalation toxicity	-	_C50: 1,5 mg/l Exposure time: 4 h Fest atmosphere: dust/mist Method: Expert judgement	
	-	Acute toxicity estimate: 1,5 mg/l Fest atmosphere: dust/mist Method: Calculation method	
bis(2-ethylhexyl) adipate:			
Acute oral toxicity	: 1	_D50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	I	∟C50 (Rat): > 5,7 mg/l Exposure time: 4 h Fest atmosphere: dust/mist	
Skin corrosion/irritation Not classified based on avai	labla in	formation	
Serious eye damage/eye ir			
Not classified based on avail			

Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

## Sikaflex<sup>®</sup>-621

Revision Date: 10.08.2023 Date of last issue: -

Version 1.0



#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

### **Components:**

#### Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h
Pentamethyl piperidylsebacate:		

#### entametnyi piperidyisebacat Toxicity to fish

Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1

# Sikaflex<sup>®</sup>-621

Print Date 10.08.2023

Revision Date: 10.08.2023 Date of last issue: - Version 1.0

M-Factor (Chronic aquatic	:
toxicity)	

1

	Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethox- ysilane:				
Т	Toxicity to fish :		LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203		
	oxicity to daphnia and other equatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202		
	oxicity to algae/aquatic lants	:	EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201		
h	bis(2-ethylhexyl) adipate:				
Т		:	EC50 (Daphnia magna (Water flea)): > 500 mg/l Exposure time: 48 h		
	oxicity to algae/aquatic	:	EC50 (Scenedesmus quadricauda (Green algae)): > 500 mg/l Exposure time: 72 h		
12 2 F	Persistence and degradabili	tv			
	lo data available	- ,			
	<b>Bioaccumulative potential</b> No data available				
12.4 N	Mobility in soil				
N	lo data available				
12.5 F	12.5 Results of PBT and vPvB assessment				
<u>P</u>	Product:				
А	Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.		
12.6 E	12.6 Endocrine disrupting properties				
Р	Product:				
A	Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.		

<b>Jika</b> ®
Print Date 10.08.2023

Revision Date: 10.08.2023	Version 1.0	Print Date 10.08.20
Date of last issue: -		
2 410 01 1401 100401		

#### 12.7 Other adverse effects

#### Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible.
 Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
Country DL 100000040272		

#### 14.1 UN number or ID number



Revision Date: 10.08.2023 Date of last issue: - Version 1.0

	IATA (Cargo)	:	Not regulated as a dan	ger	ous good
	IATA (Passenger)	:	Not regulated as a dan	ger	ous good
14.5	5 Environmental hazards				
	Not regulated as a dangerous	go	bd		
14.6	S Special precautions for use Not applicable	r			
14.7	Maritime transport in bulk a	ccc	ording to IMO instrume	nts	
	Not applicable for product as	sup	plied.		
SE	CTION 15: Regulatory info	rma	ation		
15.1	Safety, health and environm	nen	tal regulations/legislati	on	specific for the substance or mixture
	International Chemical Weapo Schedules of Toxic Chemicals			:	Not applicable
	REACH Information:		All substances containe - registered by our upst - registered by us, and/ - excluded from the reg - exempted from the re	trea /or gula	im suppliers, and/or tion, and/or
	REACH - Restrictions on the r the market and use of certain mixtures and articles (Annex )	dar	igerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
					1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)
	REACH - Candidate List of Su Concern for Authorisation (Art			:	None of the components are listed (=> 0.1 %).
	REACH - List of substances s (Annex XIV)	ubje	ect to authorisation	:	Not applicable
	Regulation (EC) No 1005/200 plete the ozone layer	9 oi	n substances that de-	:	Not applicable
	Regulation (EU) 2019/1021 or tants (recast)	ר pe	ersistent organic pollu-	:	Not applicable

## Sikaflex<sup>®</sup>-621

Print Date 10.08.2023

Revision Date: 10.08.2023 Date of last issue: - Version 1.0

Regulation (EC) No 649/2012 of the European Parlia- : Not applicable ment and the Council concerning the export and import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties
----------------------------	---	--

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

#### Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Version 1.0



Revision Date: 10.08.2023 Date of last issue: -

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

#### Full text of H-Statements

H315 H317	:	Causes skin irritation. May cause an allergic skin reaction.
H319 H332	-	Causes serious eye irritation. Harmful if inhaled.
H334	:	
П <b>3</b> 34	•	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H361f	:	Suspected of damaging fertility.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity

# Sikaflex<sup>®</sup>-621

Revision Date: 10.08.2023 Date of last issue: - Version 1.0



Eye Irrit. Repr. Resp. Sens. Skin Irrit. Skin Sens. STOT RE STOT SE PL OEL	<ul> <li>Eye irritation</li> <li>Reproductive toxicity</li> <li>Respiratory sensitisation</li> <li>Skin irritation</li> <li>Skin sensitisation</li> <li>Specific target organ toxicity - repeated exposure</li> <li>Specific target organ toxicity - single exposure</li> <li>Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the work-place (Dz.U 2018 pos 1286, with later amendments)</li> </ul>
PL OEL / NDS PL OEL / NDSch	<ul><li>Maximal Admissible Concentration</li><li>Maximal Admissible Temporary Concentration</li></ul>
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative
Further information	
Classification of the mixture	Classification procedure:

Classification of the mixture:		Classification procedure:
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

# Sikaflex<sup>®</sup>-621

Revision Date: 10.08.2023 Date of last issue: - Version 1.0



# 

PL/EN