according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaGard®-6210

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.

Karczunkowska 89 02-871 Warszawa

Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com

responsible for the SDS

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H373 May cause damage to organs through pro-

longed or repeated exposure.

Supplemental Hazard : EUH066 Repeated exposure may cause skin dryness

or cracking.

Statements

Date of last issue: 31.08.2022

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

solvent naphtha (petroleum), medium aliph.; Straight run kerosine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
naphtha (petroleum), hydrotreated heavy	Not Assigned 265-150-3	Flam. Liq. 3; H226 Asp. Tox. 1; H304 EUH066	>= 50 - <= 100
Sulfonic acids, petroleum, calcium salts	61789-86-4 263-093-9	Eye Irrit. 2; H319	>= 1 - < 2,5

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Version 2.0 Print Date 10.03.2023

Revision Date: 08.03.2023 Date of last issue: 31.08.2022

solvent naphtha (petroleum), medium aliph.; Straight run kerosine	64742-88-7 265-191-7 01-2119537181-47- XXXX	Flam. Liq. 3; H226 STOT RE 1; H372 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304	>= 1 - < 2,5
stoddard solvent; Low boiling point naphtha — unspecified	8052-41-3 232-489-3	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - < 2,5
methanol	67-56-1 200-659-6 01-2119433307-44- XXXX	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 ————————————————————————————————————	< 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Version 2.0 Print Date 10.03.2023

Date of last issue: 31.08.2022

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Erythema

See Section 11 for more detailed information on health effects

and symptoms.

Risks No known significant effects or hazards.

May cause damage to organs through prolonged or repeated

exposure.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition.

Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022



7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
naphtha (petroleum), hydrotreated heavy	Not Assigned	NDS	300 mg/m3	PL OEL
		NDSch	900 mg/m3	PL OEL
solvent naphtha (petroleum), medium aliph.; Straight run kerosine	64742-88-7	NDS	300 mg/m3	PL OEL
		NDSch	900 mg/m3	PL OEL
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
	Further informa	ation: Indicative, Ide	entifies the possibi	lity of signifi-
	cant uptake through the skin			
		NDS	100 mg/m3	PL OEL
	Further inform	ation: Skin		
		NDSch	300 mg/m3	PL OEL

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
methanol	Workers	Skin contact		40 mg/m3
	Exposure time: 8 h	1		
	Consumers	Skin contact		260 mg/m3
	Exposure time: 8 h	า		

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Date of last issue: 31.08.2022

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Version 2.0 Print Date 10.03.2023

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm). breakthrough time >30 min.

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, Skin and body protection

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour beige

Odour characteristic

Melting point/range / Freezing :

point

No data available

160 °C Boiling point/boiling range

No data available Flammability (solid, gas)

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Version 2.0 Print Date 10.03.2023 Date of last issue: 31.08.2022

Lower explosion limit /

Lower flammability limit

: No data available

: ca. 36 °C Flash point

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature No data available

рΗ Not applicable

Viscosity

 $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$ Viscosity, kinematic

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density ca. 0,87 g/cm3 (20 °C)

Relative vapour density No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions Stable under recommended storage conditions.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 2.0



Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Version 2.0 Print Date 10.03.2023 Date of last issue: 31.08.2022

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

mation

Additional ecological infor- : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1139 IMDG : UN 1139 IATA : UN 1139

14.2 UN proper shipping name

ADR : COATING SOLUTION COATING SOLUTION

IATA : Coating solution

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 3

 IMDG
 : 3

 IATA
 : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : III Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Version 2.0 Print [

Date of last issue: 31.08.2022



- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 53,2% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content:

53,2% w/w, 462,84 g/l

VOC content excluding water

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Commission Regulation (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures (Official Journal of the European Union L 235 from 5.09.2009).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. 2005 Nr. 259, item 2173 with later amendments).

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022



of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended).

Act of 27th April 2001 on waste (Dz. U. Nr. 62, item 628, as amended).

Act of 11th May 2001 on containers and waste containers (Dz. U. Nr. 63, item 638, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Economy of 21st March 2001 concerning requirements on waste thermal treatment processing (Dz. U. Nr. 37, item. 339, as amended).

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450 with later amendments).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H336	: May cause drowsiness or dizziness.
H370	: Causes damage to organs.
H372	: Causes damage to organs through prolonged or repeated exposure.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Date of last issue: 31.08.2022

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Irrit. : Eye irritation Flam. Liq. : Flammable liquids

STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2006/15/EC : Europe. Indicative occupational exposure limit values
PL OEL : Poland. Occupational exposure limits for airborne toxic sub-

stances

2006/15/EC / TWA : Limit Value - eight hours

PL OEL / NDS : Maximal Admissible Concentration

PL OEL / NDSch : Maximal Admissible Temporary Concentration

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 On basis of test data. STOT RE 2 H373 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

according to Regulation (EC) No. 1907/2006

SikaGard®-6210

Revision Date: 08.03.2023 Version 2.0

Date of last issue: 31.08.2022



Changes as compared to previous version!

PL / EN