Print Date 05.02.2024

Version 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®]-250 PC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H317 H334	May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Precautionary statements	:	Prevention:	

Sikaflex[®]-250 PC



Revision Date: 02.09.2023 Date of last issue: 08.03.2023 Version 3.0

P261 P280 P284	Avoid breathing mist or vapours. Wear protective gloves. Wear respiratory protection.
Response:	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

aliphatic prepolymer (t-polyether based) aliphatic prepolymer (d-polyether based) Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane 4,4'-methylenediphenyl diisocyanate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
aliphatic prepolymer (t-polyether	138626-39-8	Skin Sens. 1; H317	>= 5 - < 10
based)	Not Assigned		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikaflex®-250 PC

Revision Date: 02.09.2023 Date of last issue: 08.03.2023



Version 3.0

aliphatic prepolymer (d-polyether based)	39323-37-0 Not Assigned	Skin Sens. 1; H317	>= 2,5 - < 5	
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2,5 - < 5	
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 1 - < 2,5	
Reaction product of Hexameth- ylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	192526-20-8 924-669-1 01-2120768758-32- XXXX	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 0,5 - < 1	
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate Acute inhalation tox-	>= 0,5 - < 1	
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l		

Sikaflex®-250 PC

Revision Date: 02.09.2023 Date of last issue: 08.03.2023 Version 3.0



3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration	>= 0,1 - < 0,25
		limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 0,031 mg/l	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice :	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled :	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact :	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact :	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed



Revision Date: 02.09.2023 Date of last issue: 08.03.2023		Version 3.0	Print Date 05.02.2
Symptoms	:	Asthmatic appearance Allergic reactions See Section 11 for more detailed information and symptoms.	on health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction. May cause allergy or asthma symptoms or br ties if inhaled.	eathing difficul-
4.3 Indication of any immediate r	ne	dical attention and special treatment needed	ł
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water je ide/sand/foam/alcohol resistant foam/chemica extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are know	n
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ning apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	e I	neasures	
6 1 Personal precautions protec	tiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary sev	wer system.

acid bii	p with inert absorbent material (e.g. sand, silica gel, nder, universal binder, sawdust). n suitable, closed containers for disposal.
----------	---

Sikaflex[®]-250 PC

Revision Date: 02.09.2023 Date of last issue: 08.03.2023 Version 3.0



6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	incl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC

Sikaflex[®]-250 PC



Revision Date: 02.09.2023 Date of last issue: 08.03.2023

		mation: Identifies skin, Indicative	the possibility of sig	nificant uptake	
	STEL 100 ppm 2000/39/EC 442 mg/m3 442 mg/m3 100 ppm 100 ppm				
		NDS	100 mg/m3	PL OEL	
	Further information: Skin				
	NDSch 200 mg/m3 PL OE				
4,4'-methylenediphenyl diisocyanate	101-68-8	NDS	0,03 mg/m3	PL OEL	
		NDSch	0,09 mg/m3	PL OEL	
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	NDS	0,04 mg/m3	PL OEL	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercap- topropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment						
Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.				

Sikaflex[®]-250 PC

Revision Date: 02.09.2023

Date of last issue: 08.03.2023



Version 3.0

		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure of	ontr	ols

General advice		Do not flush into surface water or sanitary	v sewer system.
	•	Be not hadri into barnabo water of barnar	,

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste black
Odour	:	odourless
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available

Print Date 05.02.2024

Revision Date: 02.09.2023 Date of last issue: 08.03.2023 Version 3.0

Upper/lower flammability or explosive limits				
Upper explosion limit / Up- per flammability limit	:	No data available		
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 1 %(V)		
Flash point	:	ca. 65 °C Method: closed cup		
Auto-ignition temperature	:	No data available		
Decomposition temperature	:	No data available		
рН	:	Not applicable substance/mixture is non-soluble (in water)		
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)		
Solubility(ies) Water solubility	:	No data available		
Partition coefficient: n- octanol/water	:	No data available		
Vapour pressure	:	ca. 8 hPa (20 °C)		
Density	:	ca. 1,14 g/cm3 (20 °C)		
Relative vapour density	:	No data available		
Particle characteristics	:	No data available		

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Jika ®
Print Date 05.02.2024

Revision Date: 02.09.2023 Date of last issue: 08.03.2023

Version 3.0

Hazardous reactions	:	No hazards to be specially mentioned.
10.4 Conditions to avoid		

The product is chemically stable. 10.3 Possibility of hazardous reactions

Conditions to avoid	Avoid moisture.

10.5 Incompatible	materials
-------------------	-----------

Materials to avoid	: No data availa	able
--------------------	------------------	------

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

aliphatic prepolymer (d-polyether based):					
Acute oral toxicity :	LD50 Oral (Rat): > 2.000 mg/kg				
reaction mass of ethylbenzene	and xylene:				
Acute oral toxicity :	LD50 Oral (Rat): 3.523 mg/kg				
Urea,N,N"-(methylenedi-4,1-ph	enylene)bis[N'-butyl-:				
Acute oral toxicity :	LD50 Oral (Rat): > 2.000 mg/kg				
	Method: OECD Test Guideline 401				
Acute dermal toxicity :	LD50 Dermal (Rabbit): > 2.000 mg/kg				
·	Method: OECD Test Guideline 402				
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethox-					
ysilane:					
Acute oral toxicity :	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423				

Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402
-----------------------	---	---

4,4'-meth	vlenedi	phenvl	diisocy	vanate:
-,	, ionioan	prioriyi	anooo	, analo.

Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
Country PL 00000021205		10 / 19

Sikaflex®-250 PC

Jika ®
Print Date 05.02.2024

Revision Date: 02.09.2023 Date of last issue: 08.03.2023		Version 3.0					
		Method: OECD Test Guideline 401					
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement					
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method					
3-isocyanatomethyl-3,5,5-tr	ime	thylcyclohexyl isocyanate:					
Acute oral toxicity	:	LD50 Oral (Rat): 4.814 mg/kg					
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist					
		Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method					
Acute dermal toxicity	:	LD50 Dermal (Rat): > 7.000 mg/kg					
Skin corrosion/irritation Not classified due to lack of d	Skin corrosion/irritation Not classified due to lack of data.						
	Serious eye damage/eye irritation Not classified due to lack of data.						
Respiratory or skin sensitis	Respiratory or skin sensitisation						
Skin sensitisation May cause an allergic skin re	Skin sensitisation May cause an allergic skin reaction.						
Respiratory sensitisation May cause allergy or asthma							
Germ cell mutagenicity Not classified due to lack of d	Germ cell mutagenicity Not classified due to lack of data.						
Carcinogenicity Not classified due to lack of d	Carcinogenicity Not classified due to lack of data.						
Reproductive toxicity	Reproductive toxicity						
Not classified due to lack of d	Not classified due to lack of data.						
STOT - single exposure Not classified due to lack of d	STOT - single exposure Not classified due to lack of data.						
STOT - repeated exposure	STOT - repeated exposure						
Not classified due to lack of d	lata.						

Revision Date: 02.09.2023 Date of last issue: 08.03.2023 Version 3.0



Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:		
aliphatic prepolymer (t-polye Toxicity to algae/aquatic plants		-
		NOEC (algae): 100 mg/l Exposure time: 72 h
aliphatic prepolymer (d-poly	≏th	er based):
		EC50 (Daphnia (water flea)): > 100 mg/l
		NOEC (Daphnia (water flea)): > 100 mg/l
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/l Exposure time: 72 h
reaction mass of ethylbenzer	ne	and xylene:
Toxicity to fish (Chronic tox- icity)		-
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)		
Urea,N,N"-(methylenedi-4,1-p	ohe	enylene)bis[N'-butyl-:
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg Exposure time: 96 h

mg/l

Sikaflex®-250 PC



Revision Date: 02.09.2023 Date of last issue: 08.03.2023		Version 3.0	Print Date 05.02.202
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater gre 100 mg/l Exposure time: 72 h	en alga)): >
Reaction product of Hexame ysilane:	ethy	ylene diisocyanate, oligomers with Mercaptop	opyltrimethox-
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/ Exposure time: 96 h Method: OECD Test Guideline 203	I
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202	
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): Exposure time: 72 h Method: OECD Test Guideline 201	> 100 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product.

Sikaflex[®]-250 PC

Revision Date: 02.09.2023 Date of last issue: 08.03.2023 Version 3.0



mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)	
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good

Revision Date: 02.09.2023			
Date of last issue: 08.03.2023			

Version 3.0

IMDG	: Not regulated as a da	-	-
IATA (Cargo)	: Not regulated as a da	-	-
IATA (Passenger)	: Not regulated as a da	ngei	rous good
14.5 Environmental hazards Not regulated as a dangerous	s good		
14.6 Special precautions for use Not applicable	er		
14.7 Maritime transport in bulk a Not applicable for product as	-	ents	5
SECTION 15: Regulatory info	ormation		
15.1 Safety, health and environr International Chemical Weap Schedules of Toxic Chemical	ons Convention (CWC)	tion :	specific for the substance or mixture Not applicable
REACH Information:	All substances contair - registered by our up - registered by us, and - excluded from the re - exempted from the r	strea d/or gula	am suppliers, and/or ation, and/or
REACH - Restrictions on the the market and use of certain mixtures and articles (Annex	dangerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
			4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)
REACH - Candidate List of S Concern for Authorisation (Ar		:	None of the components are listed (=> 0.1 %).
REACH - List of substances s (Annex XIV)	subject to authorisation	:	Not applicable
Regulation (EC) No 1005/200	9 on substances that de-	:	Not applicable

Sikaflex[®]-250 PC

Print Date 05.02.2024

Revision Date: 02.09.2023 Date of last issue: 08.03.2023

plete the ozone layer

Version 3.0

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds	unds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 2,87% w/w no VOC duties
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,87% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikaflay® 250 PC

Sikaflex[®]-250 PC

Version 3.0



of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficul-

Sikaflex®-250 PC

Print Date 05.02.2024

	Revision Date: 02.09.2023
Date of last issue: 08.03.2023	Date of last issue: 08.03.2023

Version 3.0

	ties if inhaled.
H335 :	May cause respiratory irritation.
H351 :	Suspected of causing cancer.
H373 :	May cause damage to organs through prolonged or repeated
	exposure if inhaled.
H411 :	Toxic to aquatic life with long lasting effects.
H412 :	Harmful to aquatic life with long lasting effects.
H413 :	May cause long lasting harmful effects to aquatic life.
Full text of other abbreviations	
Acute Tox. :	Acute toxicity
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Asp. Tox. :	Aspiration hazard
Carc. :	Carcinogenicity
Eye Irrit. :	Eye irritation
Flam. Liq.	Flammable liquids
Resp. Sens.	Respiratory sensitisation
Skin Irrit.	Skin irritation
Skin Sens. :	Skin sensitisation
STOT RE :	Specific target organ toxicity - repeated exposure
STOT SE :	Specific target organ toxicity - single exposure
2000/39/EC :	Europe. Commission Directive 2000/39/EC establishing a first
2000/33/20	list of indicative occupational exposure limit values
PL OEL :	Ordinance of the Minister of Family, Labour and Social Policy
FLOEL .	
	of 12 June 2018 concerning the highest allowable concentra-
	tions and levels of the agents harmful for health in the work-
	place (Dz.U 2018 pos 1286, with later amendments)
2000/39/EC / TWA :	Limit Value - eight hours
2000/39/EC / STEL :	Short term exposure limit
PL OEL / NDS :	Maximal Admissible Concentration
PL OEL / NDSch :	Maximal Admissible Temporary Concentration
ADR :	European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS :	Chemical Abstracts Service
DNEL :	Derived no-effect level
EC50 :	Half maximal effective concentration
GHS :	Globally Harmonized System
IATA :	International Air Transport Association
IMDG :	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at
LD30 .	
	once, which causes the death of 50% (one half) of a group of
1.050	test animals)
LC50 :	Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL :	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL :	Occupational Exposure Limit
PBT :	Persistent, bioaccumulative and toxic
PNEC :	Predicted no effect concentration
REACH :	Regulation (EC) No 1907/2006 of the European Parliament
·	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
	oais (NEROTI), establishing a European Orienticais Ayelluy

_

Jika ®
Print Date 05.02.2024

Revision Date: 02.09.2023
Date of last issue: 08.03.2023

Version 3.0

SVHC vPvB		Substances of Very High Concern Very persistent and very bioaccumulative	
Further information			
Classification of the mixture:		Classification procedure:	
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN