

Revision Date: 12.05.2025 Date of last issue: -

Version 1.0

Print Date 12.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaCor[®] EG-5 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Corrosion protection, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2, hearing organs	H373: May cause damage to organs through pro- longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Version 1.0 Print Date 12.05.2025 Date of last issue: -Hazard pictograms Signal word Warning 1 Flammable liquid and vapour. Hazard statements H226 Causes skin irritation. H315 H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. Harmful if inhaled. H332 H335 May cause respiratory irritation. May cause damage to organs (hearing organs) H373 through prolonged or repeated exposure. Prevention: Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokina. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hexamethylene diisocyanate, oligomers reaction mass of ethylbenzene and xylene hexamethylene-di-isocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 12.05.2025 Date of last issue: - Version 1.0

Print Date 12.05.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		(,
Hexamethylene diisocyanate, oligomers Contains: hexamethylene-di-isocyanate <= 0,49 %	28182-81-2 Not Assigned	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Acute toxicity esti- mate	>= 60 - < 80
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20

SikaCor[®] EG-5 Part B

Revision Date: 12.05.2025

Revision Date: 12.05.2025 Date of last issue: -	Version 1	Print Date 12.05.2025	
hexamethylene-di-isocyanate	822-06-0 212-485-8 01-2119457571-37- XXXX	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 STOT SE 3; H335 (Respiratory system) resp. Sens. 1; H317 Specific concentration limit Resp. Sens. 1; H334 >= 0,5 % resp. Sens. 1; H317 Skin Sens. 1; H317 >= 0,5 % Acute toxicity estimate Acute oral toxicity: 746 mg/kg Acute inhalation tox- icity (vapour): 0,124 mg/l	>= 0,1 - < 0,5

Version 1.0

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.



Print Date 12.05.2025

SikaCor[®] EG-5 Part B



not induce vomiting without medical advice. the mouth with water. not give milk or alcoholic beverages. er give anything by mouth to an unconscious p s, both acute and delayed gh piratory disorder gic reactions essive lachrymation hema dache natitis	erson.
gh piratory disorder rgic reactions essive lachrymation hema dache natitis	
piratory disorder gic reactions essive lachrymation hema dache natitis	
Section 11 for more detailed information on he symptoms.	ealth effects
cause an allergic skin reaction. ses serious eye irritation. nful if inhaled. cause respiratory irritation. cause damage to organs through prolonged o	r repeated
-	
	Int effects sitising effects ses skin irritation. cause an allergic skin reaction. ses serious eye irritation. mful if inhaled. cause respiratory irritation. cause damage to organs through prolonged o osure. attention and special treatment needed at symptomatically.

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Date of last issue: -		Version 1.0	Print Date 12.05.2025
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	apparatus.
Further information	:	Use water spray to cool unopened containers.	
SECTION 6: Accidental release	-	neasures e equipment and emergency procedures	
		Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosivitions. Vapours can accumulate in low areas.	/e concentra-
6.2 Environmental precautions			
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or dr	ains inform

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

respective authorities.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth-
	ma, allergies, chronic or recurrent respiratory disease should
	not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Take precautionary measures against static discharge.
	Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure.
	Take necessary action to avoid static electricity discharge



Revision Date: 12.05.2025 Date of last issue: -		Version 1.0	Print Date 12.05.2025
		(which might cause ignition of organic vapours). Follow standard hygiene measures when handli products	ng chemical
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from open flames/ hot surfaces. No smoking. Take pr measures against electrostatic discharges.	
Hygiene measures	:	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the er	using do not
7.2 Conditions for safe storage, i	nc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-v place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Stor ance with local regulations.	refully re-
Further information on stor- age stability	:	No decomposition if stored and applied as direct	ed.

7.3 Specific end use(s)

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
Hexamethylene diisocyanate, oligomers	28182-81-2	TWA	0,01 mg/m3	98/24/EC I
			(NCO)	
	Further inform	ation: Skin, Dermal	and respiratory se	ensitisation,
	Binding			
		STEL	0,02 mg/m3	98/24/EC I
			(NCO)	
		NDS	0,04 mg/m3	PL OEL
	Further inform	ation: Skin		
		NDSch	0,08 mg/m3	PL OEL
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm	2000/39/EC
			550 mg/m3	
	Further inform	ation: Identifies the	possibility of signi	ficant uptake
	through the sk	in, Indicative		
		TWA	50 ppm	2000/39/EC
			275 mg/m3	
		NDS	260 mg/m3	PL OEL
	Further inform	ation: Skin		



Revision Date: 12.05.2025

SikaCor[®] EG-5 Part B

Version 1.0

Print Date 12.05.2025

Date of last issue: -

	1	NDSch	520 mg/m2	PL OEL	
			520 mg/m3	-	
reaction mass of ethylbenzene and xy-	Not Assigned	TWA	50 ppm	2000/39/EC	
lene			221 mg/m3		
	Further information: Identifies the possibility of significant uptake				
	through the sk	in, Indicative			
		STEL	100 ppm	2000/39/EC	
			442 mg/m3		
		NDS	100 mg/m3	PL OEL	
	Further information: Skin				
		NDSch	200 mg/m3	PL OEL	
hexamethylene-di-isocyanate	822-06-0	NDS	0,04 mg/m3	PL OEL	
	Further inform	ation: Skin			
		NDSch	0,08 mg/m3	PL OEL	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent



Revision Date: 12.05.2025 Date of last issue: -	Version 1.0	Print Date 12.05.2025
	to keep the concentrations under the o limits then respiration protection measu Ensure adequate ventilation, especially	ures must be used.

Environmental exposure controls					
General advice	 Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities. 				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid yellow
Odour	:	slight
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	ca. 145 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit		
Lower explosion limit / Lower flammability limit	:	Lower explosion limit 1,0 %(V)
Flash point	:	ca. 38 °C Method: closed cup
Auto-ignition temperature	:	333 °C
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble

Viscosity

(in water)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor[®] EG-5 Part B

_



Revision Date: 12.05.2025 Date of last issue: -		Version 1.0	Print Date 12.05.2025
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	ca. 7,9993 hPa (20 °C)	
Density	:	ca. 1,07 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

2

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions						
Hazardous reactions :	Stable under recommended storage conditions.					
	Vapours may form explosive mixture with air.					
10.4 Conditions to avoid						
Conditions to avoid :	Heat, flames and sparks.					
10.5 Incompatible materials						
Materials to avoid :	No data available					
10.6 Hazardous decomposition products						

No hazardous decomposition products are known.



Revision Date: 12.05.2025 Date of last issue: - Version 1.0

Print Date 12.05.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Hexamethylene diisocyanate, oligomers:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity		1050:15 mg/l

Acute innalation toxicity	:	LC50: 1,5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist
		Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

2-methoxy-1-methylethyl acetate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg

reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

hexamethylene-di-isocyanate:

Acute oral toxicity :	LD50 Oral (Rat): 746 mg/kg
	Acute toxicity estimate: 746 mg/kg Method: Calculation method
Acute inhalation toxicity :	LC50 (Rat): 0,124 mg/l Exposure time: 4 h Test atmosphere: vapour
	Acute toxicity estimate: 0,124 mg/l Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity :	LD50 Dermal (Rat): > 7.000 mg/kg

SikaCor[®] EG-5 Part B

Revision Date: 12.05.2025 Date of last issue: -

Skin sensitisation

Carcinogenicity

Skin corrosion/irritation Causes skin irritation.

Causes serious eye irritation.

Respiratory sensitisation Not classified due to lack of data.

Germ cell mutagenicity

Reproductive toxicity

STOT - single exposure

Aspiration toxicity

Serious eye damage/eye irritation

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Not classified due to lack of data.

Not classified due to lack of data.

Not classified due to lack of data.

May cause respiratory irritation. STOT - repeated exposure

Not classified due to lack of data.

Endocrine disrupting properties

11.2 Information on other hazards

Version 1.0

Print Date 12.05.2025

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Assessment

Components:

Hexamethylene diisocyanate, oligomers:

Toxicity to fish

: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Date of last issue: -		Version 1.0	Print Date 12.05.202
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h	
reaction mass of ethylbenze	ene	and xylene:	
Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)	
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)	
12.2 Persistence and degradabili No data available	ity		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	se	ssment	
Product:			
Assessment	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	c (PBT), or
12.6 Endocrine disrupting prope	rtie	es	
Product:			
Assessment	:	The substance/mixture does not contain componered to have endocrine disrupting properties accerses REACH Article 57(f) or Commission Delegated re(EU) 2017/2100 or Commission Regulation (EU) levels of 0.1% or higher.	ording to egulation
12.7 Other adverse effects			
Product: Additional ecological infor-	:	There is no data available for this product.	

13.1 Waste treatment methods

:

Product

The generation of waste should be avoided or minimized wherever possible.

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Date of last issue: - Version 1.0

Print Date 12.05.2025

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 1263	
IMDG	:	UN 1263	
ΙΑΤΑ	:	UN 1263	
14.2 UN proper shipping name			
ADR	:	PAINT	
IMDG	:	PAINT	
ΙΑΤΑ	:	Paint	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III F1 30 3 (D/E)	
IMDG Packing group Labels EmS Code IATA (Cargo)	: :	III 3 F-E, <u>S-E</u>	
Packing instruction (cargo	:	366	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Version 1.0 Print Date 12.05.2025 Date of last issue: aircraft) Packing instruction (LQ) Y344 Packing group Ш Labels Flammable Liquids IATA (Passenger) Packing instruction (passen-: 355 der aircraft) Packing instruction (LQ) Y344 Packing group III Labels Flammable Liquids 14.5 Environmental hazards ADR Environmentally hazardous : no IMDG Marine pollutant no IATA (Passenger) Environmentally hazardous no IATA (Cargo) Environmentally hazardous no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

- All substances contained in our Products are
 - registered by our upstream suppliers, and/or
 - registered by us, and/or
 - excluded from the regulation, and/or
 - exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 74:

SikaCor[®] EG-5 Part B

_



Revision Date: 12.05.2025 Date of last issue: -	Version 1	.0	Print Date 12.05.2025
			Hexamethylene diisocyanate, oligo- mers, hexamethylene-di-isocyanate
			Number on list 75
REACH - Candidate List of Substan Concern for Authorisation (Article 5		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject (Annex XIV)	t to authorisation	:	Not applicable
Regulation (EU) No 2024/590 on si plete the ozone layer	ubstances that de-	:	Not applicable
Regulation (EU) 2019/1021 on perstants (recast)	sistent organic pollu-	:	Not applicable
Regulation (EU) No 649/2012 of th ment and the Council concerning th of dangerous chemicals		:	Not applicable
jor-accident hazards involving dang			and of the Council on the control of ma-
	(VOCV)		or volatile organic compounds Is (VOC) content: 25% w/w
	ivestock rearing emiss and control)	ion	4 November 2010 on industrial and s (integrated pollution prevention Is (VOC) content: 25% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December



Revision Date: 12.05.2025 Date of last issue: - Version 1.0

Print Date 12.05.2025

2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Date of last issue: - Version 1.0

Print Date 12.05.2025

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements H226 Flammable liquid and vapour. Harmful if swallowed. H302 : H304 May be fatal if swallowed and enters airways. : Harmful in contact with skin. H312 : H315 Causes skin irritation. H317 May cause an allergic skin reaction. Causes serious eye irritation. H319 H330 Fatal if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. H335 May cause drowsiness or dizziness. H336 May cause damage to organs through prolonged or repeated H373 : exposure if inhaled. H412 Harmful to aquatic life with long lasting effects. : Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Chronic Long-term (chronic) aquatic hazard : Asp. Tox. Aspiration hazard 1 Eye Irrit. Eve irritation : Flammable liquids Flam. Liq. : Resp. Sens. Respiratory sensitisation Skin Irrit. Skin irritation Skin Sens. Skin sensitisation Specific target organ toxicity - repeated exposure STOT RE STOT SE Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first 2000/39/EC list of indicative occupational exposure limit values 98/24/EC I Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values PL OEL Ordinance of the Minister of Family, Labour and Social Policy : of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments) 2000/39/EC / TWA Limit Value - eight hours Short term exposure limit 2000/39/EC / STEL 98/24/EC I / STEL Limit values Short-term : 98/24/EC I / TWA Limit values 8 hours : Maximal Admissible Concentration PL OEL / NDS PL OEL / NDSch Maximal Admissible Temporary Concentration : European Agreement concerning the International Carriage of ADR Dangerous Goods by Road

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor[®] EG-5 Part B



Revision Date: 12.05.2025 Date of last issue: -

Version 1.0

Print Date 12.05.2025

CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
	•
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL	: International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
	, .
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN

Revision Date: 12.05.2025 Date of last issue: -

Version 1.0

Print Date 12.05.2025

