

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard®-2406 Protection Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.
Karczunkowska 89
02-871 Warszawa
Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com
responsible for the SDS

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard®-2406 Protection Part A






Revision Date: 20.01.2024

Version 2.0

Print Date 05.02.2024

Date of last issue: -

Hazard pictograms	:			
Signal word	:	Warning		
Hazard statements	:	H226	Flammable liquid and vapour.	
		H315	Causes skin irritation.	
		H317	May cause an allergic skin reaction.	
		H319	Causes serious eye irritation.	
		H373	May cause damage to organs through prolonged or repeated exposure if inhaled.	
		H412	Harmful to aquatic life with long lasting effects.	
Precautionary statements	:	Prevention:		
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
		P260	Do not breathe mist or vapours.	
		P264	Wash skin thoroughly after handling.	
		P273	Avoid release to the environment.	
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.	
		Response:		
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.	

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
4-morpholinecarbaldehyde

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard®-2406 Protection Part A

Revision Date: 20.01.2024

Version 2.0

Print Date 05.02.2024

Date of last issue: -

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5 - < 10
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 2,5
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not Assigned 919-446-0 265-185-4 01-2119458049-33-XXXX [corresponding group CAS 64742-82-1]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - < 2,5
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12-XXXX	Skin Sens. 1; H317	>= 1 - < 2,5
trimethylolpropane	77-99-6 201-074-9 01-2119486799-10-XXXX	Repr. 2; H361fd	>= 0,1 - < 0,5

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure if inhaled.



4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		NDS	100 mg/m ³	PL OEL
		Further information: Skin		
		NDSch	200 mg/m ³	PL OEL
Titanium dioxide (> 10 µm)	13463-67-7	NDS (inhalable fraction)	10 mg/m ³	PL OEL
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 275 mg/m ³	2000/39/EC
		NDS	260 mg/m ³	PL OEL
		Further information: Skin		
		NDSch	520 mg/m ³	PL OEL
n-butyl acetate	123-86-4	NDS	240 mg/m ³	PL OEL
		NDSch	720 mg/m ³	PL OEL
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
		Further information: Indicative		
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not Assigned	NDS	300 mg/m ³	PL OEL
		NDSch	900 mg/m ³	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
 Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
 Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024

Version 2.0

Print Date 05.02.2024

Date of last issue: -

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),

breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : various
- Odour : solvent-like
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikgard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

Upper explosion limit / Upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 1 %(V)
Flash point	: ca. 36 °C Method: closed cup
Auto-ignition temperature	: 235 °C
Decomposition temperature	: No data available
pH	: Not applicable substance/mixture is non-soluble (in water)
Viscosity	
Viscosity, dynamic	: ca. 2.800 mPa.s (20 °C)
Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: 7,9993 hPa
Density	: ca. 1,4 g/cm ³ (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available



SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23,4 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

trimethylolpropane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 0,85 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal (Rabbit): > 10.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

n-butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Assessment : Repeated exposure may cause skin dryness or cracking.
Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.



11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia (water flea)

n-butyl acetate:

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l
Exposure time: 72 h

trimethylolpropane:

Toxicity to fish : LC50 (Fish): 1.000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1.000 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered



to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

IMDG : PAINT

IATA : Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemption)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : None., Transport in accordance with 2.3.2.5 of the IMDG-Code

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

IATA (Passenger)
Environmentally hazardous : no

IATA (Cargo)

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikgard®-2406 Protection Part A



Revision Date: 20.01.2024

Version 2.0

Print Date 05.02.2024

Date of last issue: -

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 23,92% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 23,94% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024

Version 2.0

Print Date 05.02.2024

Date of last issue: -

thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361fd	:	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024

Version 2.0

Print Date 05.02.2024

Date of last issue: -

Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
PL OEL	:	Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments)
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
PL OEL / NDS	:	Maximal Admissible Concentration
PL OEL / NDSch	:	Maximal Admissible Temporary Concentration
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikagard®-2406 Protection Part A



Revision Date: 20.01.2024
Date of last issue: -

Version 2.0

Print Date 05.02.2024

Skin Sens. 1	H317	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

PL / EN