

Revision Date: 19.12.2024 Date of last issue: -

Version 1.0

Print Date 19.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikafloor[®]-264 Plus/264 Plus Thixo Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	-

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12 Acute toxicity, Category 4	72/2008) H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 4	H413: May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

1

Jika®

Sikafloor[®]-264 Plus/264 Plus Thixo Part B

Revision Date: 19.12.2024 Date of last issue: -		Version 1.0	Print Date 19.12.2024
Hazard statements :	H302 H314 H317 H413	Harmful if swallowed. Causes severe skin burns ar May cause an allergic skin re May cause long lasting harm life.	action.
Precautionary statements :	Prevention P261 P273 P280	n: Avoid breathing mist or Avoid release to the env Wear protective gloves/ eye protection/ face pro	vironment. protective clothing/
	Response	:	
	P303 + P3	61 + P353 IF ON SKIN (or had ately all contaminated c with water.	
	P304 + P3	40 + P310 IF INHALED: Rer air and keep comfortabl mediately call a POISO	e for breathing. Im-
	P305 + P3		S: Rinse cautiously inutes. Remove con- nd easy to do. Con-

Hazardous components which must be listed on the label:

benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine Adduct XA-P (epoxy amine adduct, polymer) Cashew, nutshell liq. N-benzylethylenediamine m-phenylenebis(methylamine)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor®-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 40 - < 60
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity esti- mate Acute oral toxicity: 1.030 mg/kg	>= 20 - < 25
Adduct XA-P (epoxy amine ad- duct, polymer)	110839-13-9 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 10 - < 20
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12- XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 5 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor®-264 Plus/264 Plus Thixo Part B

Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Cashew, nutshell liq.	8007-24-7 700-991-6 01-2119502450-57- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute toxicity esti- mate Acute oral toxicity: 500 mg/kg Acute dermal toxicity: 2.000 mg/kg	>= 3 - < 5
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 2,5 - < 5
N-benzylethylenediamine	4152-09-4 223-984-5 01-2120822346-58- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute oral toxicity: 300,03 mg/kg	>= 2,5 - < 3
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity estimate Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

SECTION 4: First aid measures

4.1 Description of first aid measu	Ires			
General advice	 Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. 			
If inhaled	: Move to fresh air. Consult a physician after significant exposure.			
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.			
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. 			
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 			
4.2 Most important symptoms and	d effects, both acute and delayed			
Symptoms	 Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms. 			
Risks	: Health injuries may be delayed. corrosive effects sensitising effects			
	Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.			
4.3 Indication of any immediate medical attention and special treatment needed				
Treatment	: Treat symptomatically.			



Sikafloor®-264 Plus/264 Plus Thixo Part B

Revision Date: 19.12.2024	
Date of last issue: -	

Version 1.0

Print Date 19.12.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
		extinction.

5.2 Special hazards arising from the substance or mixture

•	No hazardous combustion products are known
ucts	

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions Use personal protective equipment. Deny access to unprotected persons. 6.2 Environmental precautions Environmental precautions Do not flush into surface water or sanitary sewer system

ronmental precautions	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).	
	Do not get in eyes, on skin, or on clothing.	
	For personal protection see section 8.	
	Persons with a history of skin sensitisation problems or asth-	



Revision Date: 19.12.2024 Date of last issue: -		Version 1.0	Print Date 19.12.2024
		ma, allergies, chronic or recurrent respiratory not be employed in any process in which this used. Smoking, eating and drinking should be proh plication area. Follow standard hygiene measures when har products	mixture is being ibited in the ap-
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection	טח.
Hygiene measures	:	Handle in accordance with good industrial hy practice. When using do not eat or drink. Wh smoke. Wash hands before breaks and at the	en using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and we place. Containers which are opened must be sealed and kept upright to prevent leakage. S ance with local regulations.	carefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as di	rected.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheuse.	et prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
benzyl alcohol	100-51-6	NDS	240 mg/m3	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

:

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.

Sikafloor[®]-264 Plus/264 Plus Thixo Part B

_



rision Date: 19.12.2024 e of last issue: -		Version 1.0	Print Date 19.12.2024
Hand protection	:	Chemical-resistant, impervious gloves proved standard must be worn at all tin chemical products. Reference number facturer specifications. Suitable for short time use or protection Butyl rubber/nitrile rubber gloves (> 0,1 Contaminated gloves should be remov Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	nes when handling EN 374. Follow manu- n against splashes: mm)
Skin and body protection	:	Protective clothing (e.g. Safety shoes a long-sleeved working clothing, long tro and protective boots are additionaly rea and stirring work.	users). Rubber aprons
Respiratory protection	:	In case of inadequate ventilation wear Respirator selection must be based on exposure levels, the hazards of the pro- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: Ensure adequate ventilation. This can exhaust extraction or by general ventila ods for determining inhalation exposure ticular to the mixing / stirring area. In ca to keep the concentrations under the o limits then respiration protection measu	known or anticipated oduct and the safe work- < 10000 ppm be achieved by local ation. (EN 689 - Meth- e). This applies in par- ase this is not sufficent ccupational exposure
Environmental exposure co	ontro	ls	
General advice	:	Do not flush into surface water or sanit If the product contaminates rivers and respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	: liquid : light yellow	
Odour	: amine-like	
Melting point/ range / Freez- ing point	: No data available	9
Boiling point/boiling range	: No data available	Э

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: -	Version 1.0	Print Date 19.12.2024
Flammability (solid, gas)	: No data available	
Upper/lower flammability or Upper explosion limit / Up- per flammability limit		
Lower explosion limit / Lower flammability limit	: No data available	
Flash point	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: ca. 11 Concentration: 10 %	
Viscosity Viscosity, dynamic	: ca. 130 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: partly soluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,07 hPa	
Density	: ca. 1,01 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

No data available

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed. Components:	
benzyl alcohol:	
Acute oral toxicity	 Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
	LD50 Oral (Rat): 1.200 mg/kg
3-aminomethyl-3,5,5-trimethy	Icyclohexylamine:
Acute oral toxicity	 Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
	LD50 Oral (Rat): 1.030 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l
Country PL 10000054667	10/

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: -	Version 1.0	Print Date 19.12.2024
	Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	LD50 Dermal (Rabbit): > 2.000 mg/kg	
	LD50 (Rabbit): > 2.000 - 5.000 mg/kg	
Adduct XA-P (epoxy amine a	iduct, polymer):	
	LD50 Oral (Rat): 300 - 2.000 mg/kg Method: OECD Test Guideline 423	
Polyoxypropylene diamine:		
Acute oral toxicity	: LD50 Oral (Rat): 2.880 mg/kg	
Cashew, nutshell liq.:		
Acute oral toxicity	LD50 Oral (Rat): 500 mg/kg	
	Acute toxicity estimate: 500 mg/kg Method: Calculation method	
Acute dermal toxicity	LD50 Dermal (Rat): 2.000 mg/kg	
	Acute toxicity estimate: 2.000 mg/kg Method: Calculation method	
2,4,6-tris(dimethylaminometh	yl)phenol:	
Acute oral toxicity	LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008	
N-benzylethylenediamine:		
Acute oral toxicity	LD50 Oral (Rat): > 300 - < 2.000 mg/kg	
	Acute toxicity estimate: 300,03 mg/kg Method: Calculation method	
m-phenylenebis(methylamine	·):	
Acute oral toxicity	LD50 Oral (Rat): 930 mg/kg	
	Acute toxicity estimate: 930 mg/kg Method: Calculation method	
Acute inhalation toxicity	 LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract 	

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: -	Version 1.0	Print Date 19.12.2024
	Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity :	LD50 Dermal (Rat): > 3.100 mg/kg	
Skin corrosion/irritation Causes severe burns.		
Components:		
2,4,6-tris(dimethylaminomethy	l)phenol:	
Species : Assessment : Method :	Rabbit Corrosive OECD Test Guideline 404	
Assessment : Remarks :	irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Serious eye damage/eye irritat Causes serious eye damage.	ion	
Components:		
2,4,6-tris(dimethylaminomethy	l)phenol:	
Species : Assessment :	Rabbit Causes serious eye damage.	
Assessment : Remarks :	irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Respiratory or skin sensitisati	on	
Skin sensitisation May cause an allergic skin reacti	on.	
Respiratory sensitisation Not classified due to lack of data		
Germ cell mutagenicity Not classified due to lack of data		
Carcinogenicity Not classified due to lack of data		
Reproductive toxicity Not classified due to lack of data		
STOT - single exposure		



Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:	
benzyl alcohol:	
Toxicity to fish :	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
3-aminomethyl-3,5,5-trimethyl	cyclohexylamine:
Toxicity to algae/aquatic : plants	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h
	NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h
Polyoxypropylene diamine:	
Toxicity to algae/aquatic : plants	EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l Exposure time: 72 h
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	EC50: 80 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
N-benzylethylenediamine:	
Toxicity to fish :	LC50 (Fish): > 100 mg/l

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: -		Version 1.0	Print Date 19.12.20
		Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (calculated) (Daphnia magna (Water flea mg/l Exposure time: 48 h	a)): 10 - 100
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green alga mg/l Exposure time: 72 h	ae)): 10 - 100
m-phenylenebis(methylami	ne):	:	
Toxicity to fish	:	LC50 (Oryzias latipes (Japanese medaka)): > Exposure time: 96 h	10 - 100 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10 - 10 Exposure time: 48 h	0 mg/l
12.2 Persistence and degradabil No data available	lity		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	sse	ssment	
Product: Assessment	:	This substance/mixture contains no componen to be either persistent, bioaccumulative and to very persistent and very bioaccumulative (vPvl 0.1% or higher	xic (PBT), or
12.6 Endocrine disrupting prope	ertie	9S	
Product:			
Assessment	:	The substance/mixture does not contain comp ered to have endocrine disrupting properties as REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EU levels of 0.1% or higher.	ccording to I regulation
12.7 Other adverse effects			
Product:			
Additional ecological infor- mation	:	An environmental hazard cannot be excluded i unprofessional handling or disposal. May cause long lasting harmful effects to aqua	
	:	unprofessional handling or disposal.	

Jika®

Sikafloor®-264 Plus/264 Plus Thixo Part B

Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

:	The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe
	way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 2735	
IMDG	:	UN 2735	
ΙΑΤΑ	:	UN 2735	
14.2 UN proper shipping name			
ADR	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, N benzylethylenediamine)	
IMDG	:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, N- benzylethylenediamine)	
ΙΑΤΑ	:	Amines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, N- benzylethylenediamine)	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	8	
IMDG	:	8	
ΙΑΤΑ	:	8	
14.4 Packing group			
ADR			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-264 Plus/264 Plus Thixo Part B

Jika®

Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III C7 80 8 (E)	
IMDG Packing group Labels EmS Code		III 8 F-A, S-B	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	856 Y841 III Corrosive	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	852 Y841 III Corrosive	
14.5 Environmental hazards			
ADR			

Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are
--------------------	--

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



Revision Date: 19.12.2024 Date of last issue: -	Version 1.0		Print Date 19.12.2024
	 registered by our upstre registered by us, and/or excluded from the regul exempted from the registered 	ation, and/or	and/or
REACH - Restrictions on the man the market and use of certain dan mixtures and articles (Annex XVII)	gerous substances,		of restriction for the fol- es should be considered: list 3
		Number on	list 75:
REACH - Candidate List of Substa Concern for Authorisation (Article		None of the (=> 0.1 %).	components are listed
REACH - List of substances subje (Annex XIV)	ect to authorisation :	Not applical	ble
Regulation (EC) on substances th layer	at deplete the ozone :	Not applical	ble
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu- :	Not applical	ble
Regulation (EU) No 649/2012 of the ment and the Council concerning of dangerous chemicals		Not applical	ble
Seveso III: Directive 2012/18/EU o jor-accident hazards involving dan		nt and of the C	ouncil on the control of ma-
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 41,16% w/w		
	Directive 2010/75/EU of 2 emissions (integrated pol Volatile organic compour	lution prevent	on and control)
Other regulations:			

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)





Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on



Revision Date: 19.12.2024 Date of last issue: - Version 1.0

Print Date 19.12.2024

personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 H312 H314 H315 H317 H318 H319 H332 H412 H413		Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.
Full text of other abbreviat	ions	
Acute Tox. Aquatic Chronic Eye Dam. Eye Irrit. Skin Corr. Skin Irrit. Skin Sens. PL OEL		Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Skin corrosion Skin irritation Skin sensitisation Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentra- tions and levels of the agents harmful for health in the work- place (Dz.U 2018 pos 1286, with later amendments)
PL OEL / NDS ADR	:	Maximal Admissible Concentration European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	÷	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
Numbry DL 10000054667		10/5

Sikafloor[®]-264 Plus/264 Plus Thixo Part B



evision Date: 19.12.2024 ate of last issue: -	Version 1.0	Print Date 19.12.2024
PBT	: Persistent, bioaccumulative and toxic	
PNEC	: Predicted no effect concentration	
REACH	 Regulation (EC) No 1907/2006 of the E and of the Council of 18 December 200 istration, Evaluation, Authorisation and cals (REACH), establishing a European 	06 concerning the Reg- Restriction of Chemi-
SVHC	: Substances of Very High Concern	5,
vPvB	: Very persistent and very bioaccumulation	ive

Further information

Classification of th	e mixture:	Classification procedure:
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 4	H413	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN