

Version 1.0

Print Date 06.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®] CC 714

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Post treatment agent, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	·

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127	/2/2008)
Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 1, Central nervous system	H372: Causes damage to organs through pro- longed or repeated exposure if inhaled.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

Sikafloor® CC 714



Print Date 06.11.2024

Revision Date: 06.11.2024 Version 1.0 Date of last issue: -

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms :						
Signal word	:	Danger				
Hazard statements	:	H304 I H335 I H336 I H372 0 t	Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs (Central nervous sys- tem) through prolonged or repeated exposure if inhaled.			
		H411	Toxic to aquatic life with long lasting effects.			
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.			
Precautionary statements	:	Prevention:				
·		P210 P260	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe mist or vapours.			
		P200 P273	Avoid release to the environment.			
		Response:				
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.			
		P331 P370 + P378	Do NOT induce vomiting.			
		P391	Collect spillage.			

Hazardous components which must be listed on the label:

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 06.11.2024 Date of last issue: -

Version 1.0

Print Date 06.11.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 40
Hydrocarbons, C9-C12, n- alkanes, isoalkanes, cyclics, aro- matics (2-25%)	Not Assigned 919-446-0 265-185-4 01-2119458049-33- XXXX [corresponding group CAS 64742-82- 1]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 40
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5

For explanation of abbreviations see section 16.





Version 1.0

Print Date 06.11.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	(Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled		Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	\	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	l	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	l	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms	and eff	fects, both acute and delayed
Symptoms	: /	Aspiration may cause pulmonary oedema and pneumonitis.

Symptoms	: Aspiration may cause pulmonary oedema and pneumonitis. Cough Respiratory disorder Erythema Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.
Risks	 May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure if inhaled. Repeated exposure may cause skin dryness or cracking. Risk of serious damage to the lungs (by aspiration). irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------



Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024
SECTION 5: Firefighting meas	sure	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	:	Water High volume water jet	
5.2 Special hazards arising from	the	substance or mixture	
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may fire. Do not allow run-off from fire fighting to en courses.	
Hazardous combustion prod- ucts	:	No hazardous combustion products are kn	nown
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained br	eathing apparatus.
Further information	:	Use water spray to cool unopened contair Collect contaminated fire extinguishing wa must not be discharged into drains. Fire residues and contaminated fire exting be disposed of in accordance with local re	ater separately. This guishing water must

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions	

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-



Version 1.0

miculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Adv	<i>v</i> ice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
	vice on protection against and explosion	•	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hy	giene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Con	ditions for safe storage, in	nclu	uding any incompatibilities
	quirements for storage as and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	ther information on stor- e stability	:	No decomposition if stored and applied as directed.
7.3 Spe	cific end use(s)		
Spe	ecific use(s)	:	Consult most current local Product Data Sheet prior to any use.



Version 1.0

Print Date 06.11.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Hydrocarbons, C9-C12, n-alkanes, isoal- kanes, cyclics, aromatics (2-25%)	Not Assigned	NDS	300 mg/m3	PL OEL
		NDSch	900 mg/m3	PL OEL
reaction mass of ethylbenzene and xy- lene	Not Assigned TWA 50 ppm 2000 221 mg/m3 221 mg/m3 2000<			2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
	STEL 100 ppm 2000/39/EC 442 mg/m3			
	NDS 100 mg/m3 PL OEL			
	Further information: Skin			
	NDSch 200 mg/m3 PL OEL			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipm	nent	
Eve/face protection	:	Safety glasses with side-shields conforming to EN166

Eye/face protection	•	Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator.



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid amber
Odour	:	characteristic
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	> 100 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o		
Upper/lower flammability or o Upper explosion limit / Up- per flammability limit		
Upper explosion limit / Up-	:	Upper explosion limit
Upper explosion limit / Upper flammability limit	:	Upper explosion limit ca. 7 %(V) Lower explosion limit ca. 0,7 %(V)
Upper explosion limit / Up- per flammability limit Lower explosion limit / Lower flammability limit	:	Upper explosion limit ca. 7 %(V) Lower explosion limit ca. 0,7 %(V) > 41 °C

Sikafloor[®] CC 714



Revision Date: 06.11.2024 Date of last issue: -	Version 1.0	Print Date 06.11.2024
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in water)	
Viscosity		
Viscosity, kinematic	: < 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: ca. 100 hPa (20 °C)	
Density	: ca. 0,85 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reacti	io	ns
Hazardous reactions :	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.
10.4 Conditions to avoid Conditions to avoid :	:	Heat, flames and sparks.



Revision Date: 06.11.2024 Date of last issue: -	Version 1.0	Print Date 06.11.2024
10.5 Incompatible materials Materials to avoid	No data available	
10.6 Hazardous decomposition pro	ducts	
	No hazardous decomposition products are know	wn.
SECTION 11: Toxicological info	rmation	
11.1 Information on hazard classes	as defined in Regulation (EC) No 1272/2008	
Acute toxicity		
Not classified due to lack of data <u>Components:</u>		
Hydrocarbons, C9, aromatics:		
-	LD50 Oral (Rat): > 2.000 mg/kg	
Acute dermal toxicity :	LD50 Dermal (Rabbit): > 2.000 mg/kg	
reaction mass of ethylbenzene	and xylene:	
Acute oral toxicity :	LD50 Oral (Rat): 3.523 mg/kg	
Skin corrosion/irritation		
Repeated exposure may cause s	skin dryness or cracking.	
Components:		
Hydrocarbons, C9, aromatics:		
Assessment :	Repeated exposure may cause skin dryness or o	cracking.
Hydrocarbons, C9-C12, n-alka	nes, isoalkanes, cyclics, aromatics (2-25%):	
Assessment : Result :	Repeated exposure may cause skin dryness or o Repeated exposure may cause skin dryness or o	
Serious eye damage/eye irritat	ion	
Not classified due to lack of data		
Respiratory or skin sensitisati	on	
Skin sensitisation		
Not classified due to lack of data		
Respiratory sensitisation Not classified due to lack of data		

Country PL 10000061211

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®] CC 714

Revision Date: 06.11.2024 Date of last issue: -

Version 1.0

Print Date 06.11.2024

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components consid-: ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic	:	(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9
plants		mg/l
		Exposure time: 72 h

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)



Sikafloor[®] CC 714



Version 1.0 Revision Date: 06.11.2024 Print Date 06.11.2024 Date of last issue: -12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential No data available 12.4 Mobility in soil No data available 12.5 Results of PBT and vPvB assessment Product: Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. 12.6 Endocrine disrupting properties Product: Assessment The substance/mixture does not contain components consid-: ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects Product: Additional ecological infor-An environmental hazard cannot be excluded in the event of : unprofessional handling or disposal. mation Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Produc

ct	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed
	waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 3295	
IMDG	:	UN 3295	
ΙΑΤΑ	:	UN 3295	
14.2 UN proper shipping name			
ADR	:	HYDROCARBONS, I (solvent naphtha, nap	
IMDG	:	HYDROCARBONS, I (solvent naphtha, nap	,
ΙΑΤΑ	:	Hydrocarbons, liquid, (solvent naphtha, nap	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)	
IMDG Packing group Labels EmS Code	:	III 3 F-E, S-D	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group	:	355 Y344 III	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®] CC 714



Revision Date: 06.11.2024 Version 1.0 Print Date 06.11.2024 Date of last issue: -: Flammable Liquids Labels 14.5 Environmental hazards ADR Environmentally hazardous ves IMDG Marine pollutant yes IATA (Passenger) Environmentally hazardous yes IATA (Cargo) Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the following entries should be considered: the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Number on list 3 Number on list 75: Regulation (EU) No 649/2012 of the European Parlia-: Not applicable ment and the Council concerning the export and import of dangerous chemicals REACH - Candidate List of Substances of Very High None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %).



Revision Date: 06.11.2024 Date of last issue: -	Version 1.0	Print Date 06.11.2024
REACH - List of substances subje (Annex XIV)	ect to authorisation : Not appli	cable
Regulation (EC) on substances th layer	at deplete the ozone : Not appli	cable
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu- : Not appli	cable
Seveso III: Directive 2012/18/EU o jor-accident hazards involving dar E2	of the European Parliament and of the agerous substances. ENVIRONMENTAL HAZARDS	Council on the control of ma-
P5c	FLAMMABLE LIQUIDS	
34	Petroleum products: (a) gasolines ar (including jet fuels), (c) gas oils (inclu heating oils and gas oil blending stre alternative fuels serving the same pu properties as regards flammability ar as the products referred to in points	uding diesel fuels, home eams),(d) heavy fuel oils (e) urposes and with similar nd environmental hazards
Volatile organic compounds :	Law on the incentive tax for volatile of (VOCV) Volatile organic compounds (VOC) of	.
	Directive 2010/75/EU of 24 November emissions (integrated pollution prever Volatile organic compounds (VOC) of	ention and control)

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Sikafloor[®] CC 714



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

SECTION 16: Other information

Full text of H-Statements					
H226		Elemmable liquid and vanour			
	:	Flammable liquid and vapour.			
H304	•	May be fatal if swallowed and enters airways.			
H312	:	Harmful in contact with skin.			
H315	:	Causes skin irritation.			
H319	:	Causes serious eye irritation.			
H332	:	Harmful if inhaled.			
H335	:	May cause respiratory irritation.			
H336	:	May cause drowsiness or dizziness.			
H372	:	Causes damage to organs through prolonged or repeated			
4979		exposure if inhaled.			
H373	÷	May cause damage to organs through prolonged or repeated exposure if inhaled.			
H411	:	Toxic to aquatic life with long lasting effects.			
H412	:	Harmful to aquatic life with long lasting effects.			
Full text of other abbreviations					
Acute Tox.		Acute toxicity			
Aquatic Chronic	:	Long-term (chronic) aquatic hazard			
Asp. Tox.	:	Aspiration hazard			
Eye Irrit.	:	Eye irritation			
Flam. Lig.	:	Flammable liquids			
Skin Irrit.	:	Skin irritation			
STOT RE	:				
	:	Specific target organ toxicity - repeated exposure			
STOT SE	÷	Specific target organ toxicity - single exposure			
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values			
PL OEL		Ordinance of the Minister of Family, Labour and Social Policy			
0	•	of 12 June 2018 concerning the highest allowable concentra-			
		tions and levels of the agents harmful for health in the work-			
		place (Dz.U 2018 pos 1286, with later amendments)			
2000/39/EC / TWA		Limit Value - eight hours			
2000/39/EC / STEL	:	Short term exposure limit			
PL OEL / NDS	:	Maximal Admissible Concentration			
PL OEL / NDSch	:	Maximal Admissible Concentration Maximal Admissible Temporary Concentration			
ADR	:	European Agreement concerning the International Carriage of			
ADR	·	Dangerous Goods by Road			
CAS	:	Chemical Abstracts Service			
DNEL	:	Derived no-effect level			
EC50		Half maximal effective concentration			
GHS	:	Globally Harmonized System			
IATA	:	International Air Transport Association			
IMDG	:	International Maritime Code for Dangerous Goods			
LD50	:	Median lethal dosis (the amount of a material, given all at			
2000	·	once, which causes the death of 50% (one half) of a group of			
		test animals)			
LC50		Median lethal concentration (concentrations of the chemical in			
2000	·	air that kills 50% of the test animals during the observation			
		period)			
		ponody			

Sikafloor[®] CC 714

_



Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024	
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978		
OEL	:	Occupational Exposure Limit		
PBT	:	Persistent, bioaccumulative and toxic		
PNEC	:	Predicted no effect concentration		
REACH	:	Regulation (EC) No 1907/2006 of the Europe and of the Council of 18 December 2006 cor istration, Evaluation, Authorisation and Restr cals (REACH), establishing a European Che	cerning the Reg- iction of Chemi-	
SVHC	:	Substances of Very High Concern		
vPvB	:	Very persistent and very bioaccumulative		

Further information

Classification of the mixtu	ire:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 1	H372	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL / EN