



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika Boom®-583 Low Expansion

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.
Karczunkowska 89
02-871 Warszawa
Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com
responsible for the SDS

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated	H373: May cause damage to organs through pro-

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

exposure, Category 2	longed or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Category 4	H413: May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H413	May cause long lasting harmful effects to aquatic life.

Precautionary statements :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust or mist.
P263	Avoid contact during pregnancy and while nursing.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023

Version 1.0

Print Date 28.02.2023

Date of last issue: -

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues
alkanes, C14-17, chloro
4,4'-methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 25 - < 40
alkanes, C14-17, chloro	85535-85-9 287-477-0 01-2119519269-33-XXXX	Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	>= 10 - < 20
Glycerol, propoxylated (polymer)	25791-96-2 500-044-5 01-2119484612-36-XXXX	Acute Tox. 4; H302 Acute toxicity estimate Acute oral toxicity: 1.000 mg/kg	>= 5 - < 10

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
 Date of last issue: -

Version 1.0

Print Date 28.02.2023

4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 01-2119457014-47-XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l	>= 2,5 - < 5
octamethylcyclotetrasiloxane [D4]	556-67-2 209-136-7 01-2119529238-36-XXXX	Flam. Liq. 3; H226 Repr. 2; H361f Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 10	>= 0,0025 - < 0,025
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 01-2119472128-37-XXXX	Flam. Gas 1A; H220	>= 5 - < 10
butane	106-97-8 203-448-7 01-2119474691-32-XXXX	Flam. Gas 1A; H220	>= 5 - < 10
propane	74-98-6 200-827-9 01-2119486944-21-XXXX	Flam. Gas 1A; H220	>= 2,5 - < 5

For explanation of abbreviations see section 16.



SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Headache
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause harm to breast-fed children.
May cause damage to organs through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
 Date of last issue: -

Version 1.0

Print Date 28.02.2023

Do not get in eyes, on skin, or on clothing.
 For personal protection see section 8.
 Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharge.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Follow standard hygiene measures when handling chemical products

- Advice on protection against fire and explosion : Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	NDS	0,03 mg/m3	PL OEL
		NDSch	0,09 mg/m3	PL OEL
dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
 Date of last issue: -

Version 1.0

Print Date 28.02.2023

			1.920 mg/m3	
Further information: Indicative				
		NDS	1.000 mg/m3	PL OEL
butane	106-97-8	NDS	1.900 mg/m3	PL OEL
		NDSch	3.000 mg/m3	PL OEL
propane	74-98-6	NDS	1.800 mg/m3	PL OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	NDS	0,03 mg/m3	PL OEL
		NDSch	0,09 mg/m3	PL OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
 Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
 Eye wash bottle with pure water

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

 Suitable for short time use or protection against splashes:
 Butyl rubber/nitrile rubber gloves (> 0,1 mm)
 Contaminated gloves should be removed.
 Suitable for permanent exposure:
 Viton gloves (0.4 mm),
 breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).

- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
 organic vapor (Type A) and particulate filter
 A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
 P1: Inert material; P2, P3: hazardous substances
 Ensure adequate ventilation, especially in confined areas.
 When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
 If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: aerosol
Colour	: light yellow, yellow
Odour	: slight
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flammability	: Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
pH	: Not applicable substance/mixture reacts with water
Viscosity	
Viscosity, kinematic	: No data available
Solubility(ies)	
Water solubility	: substance/mixture reacts with water
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: 5100 hPa

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

Density : ca. 1 g/cm³ (23 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Glycerol, propoxylated (polymer):

Acute oral toxicity : LD50 Oral (Rat): > 1.000 mg/kg

Acute toxicity estimate: 1.000 mg/kg
Method: Calculation method

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l
Test atmosphere: dust/mist
Method: Calculation method

octamethylcyclotetrasiloxane [D4]:

Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Causes skin irritation.

Components:

alkanes, C14-17, chloro:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.



Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
Exposure time: 72 h

alkanes, C14-17, chloro:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10



12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

Components:

octamethylcyclotetrasiloxane [D4]:

Assessment : PBT substance.
: vPvB substance.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

- European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

- ADR : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

- ADR : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

- | | Class | Subsidiary risks |
|------|-------|------------------|
| ADR | : 2 | 2.1 |
| IMDG | : 2.1 | |
| IATA | : 2.1 | |

14.4 Packing group

- ADR**
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

- IMDG**
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

- IATA (Cargo)**
Packing instruction (cargo aircraft) : 203

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Diphenylmethanediisocyanate, isomers and homologues (Number on list 74, 56)
4,4'-methylenediphenyl diisocyanate (Number on list 74, 56)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : alkanes, C14-17, chloro

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 19% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 19% w/w

Other regulations:

75/324/EEC

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC,

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. 2005 Nr. 259, item 2173 with later amendments).

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended).

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450 with later amendments).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H361f	:	Suspected of damaging fertility.
H362	:	May cause harm to breast-fed children.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Lact.	:	Effects on or via lactation
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
PL OEL	:	Poland. Occupational exposure limits for airborne toxic substances
2000/39/EC / TWA	:	Limit Value - eight hours
PL OEL / NDS	:	Maximal Admissible Concentration
PL OEL / NDSch	:	Maximal Admissible Temporary Concentration
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023

Version 1.0

Print Date 28.02.2023

Date of last issue: -

GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
Lact.	H362
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 4	H413

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Based on product data or assessment

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL / EN

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika Boom®-583 Low Expansion



Revision Date: 28.02.2023
Date of last issue: -

Version 1.0

Print Date 28.02.2023
