according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Date of last issue: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaPower®-415

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.

Karczunkowska 89 02-871 Warszawa

Telephone : +48 22 27 28 700
Telefax : +48 22 27 28 800
E-mail address of person : EHS@pl.sika.com

responsible for the SDS

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Warning

Hazard statements : H315 Causes skin irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025 Date of last issue: -

H317 May cause an allergic skin reaction.
H319 Causes serious eve irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked
Hardener LI (Isophoronedialdimine)
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
Cashew, nutshell liq.

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.


Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415

Revision Date: 10.02.2025



Date of last issue: -

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20
		specific concentration limit Eye Irrit. 2; H319 >= 5 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
calcium oxide	1305-78-8 215-138-9 01-2119475325-36- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	>= 3 - < 5
Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked	1617507-45-5 Not Assigned	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 2,5 - < 5
Hardener LI (Isophoronedial-dimine)	932742-30-8 700-071-4 01-2119880654-28- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
1,3-Isobenzofurandione, reaction products with diethylenetriamine	Not Assigned 942-764-6 01-2120096580-52- XXXX	Acute Tox. 4; H302 Aquatic Chronic 2; H411	>= 1 - < 2,5
2,2-Dimethyl-3-lauroyloxy- propanal	102985-93-3 468-880-2 01-0000019675-60- XXXX	Aquatic Chronic 3; H412	>= 1 - < 2,5

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415

Revision Date: 10.02.2025



Date of last issue: -

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % specific concentration limit Skin Sens. 1; H317 >= 0,5 % Acute toxicity estimate Acute inhalation toxicity (dust/mist):	>= 0,1 - < 0,25
Cashew, nutshell liq.	8007-24-7 700-991-6 01-2119502450-57- XXXX	O,031 mg/l Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute toxicity estimate Acute oral toxicity: 500 mg/kg Acute dermal toxicity: 2.000 mg/kg	>= 0,1 - < 0,5
salicylic acid	69-72-7 200-712-3 01-2119486984-17- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d Acute toxicity estimate Acute oral toxicity: 891 mg/kg	>= 0,1 - < 0,5

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

Substances with a workplace exposure limit :				
bis(2-ethylhexyl) adipate	103-23-1		>= 2,5 - < 5	
	203-090-1			
	01-2119439699-19-			
	XXXX			

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Date of last issue: -

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
calcium oxide	1305-78-8	TWA (Respirable	1 mg/m3	2017/164/EU
		fraction)	-	
	Further information: Indicative			
		STEL (Respirable	4 mg/m3	2017/164/EU
		fraction)	-	
		NDS (inhalable	2 mg/m3	PL OEL
		fraction)		
		NDS (respirable	1 mg/m3	PL OEL
		fraction)		
		NDSch (inhalable	6 mg/m3	PL OEL
		fraction)		
		NDSch (respirable	4 mg/m3	PL OEL
		fraction)		
bis(2-ethylhexyl) adipate	103-23-1	NDS	400 mg/m3	PL OEL

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

3-isocyanatomethyl-3,5,5- 4098-71-9 NDS 0,04 mg/m3 PL OEL trimethylcyclohexyl isocyanate

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour black

Odour odourless

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

: > 150 °C Flash point

Method: closed cup

Auto-ignition temperature No data available

Decomposition temperature No data available

Not applicable pН

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic No data available

Solubility(ies)

Water solubility No data available

Partition coefficient: n-

octanol/water

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415

Revision Date: 10.02.2025



Date of last issue: -

Vapour pressure : 0,01 hPa

Density : ca. 1,3 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Date of last issue: -

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Hardener LI (Isophoronedialdimine):

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

Cashew, nutshell liq.:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

Acute toxicity estimate: 500 mg/kg Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): 2.000 mg/kg

Acute toxicity estimate: 2.000 mg/kg

Method: Calculation method

salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

bis(2-ethylhexyl) adipate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415

Revision Date: 10.02.2025



Date of last issue: -

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Method : OECD Test Guideline 405

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Toxicology data for the components

Information given is based on data on the components and

the toxicology of similar products.

Based on available data, the classification criteria are not met.

Country PL 100000026770



12 / 20

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Date of last issue: -

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

Hardener LI (Isophoronedialdimine):

LC50 (Fish): 87,2 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l

Exposure time: 72 h

2,2-Dimethyl-3-lauroyloxy-propanal:

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 0,18 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,352 mg/l

Species: Danio rerio (zebra fish) Method: OECD Test Guideline 210

GLP: yes

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,24 mg/l

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

GLP: yes

Toxicity to terrestrial organ-

isms

LC50: > 1.000 mg/kgExposure time: 14 d

End point: Acute contact toxicity Method: OECD Test Guideline 207

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Date of last issue: -

bis(2-ethylhexyl) adipate:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 500 mg/l

aquatic invertebrates

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Scenedesmus quadricauda (Green algae)): > 500 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

Components:

2,2-Dimethyl-3-lauroyloxy-propanal:

Biodegradability Biodegradation: 85,6 %

Method: OECD Test Guideline 301F

Remarks: Readily biodegradable, according to appropriate

OECD test.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Components:

2,2-Dimethyl-3-lauroyloxy-propanal:

Distribution among environ-

Adsorption/Soil

mental compartments

Koc: 1,5 - 5 ml/g, log Koc: 4,29 Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-An environmental hazard cannot be excluded in the event of

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

unprofessional handling or disposal. mation

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.2 UN proper shipping name

ADR Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.4 Packing group

ADR Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA (Cargo) Not regulated as a dangerous good

IATA (Passenger) Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 74: 3isocyanatomethyl-3,5,5trimethylcyclohexyl isocyanate

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parlia: Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

ment and the Council concerning the export and import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)
Not applicable

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H330 : Fatal if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation.

H361d : Suspected of damaging the unborn child.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values

PL OEL : Ordinance of the Minister of Family, Labour and Social Policy

of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the work-

place (Dz.U 2018 pos 1286, with later amendments)

2017/164/EU / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

PL OEL / NDS : Maximal Admissible Concentration

PL OEL / NDSch : Maximal Admissible Temporary Concentration

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method

Eye Irrit. 2 H319 Based on product data or assessment

Skin Sens. 1 H317 Calculation method Aquatic Chronic 3 H412 Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaPower®-415



Revision Date: 10.02.2025 Version 1.0 Print Date 10.02.2025

Date of last issue: -

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

PL/EN