

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaRoof® Adhesive C-300

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Poland Spółka z o.o.  
Karczunkowska 89  
02-871 Warszawa  
Telephone : +48 22 27 28 700  
Telefax : +48 22 27 28 800  
E-mail address of person responsible for the SDS : EHS@pl.sika.com

#### 1.4 Emergency telephone number

112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |   |
|--|---|
| Flammable liquids, Category 2  | H225: Highly flammable liquid and vapour.   |
| Acute toxicity, Category 4   | H332: Harmful if inhaled.   |
| Skin irritation, Category 2  | H315: Causes skin irritation.   |
| Eye irritation, Category 2   | H319: Causes serious eye irritation.  |
| Respiratory sensitisation, Category 1  | H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.    |
| Skin sensitisation, Category 1   | H317: May cause an allergic skin reaction.  |
| Carcinogenicity, Category 2  | H351: Suspected of causing cancer.  |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation.   |
| Specific target organ toxicity - repeated exposure, Category 2                   | H373: May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Long-term (chronic) aquatic hazard, Category 3                                   | H412: Harmful to aquatic life with long lasting effects.                            |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025

Version 3.0

Print Date 04.03.2026

Date of last issue: 28.03.2025

|                          |   |  |
|--------------------------|---|--|
| Hazard pictograms        | : |      |
| Signal word              | : | Danger   |
| Hazard statements        | : | H225 Highly flammable liquid and vapour.<br>H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H319 Causes serious eye irritation.<br>H332 Harmful if inhaled.<br>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>H335 May cause respiratory irritation.<br>H351 Suspected of causing cancer.<br>H373 May cause damage to organs through prolonged or repeated exposure if inhaled.<br>H412 Harmful to aquatic life with long lasting effects.  |
| Precautionary statements | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P260 Do not breathe mist or vapours.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.<br><b>Response:</b><br>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.<br>P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.<br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

### Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification   | Concentration<br>(% w/w) |
|--|---|--|--------------------------|
| Diphenylmethanediisocyanate, isomeres and homologues | 9016-87-9<br>Not Assigned                             | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>Carc. 2; H351<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br><br>specific concentration<br>limit<br>Eye Irrit. 2; H319<br>>= 5 %<br><br>specific concentration<br>limit<br>Resp. Sens. 1; H334<br>>= 0,1 %<br><br>specific concentration<br>limit<br>Skin Irrit. 2; H315<br>>= 5 %<br><br>specific concentration<br>limit<br>STOT SE 3; H335<br>>= 5 % | >= 25 - < 40             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025

Version 3.0

Print Date 04.03.2026

Date of last issue: 28.03.2025

|                |  |   |              |
|----------------|--|---|--------------|
| methyl acetate | 79-20-9<br>201-185-2<br>607-021-00-X<br>01-2119459211-47-XXXX  | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>EUH066   | >= 10 - < 20 |
| ethyl acetate  | 141-78-6<br>205-500-4<br>607-022-00-5<br>01-2119475103-46-XXXX | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>(Central nervous system)<br>EUH066   | >= 2,5 - < 5 |
| cyclohexane    | 110-82-7<br>203-806-2<br>601-017-00-1<br>01-2119463273-41-XXXX | Flam. Liq. 2; H225<br>Asp. Tox. 1; H304<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410 | >= 1 - < 2,5 |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Asthmatic appearance  
Cough  
Respiratory disorder

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

|       |   |
|-------|---|
|       | Allergic reactions<br>Excessive lachrymation<br>Erythema<br>Headache<br>Dermatitis<br>See Section 11 for more detailed information on health effects and symptoms.  |
| Risks | : irritant effects<br>sensitising effects<br><br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>Harmful if inhaled.<br>May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>May cause respiratory irritation.<br>Suspected of causing cancer.<br>May cause damage to organs through prolonged or repeated exposure if inhaled. |

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components   | CAS-No.   | Value type (Form of exposure)  | Control parameters *               | Basis *     |
|--|-----------|--|------------------------------------|-------------|
| Diphenylmethanediisocyanate, isomeres and homologues | 9016-87-9 | NDS  | 0,03 mg/m <sup>3</sup>             | PL OEL      |
|  |           | NDSch  | 0,09 mg/m <sup>3</sup>             | PL OEL      |
|  |           | TWA  | 0,01 mg/m <sup>3</sup> (NCO)       | 98/24/EC I  |
|  |           | Further information: Skin, Dermal and respiratory sensitisation, Binding |                                    |             |
|  |           | STEL   | 0,02 mg/m <sup>3</sup> (NCO)       | 98/24/EC I  |
| methyl acetate                                       | 79-20-9   | NDS  | 250 mg/m <sup>3</sup>              | PL OEL      |
|  |           | NDSch  | 600 mg/m <sup>3</sup>              | PL OEL      |
| ethyl acetate  | 141-78-6  | STEL   | 400 ppm<br>1.468 mg/m <sup>3</sup> | 2017/164/EU |
|  |           | Further information: Indicative  |                                    |             |
|  |           | TWA  | 200 ppm<br>734 mg/m <sup>3</sup>   | 2017/164/EU |
|  |           | NDS  | 200 ppm<br>734 mg/m <sup>3</sup>   | PL OEL      |
|  |           | NDSch  | 400 ppm<br>1.468 mg/m <sup>3</sup> | PL OEL      |
| cyclohexane  | 110-82-7  | TWA  | 200 ppm<br>700 mg/m <sup>3</sup>   | 2006/15/EC  |
|  |           | Further information: Indicative  |                                    |             |
|  |           | NDS  | 300 mg/m <sup>3</sup>              | PL OEL      |
|  |           | Further information: Skin  |                                    |             |
|  |           | NDSch  | 1.000 mg/m <sup>3</sup>            | PL OEL      |

\*The above mentioned values are in accordance with the legislation in effect at the date of the re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

lease of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.  
Ensure adequate ventilation, especially in confined areas.

#### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

Physical state : liquid  
Form : viscous liquid  
Colour : yellow  
Odour : slight

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : 57 °C

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : Upper flammability limit  
per flammability limit 16 %(V)

Lower explosion limit / Lower flammability limit : Lower flammability limit  
3,1 %(V)

Flash point : -13 °C  
Method: closed cup

Auto-ignition temperature : 400 °C

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, dynamic : ca. 4.600 mPa.s

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : practically insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 228 hPa (20 °C)

Density : ca. 1,1 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Harmful if inhaled.

##### Components:

##### **Diphenylmethanediisocyanate, isomeres and homologues:**

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

##### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Suspected of causing cancer.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

May cause respiratory irritation.

#### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

Not classified due to lack of data.

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Diphenylmethanediisocyanate, isomeres and homologues:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l  
Exposure time: 72 h

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 1133  
IMDG : UN 1133  
IATA : UN 1133

#### 14.2 UN proper shipping name

- ADR : ADHESIVES  
IMDG : ADHESIVES  
IATA : Adhesives

#### 14.3 Transport hazard class(es)

- |      | Class | Subsidiary risks |
|------|-------|------------------|
| ADR  | : 3   |                  |
| IMDG | : 3   |                  |
| IATA | : 3   |                  |

#### 14.4 Packing group

- ADR

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

Packing group : III  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (E)  
Remarks : Transport according to 2.2.3.1.4 ADR.

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Remarks : Transport according to 2.3.2.2 IMDG.

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids  
Remarks : Transport according to 3.3.3.1.1 IATA.

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025

Version 3.0

Print Date 04.03.2026

Date of last issue: 28.03.2025

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 40:

methyl acetate, ethyl acetate, cyclohexane

Number on list 56: Diphenylmethanediisocyanate, isomeres and homologues

Number on list 57: cyclohexane

Number on list 74: Diphenylmethanediisocyanate, isomeres and homologues

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

Volatile organic compounds (VOC) content: 18% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 18% w/w

### Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amend-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025  
Date of last issue: 28.03.2025

Version 3.0

Print Date 04.03.2026

ed).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

|      |   |   |
|------|---|---|
| H225 | : | Highly flammable liquid and vapour.   |
| H304 | : | May be fatal if swallowed and enters airways.                                 |
| H315 | : | Causes skin irritation.   |
| H317 | : | May cause an allergic skin reaction.  |
| H319 | : | Causes serious eye irritation.  |
| H332 | : | Harmful if inhaled.   |
| H334 | : | May cause allergy or asthma symptoms or breathing difficulties if inhaled.    |
| H335 | : | May cause respiratory irritation.   |
| H336 | : | May cause drowsiness or dizziness.  |
| H351 | : | Suspected of causing cancer.  |
| H373 | : | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H400 | : | Very toxic to aquatic life.   |
| H410 | : | Very toxic to aquatic life with long lasting effects.                         |

### Full text of other abbreviations

|                 |   |   |
|-----------------|---|---|
| Acute Tox.      | : | Acute toxicity  |
| Aquatic Acute   | : | Short-term (acute) aquatic hazard                       |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard                      |
| Asp. Tox.       | : | Aspiration hazard                                       |
| Carc.           | : | Carcinogenicity   |
| Eye Irrit.      | : | Eye irritation  |
| Flam. Liq.      | : | Flammable liquids                                       |
| Resp. Sens.     | : | Respiratory sensitisation                               |
| Skin Irrit.     | : | Skin irritation   |
| Skin Sens.      | : | Skin sensitisation                                      |
| STOT RE         | : | Specific target organ toxicity - repeated exposure      |
| STOT SE         | : | Specific target organ toxicity - single exposure        |
| 2006/15/EC      | : | Europe. Indicative occupational exposure limit values   |
| 2017/164/EU     | : | Europe. Commission Directive 2017/164/EU establishing a |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025

Version 3.0

Print Date 04.03.2026

Date of last issue: 28.03.2025

|                    |   |  |
|--------------------|---|--|
| 98/24/EC I         | : | fourth list of indicative occupational exposure limit values<br>Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values  |
| PL OEL             | : | Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments) |
| 2006/15/EC / TWA   | : | Limit Value - eight hours  |
| 2017/164/EU / STEL | : | Short term exposure limit  |
| 2017/164/EU / TWA  | : | Limit Value - eight hours  |
| 98/24/EC I / STEL  | : | Limit values Short-term  |
| 98/24/EC I / TWA   | : | Limit values 8 hours   |
| PL OEL / NDS       | : | Maximal Admissible Concentration   |
| PL OEL / NDSch     | : | Maximal Admissible Temporary Concentration   |
| ADR                | : | European Agreement concerning the International Carriage of Dangerous Goods by Road  |
| CAS                | : | Chemical Abstracts Service   |
| DNEL               | : | Derived no-effect level  |
| EC50               | : | Half maximal effective concentration   |
| GHS                | : | Globally Harmonized System   |
| IATA               | : | International Air Transport Association  |
| IMDG               | : | International Maritime Code for Dangerous Goods  |
| LD50               | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  |
| LC50               | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL             | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL                | : | Occupational Exposure Limit  |
| PBT                | : | Persistent, bioaccumulative and toxic  |
| PNEC               | : | Predicted no effect concentration  |
| REACH              | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency   |
| SVHC               | : | Substances of Very High Concern  |
| vPvB               | : | Very persistent and very bioaccumulative   |

### Further information

#### Classification of the mixture:

|               |      |
|---------------|------|
| Flam. Liq. 2  | H225 |
| Acute Tox. 4  | H332 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2  | H319 |
| Resp. Sens. 1 | H334 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaRoof® Adhesive C-300



Revision Date: 26.11.2025

Version 3.0

Print Date 04.03.2026

Date of last issue: 28.03.2025

---

|                   |      |                    |
|-------------------|------|--------------------|
| Skin Sens. 1      | H317 | Calculation method |
| Carc. 2           | H351 | Calculation method |
| STOT SE 3         | H335 | Calculation method |
| STOT RE 2         | H373 | Calculation method |
| Aquatic Chronic 3 | H412 | Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

PL / EN