

Revision Date: 06.11.2024 Date of last issue: -

Version 1.0

Print Date 06.11.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikafloor® CC 713

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Post treatment agent, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	·

#### 1.4 Emergency telephone number

112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127 Flammable liquids, Category 3	<b>72/2008)</b> H226: Flammable liquid and vapour.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 1, Central nervous system	H372: Causes damage to organs through pro- longed or repeated exposure if inhaled.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

## Sikafloor<sup>®</sup> CC 713



Revision Date: 06.11.2024 Date of last issue: -

## 2.2 Label elements

Laber elements		
Labelling (REGULATION (EC	) No 1272/20	08)
Hazard pictograms :		
Signal word :	Danger	
Hazard statements :	H226 H304 H335 H336 H362 H372	Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. May cause harm to breast-fed children. Causes damage to organs (Central nervous sys- tem) through prolonged or repeated exposure if inhaled.
	H411	Toxic to aquatic life with long lasting effects.
Supplemental Hazard : Statements	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements :	Preventio	n:
	P201 P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260 P263	Do not breathe mist or vapours. Avoid contact during pregnancy and while nursing.
	P273	Avoid release to the environment.
	Response	:
	P301 + P3	10 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	P331 P370 + P3	<ul><li>Do NOT induce vomiting.</li><li>78 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.</li></ul>
	P391	Collect spillage.

Version 1.0

#### Hazardous components which must be listed on the label:

Hydrocarbons, C9, aromatics Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) alkanes, C14-17, chloro

#### 2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Print Date 06.11.2024



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 60 - < 80
Hydrocarbons, C9-C12, n- alkanes, isoalkanes, cyclics, aro- matics (2-25%)	Not Assigned 919-446-0 265-185-4 01-2119458049-33- XXXX [corresponding group CAS 64742-82- 1]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
alkanes, C14-17, chloro	85535-85-9 287-477-0 01-2119519269-33- XXXX	Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	>= 1 - < 2,5

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# **Jika**®

## Sikafloor® CC 713 Revision Date: 06.11.2024 Version 1.0 Date of last issue: -

rision Date: 06.11.2024 e of last issue: -	Version 1	Version 1.0		
toluene	108-88-3 203-625-9 01-2119471310-51- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 0,5 - < 1	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid mea	sures
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	<ul> <li>Aspiration may cause pulmonary oedema and pneumonitis. Cough Respiratory disorder Erythema Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.</li> </ul>
Risks	<ul> <li>May be fatal if swallowed and enters airways.</li> <li>May cause respiratory irritation.</li> <li>May cause drowsiness or dizziness.</li> <li>May cause harm to breast-fed children.</li> <li>Causes damage to organs through prolonged or repeated exposure if inhaled.</li> </ul>



Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024
		Repeated exposure may cause skin dryness or	cracking.
		Risk of serious damage to the lungs (by aspirati irritant effects	on).
4.3 Indication of any immediate r	neo	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	:	Water High volume water jet	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter fire.	er and spread
		Do not allow run-off from fire fighting to enter dra courses.	ains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	g apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water se must not be discharged into drains. Fire residues and contaminated fire extinguishir be disposed of in accordance with local regulation	ig water must

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Use personal protective equipment.
	Remove all sources of ignition.
	Deny access to unprotected persons.
	Beware of vapours accumulating to form explosive concentra-
	tions. Vapours can accumulate in low areas.



Revision Date: 06.11.2024	Version 1.0	Print Date 06.11.2024
Date of last issue: -		

#### 6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
		respective autionities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

,	Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Take precautionary measures against static discharge.</li> <li>Open drum carefully as content may be under pressure.</li> <li>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
	Advice on protection against ire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
ł	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 C	onditions for safe storage, in	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.



Revision Date: 06.11.2024	Version 1.0	Print Date 06.11.2024
Date of last issue: -		

#### 7.3 Specific end use(s)

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Hydrocarbons, C9-C12, n-alkanes, isoal- kanes, cyclics, aromatics (2-25%)	Not Assigned	NDS	300 mg/m3	PL OEL
		NDSch	900 mg/m3	PL OEL
toluene	108-88-3	TWA	50 ppm 192 mg/m3	2006/15/EC
	Further inform	ation: Indicative, Ide rough the skin	entifies the possib	ility of signifi-
		STEL	100 ppm 384 mg/m3	2006/15/EC
		NDS	100 mg/m3	PL OEL
	Further inform	ation: Skin		
		NDSch	200 mg/m3	PL OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-
tion (EU) 2020/878
Sikafloor <sup>®</sup> CC 713



Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024
Respiratory protection	Respira exposur ing limit organic A1: < 10 P1: Iner Ensure exhaust ods for ticular to to keep	of inadequate ventilation weat tor selection must be based of re levels, the hazards of the p s of the selected respirator. vapor (Type A) and particulat 000 ppm; A2: < 5000 ppm; A3 t material; P2, P3: hazardous adequate ventilation. This can extraction or by general vent determining inhalation expose to the mixing / stirring area. In the concentrations under the en respiration protection mea	on known or anticipated broduct and the safe work- te filter 3: < 10000 ppm s substances n be achieved by local tilation. (EN 689 - Meth- ure). This applies in par- case this is not sufficent e occupational exposure
Environmental exposur	e controls		
General advice	If the pr	product from entering drains oduct contaminates rivers and ive authorities.	

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid brown
Odour	:	aromatic
Melting point/freezing point	:	< -40 °C
Boiling point/boiling range	:	110 - 140 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	ехр	losive limits
Upper explosion limit / Up- per flammability limit	:	Upper explosion limit ca. 7 %(V)
Lower explosion limit / Lower flammability limit	:	Lower explosion limit ca. 1 %(V)
Flash point	:	> 39 °C Method: closed cup
Auto-ignition temperature	:	235 °C

## Sikafloor<sup>®</sup> CC 713



Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024
Decomposition temperature	:	No data available	
рH	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	3,1 - 3,8 hPa (20 °C)	
Density	:	ca. 0,95 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
······	-		
Particle characteristics	:	No data available	

#### 9.2 Other information

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

#### SAFETY DATA SHEET according to Regulation (EC) No. 1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor® CC 713

## **Jika**®

Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024
Conditions to avoid	:	Heat, flames and sparks.	
10.5 Incompatible materials			
Materials to avoid	:	No data available	
10.6 Hazardous decomposition p	oro	ducts	
	:	No hazardous decomposition products are know	wn.
SECTION 11: Toxicological inf			
	es	as defined in Regulation (EC) No 1272/2008	
Acute toxicity Not classified due to lack of da	ata.		
Components:			
Hydrocarbons, C9, aromatics Acute oral toxicity	:s: :	LD50 Oral (Rat): > 2.000 mg/kg	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg	
Skin corrosion/irritation Repeated exposure may cause <u>Components:</u>	e s	kin dryness or cracking.	
Hydrocarbons, C9, aromatics	s:		
Assessment	:	Repeated exposure may cause skin dryness or o	cracking.
Hydrocarbons, C9-C12, n-alk	kar	nes, isoalkanes, cyclics, aromatics (2-25%):	
Assessment Result	:	Repeated exposure may cause skin dryness or on Repeated exposure may cause skin dryness or one of the second secon	
alkanes, C14-17, chloro:			
Assessment	:	Repeated exposure may cause skin dryness or o	cracking.
Serious eye damage/eye irrit Not classified due to lack of da			
Respiratory or skin sensitisa	atio	on	
Skin sensitisation Not classified due to lack of da	ata.		

## Sikafloor<sup>®</sup> CC 713

**Jika**®

Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

#### **Reproductive toxicity**

May cause harm to breast-fed children.

#### STOT - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

#### STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

#### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

Hydrocarbons, C9, aromatics:					
Toxicity to algae/aquatic plants	:	(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l Exposure time: 72 h			
<b>alkanes, C14-17, chloro:</b> M-Factor (Acute aquatic tox- icity)	:	1			
M-Factor (Chronic aquatic toxicity)	:	10			

1

## Sikafloor<sup>®</sup> CC 713



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

#### **12.6 Endocrine disrupting properties**

#### Product:

Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods Product The generation of waste should be avoided or minimized 5 wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

SECTION 14: Transport information			
14.1 UN number or ID number			
ADR	:	UN 1993	
IMDG	:	UN 1993	
ΙΑΤΑ	:	UN 1993	
14.2 UN proper shipping name			
ADR	:	FLAMMABLE LIQUID, N.O.S. (solvent naphtha, naphtha (petroleum))	
IMDG	:	FLAMMABLE LIQUID, N.O.S. (solvent naphtha, naphtha (petroleum), alkanes, C14-17, chlo- ro)	
ΙΑΤΑ	:	Flammable liquid, n.o.s. (solvent naphtha, naphtha (petroleum))	
14.3 Transport hazard class(es)			
		Class Subsidiary risks	
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)	
<b>IMDG</b> Packing group Labels EmS Code	:	III 3 F-E, S-E	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ)	:	366 Y344	
Packing group Labels	:	III Flammable Liquids	
IATA (Passenger) Packing group Labels	:	III Flammable Liquids	

## Sikafloor<sup>®</sup> CC 713

Revision Date: 06.11.2024 Version 1.0 Print Date 06.11.2024 Date of last issue: -

#### 14.5 Environmental hazards

ADR Environmentally hazardous : yes IMDG Marine pollutant yes IATA (Passenger) Environmentally hazardous yes : IATA (Cargo) Environmentally hazardous : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

**REACH Information:** 

- All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 48: toluene
		Number on list 75:
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	alkanes, C14-17, chloro



## Sikafloor<sup>®</sup> CC 713



sion Date: 06.11.2024 e of last issue: -	Version 1.0	Print Date 06.11.202		
REACH - List of substances s (Annex XIV)	ubject to authorisation : Not applicab	le		
Regulation (EC) on substance layer	es that deplete the ozone : Not applicable	le		
Regulation (EU) 2019/1021 or tants (recast)	n persistent organic pollu- : Not applicab	le		
Seveso III: Directive 2012/18/ jor-accident hazards involving E2	EU of the European Parliament and of the Co dangerous substances. ENVIRONMENTAL HAZARDS	ouncil on the control of ma-		
P5c	FLAMMABLE LIQUIDS			
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)			
Volatile organic compounds	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 75,9% w/w			
	Directive 2010/75/EU of 24 November 2	010 on industrial		

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as



Revision Date: 06.11.2024 Date of last issue: - Version 1.0

Print Date 06.11.2024

amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### Full text of H-Statements

H225

: Highly flammable liquid and vapour.

### Sikafloor<sup>®</sup> CC 713



Revision Date: 06.11.2024 Version 1.0 Print Date 06.11.2024 Date of last issue: -H226 Flammable liquid and vapour. : May be fatal if swallowed and enters airways. H304 Causes skin irritation. H315 May cause respiratory irritation. H335 May cause drowsiness or dizziness. H336 H361d Suspected of damaging the unborn child. May cause harm to breast-fed children. H362 H372 Causes damage to organs through prolonged or repeated exposure if inhaled. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. : H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. Full text of other abbreviations Aquatic Acute Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Aquatic Chronic 1 Asp. Tox. Aspiration hazard : Flam. Liq. Flammable liquids : Effects on or via lactation Lact. Repr. Reproductive toxicity Skin Irrit. Skin irritation STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure 2006/15/EC Europe. Indicative occupational exposure limit values Ordinance of the Minister of Family, Labour and Social Policy PL OEL of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments) Limit Value - eight hours 2006/15/EC / TWA : Short term exposure limit 2006/15/EC / STEL PL OEL / NDS Maximal Admissible Concentration PL OEL / NDSch Maximal Admissible Temporary Concentration European Agreement concerning the International Carriage of ADR Dangerous Goods by Road CAS **Chemical Abstracts Service** Derived no-effect level DNEL **EC50** Half maximal effective concentration GHS **Globally Harmonized System** International Air Transport Association IATA : IMDG International Maritime Code for Dangerous Goods : LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) LC50 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) International Convention for the Prevention of Pollution from MARPOL Ships, 1973 as modified by the Protocol of 1978 OEL **Occupational Exposure Limit** PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration





Revision Date: 06.11.2024 Date of last issue: -		Version 1.0	Print Date 06.11.2024			
REACH	and of the Co istration, Eva	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency				
SVHC	•	: Substances of Very High Concern				
vPvB		Very persistent and very bioaccumulative				
Further information						
Classification of the m	ixture:	Classification p	rocedure:			
Flam. Liq. 3	H226	Based on produc	t data or assessment			
Lact.	H362	Calculation meth	od			
STOT SE 3	H336	Calculation meth	od			
STOT SE 3	H335	Calculation meth	od			
STOT RE 1	H372	Calculation meth	od			
Asp. Tox. 1	H304	Calculation meth	od			
Aquatic Chronic 2	H411	Calculation meth	od			

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL / EN