Version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®]-295 N

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person responsible for the SDS	: EHS@pl.sika.com

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 H412	May cause an allergic skin reaction. Harmful to aquatic life with long lasting ef- fects.
Precautionary statements	:	Prevention:	

Sikaflex[®]-295 N

Print Date 05.02.2024

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0

P261 P273 P280	Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.
	P273 P280 Response: P333 + P313 P362 + P364 Disposal:

Hazardous components which must be listed on the label:

aliphatic prepolymer (t-polyether based) aliphatic prepolymer (d-polyether based) bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate 2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate Pentamethyl piperidylsebacate

Additional Labelling

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not
	breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 26.05.2023 Date of last issue: 08.03.2023



Version 4.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
aliphatic prepolymer (t-polyether based)	138626-39-8 Not Assigned	Skin Sens. 1; H317	>= 10 - < 20
aliphatic prepolymer (d-polyether based)	39323-37-0 Not Assigned	Skin Sens. 1; H317	>= 5 - < 10
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
bis[2-[2-(1-methylethyl)-3- oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	59719-67-4 261-879-6 01-2119983487-19- XXXX	Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit	>= 0,25 - < 0,5
		Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	
		Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l	

Sikaflex®-295 N

Print Date 05.02.2024

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]- 1,3-propanediyl diacrylate	15625-89-5 239-701-3 01-2119489896-11- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 0,5	
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1		
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25	
Substances with a workplace exposure limit :				
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 2,5 - < 5	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice.

Jika ®
Print Date 05.02.2024

Revision Date: 26.05.2023 Date of last issue: 08.03.2023	Version 4.0	Print Date 05.02.20
	Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco	nscious person.
4.2 Most important symptoms ar	d effects, both acute and delayed	
Symptoms	: Allergic reactions See Section 11 for more detailed information and symptoms.	tion on health effects
Risks	: sensitising effects	
	May cause an allergic skin reaction.	
4.3 Indication of any immediate I	nedical attention and special treatment nee	eded
-	T () ()	
	: Treat symptomatically.	
SECTION 5: Firefighting meas	sures	
SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media	sures : In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/cher extinction.	
SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from	sures : In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/cher extinction.	mical powder for
 SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion products 	sures : In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/cher extinction. the substance or mixture	mical powder for
 SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- 	 Sures In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/chere extinction. the substance or mixture No hazardous combustion products are k 	mical powder for nown

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

Jika ®
Print Date 05.02.2024

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	incl	uding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

7.3 Specific end use(s)

age stability

Further information on stor-

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

No decomposition if stored and applied as directed.

SECTION 8: Exposure controls/personal protection

:

8.1 Control parameters

Occupational Exposure Limits



Revision Date: 26.05.2023 Date of last issue: 08.03.2023

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	NDS (inhalable fraction)	10 mg/m3	PL OEL
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	NDS	0,04 mg/m3	PL OEL

Version 4.0

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis[2-[2-(1-methylethyl)- 3-oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	Workers	Inhalation	Long-term systemic effects	29,4 mg/m3
	Workers	Skin contact	Long-term systemic effects	16,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	6,25 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8,3 mg/kg
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis[2-[2-(1-methylethyl)-3- oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	Fresh water	0,0186 mg/l
	Marine water	0,00186 mg/l
	Fresh water sediment	0,709 mg/kg
	Marine sediment	0,0709 mg/kg
	Soil	1,131 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.



Revision Date: 26.05.2023 Date of last issue: 08.03.2023	Version 4.0	Print Date 05.02.2
Skin and body protection	: Protective clothing (e.g. Safety sh long-sleeved working clothing, lon and protective boots are additiona and stirring work.	ig trousers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation we Respirator selection must be based exposure levels, the hazards of the ing limits of the selected respirato organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; Ensure adequate ventilation. This exhaust extraction or by general work for determining inhalation expiration in the mixing / stirring area. to keep the concentrations under limits then respiration protection metals. 	ed on known or anticipated le product and the safe work- r. ; A3: < 10000 ppm can be achieved by local rentilation. (EN 689 - Meth- posure). This applies in par- . In case this is not sufficent the occupational exposure
Environmental exposure of	ontrols	
General advice	: Do not flush into surface water or If the product contaminates rivers respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

information on basic physical	an	a chemical propert
Physical state	:	liquid
Appearance	:	paste
Colour	:	various
Odour	:	slight
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up-	•	
per flammability limit		
Lower explosion limit /	:	No data available
Lower flammability limit		

Sikaflex[®]-295 N



Date of last issue: 08.03.2023		
Flash point : > 101 Metho	°C nd: closed cup	
Auto-ignition temperature : No dat	ta available	
Decomposition temperature : No da	ta available	
	oplicable ance/mixture is non-soluble (in water)	
Viscosity Viscosity, kinematic : > 20,5	5 mm2/s (40 °C)	
Solubility(ies) Water solubility : insolul	ble	
Partition coefficient: n- : No da octanol/water	ta available	
Vapour pressure : 0,01 h	Pa	
Density : ca. 1,2	23 g/cm3 (20 °C)	
Relative vapour density : No da	ta available	
Particle characteristics : No da	ta available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Sikaflex[®]-295 N



Revision Date: 26.05.2023 Date of last issue: 08.03.2023	Version 4.0	Print Date 05.02.202
Conditions to avoid	: Avoid moisture.	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decompositio No decomposition if stored	-	
SECTION 11: Toxicologica		
11.1 Information on hazard cl	asses as defined in Regulation (EC) No 1272/2	2008
Acute toxicity Not classified based on ava <u>Components:</u>	ailable information.	
aliphatic prepolymer (d-p	olvether based):	
Acute oral toxicity	: LD50 Oral (Rat): > 2.000 mg/kg	
Urea,N,N"-(methylenedi-4	,1-phenylene)bis[N'-butyl-:	
Acute oral toxicity	: LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402	
bis[2-[2-(1-methylethyl)-3	-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbam	ate:
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg	
3-isocyanatomethyl-3,5,5	-trimethylcyclohexyl isocyanate:	
Acute oral toxicity	: LD50 Oral (Rat): 4.814 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): 0,031 mg/l Exposure time: 4 h	
	Test atmosphere: dust/mist	
	Acute toxicity estimate: 0,031 mg/l	
	Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: LD50 Dermal (Rat): > 7.000 mg/kg	
2-ethyl-2-[[(1-oxoallyl)oxy	/]methyl]-1,3-propanediyl diacrylate:	
Acute oral toxicity	: LD50 Oral (Rat): 3.680 - 5.000 mg/kg	

Sikaflex[®]-295 N

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0

	Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
	Pentamethyl piperidylsebacate:
	Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg
	Skin corrosion/irritation
	Not classified based on available information.
	Serious eye damage/eye irritation
	Not classified based on available information.
	Respiratory or skin sensitisation
	Skin sensitisation
	May cause an allergic skin reaction.
	Respiratory sensitisation
	Not classified based on available information.
	Germ cell mutagenicity
	Not classified based on available information.
	Carcinogenicity
	Not classified based on available information.
	Reproductive toxicity Not classified based on available information.
	STOT - single exposure Not classified based on available information.
	STOT - repeated exposure
	Not classified based on available information.
	Aspiration toxicity
	Not classified based on available information.
11.2	2 Information on other hazards
	Endocrine disrupting properties
	Product:
	Assessment : The substance/mixture does not contain components cons ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (ELI) 2017/2100 or Commission Regulation (ELI) 2018/605

components consid-

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0



SECTION 12: Ecological information

12.1 Toxicity

Components:

aliphatic prepolymer (t-polyether based):

Toxicity to algae/aquatic	: EC50 (algae): 100 mg/l
plants	Exposure time: 72 h

NOEC (algae): 100 mg/l Exposure time: 72 h

aliphatic prepolymer (d-polyether based):

Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia (water flea)): > 100 mg/l		
	NOEC (Daphnia (water flea)): > 100 mg/l		
Toxicity to algae/aquatic : plants	EC50 (algae): > 100 mg/l Exposure time: 72 h		

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 87,1 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Scenedesmus capricornutum (fresh water algae)): 18,6 mg/l Exposure time: 72 h

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): 0	,87 mg/l
-	Exposure time: 96 h	•
	Method: OECD Test Guideline 20)3

M-Factor (Acute aquatic tox- : 1 icity)

Sikaflex[®]-295 N

Print Date 05.02.2024

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0

M-Factor (Chronic aquatic : 1 toxicity)

Pentamethyl piperidylsebacate:

Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1

M-Factor (Chronic aquatic : 1 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:		
Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product :	: The generation of waste should be avoided or minimized	
-----------	--	--

Sikaflex[®]-295 N



Revision Date: 26.05.2023Version 4.0Date of last issue: 08.03.2023

	wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental bazarde		

14.5 Environmental hazards

Not regulated as a dangerous good

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0



14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

REACH - Restrictions on the ma the market and use of certain da	5.1 Safety, health and environmental regulations/legislat REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		
			3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)
International Chemical Weapons Schedules of Toxic Chemicals ar		:	Not applicable
REACH - Candidate List of Subs Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subj (Annex XIV)	ect to authorisation	:	Not applicable
Regulation (EC) No 1005/2009 o plete the ozone layer	n substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on petants (recast)	ersistent organic pollu-	:	Not applicable
Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable
REACH Information:	All substances containe - registered by our ups		

Sikaflex[®]-295 N

Jika ®
Print Date 05.02.2024

of ma-

Revision Date: 26.05.2023
Date of last issue: 08.03.2023

Version 4.0

		 excluded from the regulation, and/or exempted from the registration.
Seveso III: Directive 2012/18/ jor-accident hazards involving		of the European Parliament and of the Council on the control on gerous substances. Not applicable
Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 1,01% w/w no VOC duties

- registered by us, and/or

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 1,05% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Version 4.0



amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315	:	Causes skin irritation.		
H317	:	May cause an allergic skin reaction.		
H319	:	Causes serious eye irritation.		
H330	:	Fatal if inhaled.		
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.		
H335	:	May cause respiratory irritation.		
H351	:	Suspected of causing cancer.		
H361f	:	Suspected of damaging fertility.		
H400	:	Very toxic to aquatic life.		
H410	:	Very toxic to aquatic life with long lasting effects.		
H411	:	Toxic to aquatic life with long lasting effects.		
H413	:	May cause long lasting harmful effects to aquatic life.		
Full text of other abbreviations				
Acute Tox.	:	Acute toxicity		
Aquatic Acute	:	Short-term (acute) aquatic hazard		

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0



Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
PL OEL	: Poland. Occupational exposure limits for airborne toxic sub-
-	stances
PL OEL / NDS	: Maximal Admissible Concentration
ADR	: European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL	: International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Silcaflox® 20E N

Sikaflex[®]-295 N

Revision Date: 26.05.2023 Date of last issue: 08.03.2023 Version 4.0



PL/EN