

Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Print Date 08.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikafloor[®]-262 AS N /262 AS N Thixo Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	-

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Cleasting (DECUL ATION (EC) No 4070/0000)

Classification (REGULATION (EC) No 12 Acute toxicity, Category 4	72/2008) H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the un- born child.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Jika®

Sikafloor[®]-262 AS N /262 AS N Thixo Part B

Revision Date: 08.11.2024 Date of last issue: 18.07.2024			Version 3.1	Print Date 08.11.2024
Hazard pictograms	:			
Signal word	:	Danger		
Hazard statements	:	H302 H314 H317 H361 H373 H412	Harmful if swallowed. Causes severe skin burns May cause an allergic skin Suspected of damaging fer child. May cause damage to orga or repeated exposure. Harmful to aquatic life with	reaction. rtility or the unborn ans through prolonged
Supplemental Hazard Statements	:	EUH071	Corrosive to the respi	ratory tract.
Precautionary statements	:	Prevention P201 P260 P280	n: Obtain special instruc Do not breathe mist o Wear protective glove eye protection/ face p	r vapours. es/ protective clothing/
		Response	:	
		P303 + P36	61 + P353 IF ON SKIN (or ately all contaminated with water.	hair): Take off immedi- I clothing. Rinse skin
		P304 + P34 P305 + P3	40 + P310 IF INHALED: R air and keep comforta mediately call a POIS 51 + P338 + P310 IF IN E`	ON CENTER/ doctor. YES: Rinse cautiously minutes. Remove con- and easy to do. Con-

Hazardous components which must be listed on the label:

Adduct IXA-P (epoxy amine adduct, polymer) 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) 2-piperazin-1-ylethylamine Cashew, nutshell liq. 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Print Date 08.11.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration
	Registration number		(% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 40 - < 60
Adduct IXA-P (epoxy amine ad- duct, polymer)	212580-83-1 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 10 - < 20
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity esti- mate Acute oral toxicity: 1.030 mg/kg	>= 10 - < 20

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor®-262 AS N /262 AS N Thixo Part B

Revision Date: 08.11.2024 Date of last issue: 18.07.2024

Version 3.1

1	 		_
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071	>= 5 - < 10
		Acute toxicity esti- mate	
		Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	
2-piperazin-1-ylethylamine Contains: 2-(2-aminoethylamino)ethanol <= 0,29 %	140-31-8 205-411-0 01-2119471486-30- XXXX	Repr. 2; H361 STOT RE 1; H372 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 5 - < 10
2,4,6- tris(dimethylaminomethyl)phenol Contains:	90-72-2 202-013-9 01-2119560597-27-	Acute dermal toxicity: 866 mg/kg Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 5 - < 10
bis[(dimethylamino)methyl]phenol <= 15 %	XXXX	Acute toxicity esti-	
		Acute oral toxicity: 1.999 mg/kg	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor®-262 AS N /262 AS N Thixo Part B

Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Cashew, nutshell liq.	8007-24-7 700-991-6 01-2119502450-57- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute toxicity esti- mate Acute oral toxicity: 500 mg/kg	>= 3 - < 5
	00500.00.4	Acute dermal toxicity: 2.000 mg/kg	4 0.5
2-Propenenitrile, reaction prod- ucts with 2,2,4(or 2,4,4)-trimethyl- 1,6-hexanediamine	90530-20-4 292-059-6 01-2120773937-35- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 1 - < 2,5
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	25513-64-8 247-063-2 01-2119560598-25- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Acute toxicity esti-	>= 0,1 - < 0,5
		mate Acute oral toxicity: 910 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.	
If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with di ty.	fficul-
In case of eye contact	: Small amounts splashed into eyes can cause irreversible sue damage and blindness. In the case of contact with eyes, rinse immediately with p	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Date of last issue: 18.07.2024		Version 3.1	Print Date 08.11.2024
		of water and seek medical advice. Continue rinsing eyes during transport to hospi Remove contact lenses. Keep eye wide open while rinsing.	tal.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsciou	
4.2 Most important symptoms an	nd	effects, both acute and delayed	
Symptoms	:	Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information o and symptoms.	n health effects
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects	
		Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility or the unborn c May cause damage to organs through prolonge exposure. Corrosive to the respiratory tract. Causes severe burns.	
4.3 Indication of any immediate r	me	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sui	res	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/ ide/sand/foam/alcohol resistant foam/chemical extinction.	
5.2 Special hazards arising from	th	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	ng apparatus.

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Date of last issue: 18.07.2024		Version 3.1	Print Date 08.11.2024
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental release	se i	neasures	
6.1 Personal precautions, protect	ctiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary s If the product contaminates rivers and lakes respective authorities.	
6.3 Methods and material for co	ntai	nment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. acid binder, universal binder, sawdust). Keep in suitable, closed containers for disp	
			osal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



Revision Date: 08.11.2024	Version 3.1	Print Date 08.11.2024
Date of last issue: 18.07.2024		

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

7.3

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
benzyl alcohol	100-51-6	NDS	240 mg/m3	PL OEL


*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipme	nt
Eye/face protection	 Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing





Revision Date: 08.11.2024 Date of last issue: 18.07.2024	Version 3.1	Print Date 08.11.2024
	and stirring work.	
Respiratory protection	 In case of inadequate ventilation wear in Respirator selection must be based on a exposure levels, the hazards of the proo- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < Ensure adequate ventilation. This can b exhaust extraction or by general ventilar ods for determining inhalation exposure ticular to the mixing / stirring area. In can to keep the concentrations under the oc- limits then respiration protection measure 	known or anticipated duct and the safe work- < 10000 ppm be achieved by local tion. (EN 689 - Meth- e). This applies in par- ise this is not sufficent ccupational exposure
Environmental exposure cor	ntrols	
General advice	: Do not flush into surface water or sanita If the product contaminates rivers and la respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid yellow
Odour	:	amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Upper flammability limit		No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup





Revision Date: 08.11.2024 Date of last issue: 18.07.2024		Version 3.1	Print Date 08.11.2024
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	ca. 11 (20 °C) Concentration: 50 %	
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,07 hPa	
Density	:	ca. 1,03 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

_

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------



Revision Date: 08.11.2024	Version 3.1	Print Date 08.11.2024		
Date of last issue: 18.07.2024				
10.5 Incompatible materials				
Materials to avoid : No data available				
10.6 Hazardous decomposition pro	ducts			
• •				
No decomposition if stored and a	pplied as directed.			
SECTION 11: Toxicological info	mation			
11.1 Information on hazard classes	as defined in Regulation (EC) No 1272	2/2008		
Acute toxicity				
Harmful if swallowed.				
Commonantos				

Components:	
benzyl alcohol: Acute oral toxicity	: Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
	LD50 Oral (Bat): 1 200 mg/kg

LD50 Oral (Rat): 1.200 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulatio No. 1272/2008	n (EC)
		LD50 Oral (Rat): 1.030 mg/kg	
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg	
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg	
m-phenylenebis(methylami	ne)	:	
Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg	
		Acute toxicity estimate: 930 mg/kg Method: Calculation method	
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.	
		Acute toxicity estimate: 1,34 mg/l	
ountry PL 10000003794			11,

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Date of last issue: 18.07.2024		Version 3.1	Print Date 08.11.2024
		tmosphere: dust/mist d: Calculation method	
Acute dermal toxicity	: LD50 I	Dermal (Rat): > 3.100 mg/kg	
2-piperazin-1-ylethylamine:			
Acute oral toxicity	: LD50 (Oral (Rat): > 1.999 mg/kg	
		toxicity estimate: 1.999 mg/kg d: Calculation method	
Acute dermal toxicity	: LD50 I	Dermal (Rabbit): ca. 866 mg/kg	
		toxicity estimate: 866 mg/kg d: Calculation method	
2,4,6-tris(dimethylaminome	nyl)pheno	l:	
Acute oral toxicity	Remai Annex	(Rat): > 1.999 mg/kg rks: Harmful if swallowed. VI - Harmonised LATION (EC) No 1272/2008	
Cashew, nutshell liq.:			
Acute oral toxicity	: LD50 (Oral (Rat): 500 mg/kg	
		toxicity estimate: 500 mg/kg d: Calculation method	
Acute dermal toxicity	: LD50 I	Dermal (Rat): 2.000 mg/kg	
		toxicity estimate: 2.000 mg/kg d: Calculation method	
2,2,4(or 2,4,4)-trimethylhexa	ne-1,6-dia	mine:	
Acute oral toxicity	: LD50 (Oral (Rat): 910 mg/kg	
		toxicity estimate: 910 mg/kg d: Calculation method	
Skin corrosion/irritation Causes severe burns.			
Components:			
2,4,6-tris(dimethylaminome	nyl)pheno	l:	
Species Assessment Method	: Rabbit : Corros : OECD		

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Print Date 08.11.2024

Assessment	:	irritating
Remarks	:	Annex VI - Harmonised
		REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	-	Rabbit Causes serious eye damage.
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Print Date 08.11.2024

SECTION 12: Ecological information

12.1 Toxicity **Components:** benzyl alcohol: Toxicity to fish : LC50 (Fish): > 100 mg/l Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h aquatic invertebrates 3-aminomethyl-3,5,5-trimethylcyclohexylamine: Toxicity to algae/aquatic ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 : plants mg/l Exposure time: 72 h NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h m-phenylenebis(methylamine): Toxicity to fish LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l • Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l aquatic invertebrates Exposure time: 48 h 2-piperazin-1-ylethylamine: Toxicity to fish ÷ LC50 (Fish): > 100 mg/l Exposure time: 96 h 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine: Toxicity to algae/aquatic EC50 (Scenedesmus capricornutum (fresh water algae)): 29,5 • plants mg/l Exposure time: 72 h Toxicity to fish (Chronic tox-÷ LC50: 174 mg/l Exposure time: 48 h icity) Species: Leuciscus idus (Golden orfe) 12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

Jika®

Sikafloor®-262 AS N /262 AS N Thixo Part B

Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Print Date 08.11.2024

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

- Assessment
- : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Pro	duct:

Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
	levels of 0.176 of higher.

12.7 Other adverse effects

TTOULOL.		
Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

Sikafloor®-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Date of last issue: 18.07.2024

Version 3.1

Print Date 08.11.2024

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 1760	
IMDG	:	UN 1760	
ΙΑΤΑ	:	UN 1760	
14.2 UN proper shipping name			
ADR	:	CORROSIVE LIQUID (3-aminomethyl-3,5,5- phenylenebis(methyla	-trimethylcyclohexylamine, m-
IMDG	:	CORROSIVE LIQUID (3-aminomethyl-3,5,5- phenylenebis(methyla	-trimethylcyclohexylamine, m-
ΙΑΤΑ	:	Corrosive liquid, n.o.s (3-aminomethyl-3,5,5- phenylenebis(methyla	-trimethylcyclohexylamine, m-
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	8	
IMDG	:	8	
ΙΑΤΑ	:	8	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	II C9 80 8 (E)	
IMDG Packing group Labels EmS Code Remarks		II 8 F-A, S-B Alkalis	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	855 Y840 II Corrosive	

tion (EU) 2020/878

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Version 3.1 Print Date 08.11.2024 Date of last issue: 18.07.2024 IATA (Passenger)

:	851
:	Y840
:	II
:	Corrosive
	:

14.5 Environmental hazards

ADR Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

: Not applicable

- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the following entries should be considered: the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: None of the components are listed (=> 0.1 %).

Number on list 75:

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024	Version 3.1	Print Date 08.11.2024
Date of last issue: 18.07.2024		

REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	: Not applicable
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	: Not applicable
Seveso III: Directive 2012/18/EU of the European Parliam jor-accident hazards involving dangerous substances. Not applicable	ent and of the Council on the control of ma-
Valatila argania compounda de la cur en the incentive to	w for volatile, are asia a managenda

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 42,6% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 42,6% w/w

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC)



Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Print Date 08.11.2024

No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 :	Harmful if swallowed.
H311 :	Toxic in contact with skin.
H312 :	Harmful in contact with skin.
H314 :	Causes severe skin burns and eye damage.

_

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 08.11.2024 Date of last issue: 18.07.2024	Version 3.1	Print Date 08.11.2024
H315 : H317 : H318 : H319 : H332 : H361 : H372 : H411 : H412 : H413 :	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Suspected of damaging fertility or the unborn chi Causes damage to organs through prolonged or exposure. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic	repeated
Full text of other abbreviations		
Acute Tox.:Aquatic Chronic:Eye Dam.:Eye Irrit.:Repr.:Skin Corr.:Skin Irrit.:	Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Reproductive toxicity Skin corrosion Skin irritation	
Skin Sens. : STOT RE : PL OEL :	Skin sensitisation Skin sensitisation Specific target organ toxicity - repeated exposure Ordinance of the Minister of Family, Labour and of 12 June 2018 concerning the highest allowable tions and levels of the agents harmful for health i place (Dz.U 2018 pos 1286, with later amendme	Social Policy e concentra- n the work-
PL OEL / NDS : ADR :	Maximal Admissible Concentration European Agreement concerning the Internation	al Carriage of
CAS : DNEL : EC50 : GHS : IATA : IMDG : LD50 :	Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Good Median lethal dosis (the amount of a material, giv once, which causes the death of 50% (one half)	/en all at
LC50 :	test animals) Median lethal concentration (concentrations of th air that kills 50% of the test animals during the ob period)	
MARPOL :	International Convention for the Prevention of Pc Ships, 1973 as modified by the Protocol of 1978	llution from
OEL : PBT : PNEC : REACH :	Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European and of the Council of 18 December 2006 concern istration, Evaluation, Authorisation and Restrictio cals (REACH), establishing a European Chemica	ning the Reg- n of Chemi-
SVHC : vPvB :	Substances of Very High Concern Very persistent and very bioaccumulative	



Revision Date: 08.11.2024 Date of last issue: 18.07.2024 Version 3.1

Classification procedure:

Print Date 08.11.2024

Further information

Classification of the mixture:

Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN