

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] MRP Soft Light Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Poland Spółka z o.o.
	Karczunkowska 89
	02-871 Warszawa
Telephone	: +48 22 27 28 700
Telefax	: +48 22 27 28 800
E-mail address of person	: EHS@pl.sika.com
responsible for the SDS	

1.4 Emergency telephone number

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1, hearing organs	H372: Causes damage to organs through pro- longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Hazard pictograms

Revision Date: 08.03.2023 Date of last issue: 31.08.2022



:	Danger	
:	H226 H315 H317 H319 H361d H372	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging the unborn child. Causes damage to organs (hearing organs) through prolonged or repeated exposure.
:	Prevention:	
	P201 P210	Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe mist or vapours.
	P264	Wash skin thoroughly after handling.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	Response:	
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
	:	 H226 H315 H317 H319 H361d H372 Prevention: P201 P210 P260 P264 P280 Response:

Version 4.0

Hazardous components which must be listed on the label:

styrene maleic anhydride

Additional Labelling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 01-2119457861-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation tox-	>= 10 - < 20
		icity (vapour): 11,8 mg/l	
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2,5 - < 5
maleic anhydride	108-31-6 203-571-6 01-2119472428-31- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Inhalation, Respira- tory system) EUH071	>= 0,001 - < 0,1
		specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	



Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

Substances with a workplace e	xposure limit :	
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX	>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	: Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: irritant effects sensitising effects
	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.



Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing m	edia :	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising	from the	e substance or mixture
Specific hazards during f fighting	ire- :	Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion p ucts	orod- :	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipr for firefighters	nent :	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions	
Environmental precautions	 Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cont	tainment and cleaning up
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
6.4 Reference to other sections	

For personal protection see section 8.

Revision Date: 08.03.2023 Date of last issue: 31.08.2022



Version 4.0

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling :	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
1.2	Conditions for safe storage, inc	
	Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- : age stability	No decomposition if stored and applied as directed.
7.3	Specific end use(s)	
	Specific use(s) :	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

	Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
	styrene	100-42-5	NDS	50 mg/m3	PL OEL
~					0 / 10

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika[®] MRP Soft Light Part A



Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

		NDSch	100 mg/m3	PL OEL	
Titanium dioxide (> 10 μm)	13463-67-7	NDS (inhalable	10 mg/m3	PL OEL	
		fraction)			
reaction mass of ethylbenzene and xy-	Not Assigned	TWA	50 ppm	2000/39/EC	
lene			221 mg/m3		
	Further information: Identifies the possibility of significant uptake				
	through the skin, Indicative				
		STEL	100 ppm	2000/39/EC	
			442 mg/m3		
		NDS	100 mg/m3	PL OEL	
	Further inform	ation: Skin			
		NDSch	200 mg/m3	PL OEL	
maleic anhydride	108-31-6	NDS	0,5 mg/m3	PL OEL	
	Further information: Skin				
		NDSch	1 mg/m3	PL OEL	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Hand protection: Chemical-resistant, impervious gloves complying with an proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow ma facturer specifications.	
Suitable for short time use or protection against splashes Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	:
Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 203 long-sleeved working clothing, long trousers). Rubber apr and protective boots are additionally recommended for mi and stirring work.	rons
 Respiratory protection In case of inadequate ventilation wear respiratory protection Respirator selection must be based on known or anticipate exposure levels, the hazards of the product and the safe ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by loc exhaust extraction or by general ventilation. (EN 689 - Me ods for determining inhalation exposure). This applies in p ticular to the mixing / stirring area. In case this is not suffice 	ted work- cal eth- par-



Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice

: Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Information on basic physical	an	d chemical properties
Physical state Appearance Colour	:	liquid paste yellow
Odour	:	characteristic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	1 %(V)
Flash point	:	ca. 32 °C Method: closed cup
Auto-ignition temperature	:	465 °C
Decomposition temperature	:	No data available
рН	:	Not applicable
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

Revision Date: 08.03.2023 Date of last issue: 31.08.2022





Solubility(ies)

Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	5,9995 hPa
Density	:	1,25 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.

10.4 Conditions to avoid

leat, flames and sparks.
ł

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Print Date 10.03.2023

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

styrene:

Acute inhalation toxicity	:	LC50 (Rat): 11,8 mg/l Exposure time: 4 h Test atmosphere: vapour
		Acute toxicity estimate: 11,8 mg/l Test atmosphere: vapour Method: Calculation method

reaction mass of ethylbenzene and xylene:

A outo oral toxicity	· .	DEC Orol (Dat), 2 E22 ma/ka
Acute oral toxicity	•	LD50 Oral (Rat): 3.523 mg/kg

maleic anhydride:

Acute inhalation toxicity : A	Assessment: Corrosive to the respiratory tract.
-------------------------------	---

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure.

Revision Date: 08.03.2023 Date of last issue: 31.08.2022

Version 4.0



Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox-	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other	:	NOEC: 1,17 mg/l

aquatic invertebrates (Chron-	Exposure time: 7 d
ic toxicity)	Species: Daphnia (water flea)

2

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to



Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

:	UN 3269
:	UN 3269
:	UN 3269
:	POLYESTER RESIN KIT
:	POLYESTER RESIN KIT
:	Polyester resin kit
	:

Print Date 10.03.2023

Revision Date: 08.03.2023	
Date of last issue: 31.08.2022	

Version 4.0

risks

			Class	Subsidiary
	ADR		Class	Subsidiary
		:	3	
	IMDG	:	3	
		÷	3	
14.4	Packing group			
	ADR Packing group Classification Code Labels Tunnel restriction code	::	III F3 3 (E)	
	IMDG Packing group Labels EmS Code	:	III 3 F-E, S-D	
	IATA (Cargo) Packing instruction (cargo aircraft)	:	370	
	Packing instruction (LQ) Packing group Labels	:	Y370 III Flammable Liquids	
	IATA (Passenger) Packing instruction (passen- ger aircraft)	:	370	
	Packing instruction (LQ) Packing group Labels	:	Y370 III Flammable Liquids	
14.	5 Environmental hazards		·	
	ADR			
	Environmentally hazardous	:	no	
	IMDG Marine pollutant	:	no	
	IATA (Passenger) Environmentally hazardous	:	no	
	IATA (Cargo)		20	

Environmentally hazardous 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

: no

Not applicable for product as supplied.

Sika® MRP Soft Light Part A

Print Date 10.03.2023

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

SECTION 15: Regulatory information

15.	15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
	REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3	
	International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			Not applicable	
	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).	
	REACH - List of substances subject to authorisation (Annex XIV)			Not applicable	
	Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer			Not applicable	
	Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable tants (recast)			Not applicable	
	Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable	
	REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	strea /or gula	am suppliers, and/or ation, and/or	
	Seveso III: Directive 2012/18/EU jor-accident hazards involving da P5c			t and of the Council on the control of ma-	
	Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 2,9% w/w	
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)			ution prevention and control)	

Volatile organic compounds (VOC) content: 19,99% w/w

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0



Π

Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended).

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Print Date 10.03.2023

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

1485, with later amendments)

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

11000		
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H361d	:	Suspected of damaging the unborn child.
H372	:	Causes damage to organs through prolonged or repeated
		exposure.
H373	:	May cause damage to organs through prolonged or repeated
		exposure if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviat	ions	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
	:	Long-term (chronic) aquatic hazard Aspiration hazard
Aquatic Chronic	:	
Aquatic Chronic Asp. Tox.	:	Aspiration hazard
Aquatic Chronic Asp. Tox. Eye Dam.	:	Aspiration hazard Serious eye damage
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit.		Aspiration hazard Serious eye damage Eye irritation
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq.		Aspiration hazard Serious eye damage Eye irritation Flammable liquids
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr.	:	Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens.		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr.		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr. Skin Irrit.		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion Skin irritation
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr. Skin Irrit. Skin Sens. STOT RE STOT SE		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion Skin irritation Skin sensitisation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr. Skin Irrit. Skin Sens. STOT RE		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr. Skin Irrit. Skin Sens. STOT RE STOT SE		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion Skin irritation Skin sensitisation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr. Skin Irrit. Skin Sens. STOT RE STOT SE		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first
Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Repr. Resp. Sens. Skin Corr. Skin Irrit. Skin Sens. STOT RE STOT SE 2000/39/EC		Aspiration hazard Serious eye damage Eye irritation Flammable liquids Reproductive toxicity Respiratory sensitisation Skin corrosion Skin irritation Skin sensitisation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika[®] MRP Soft Light Part A

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Print Date 10.03.2023

Version 4.0

2000/39/EC / TWA 2000/39/EC / STEL PL OEL / NDS PL OEL / NDSch ADR		Limit Value - eight hours Short term exposure limit Maximal Admissible Concentration Maximal Admissible Temporary Concentration European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL		Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ		International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50		Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	;	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL		Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	-	Predicted no effect concentration
REACH	i	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC		Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure: Based on product data or assessment Flam. Liq. 3 H226 Skin Irrit. 2 H315 Calculation method Eye Irrit. 2 H319 Calculation method Skin Sens. 1 H317 Calculation method H361d Calculation method Repr. 2 STOT RE 1 H372 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

PL/EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika[®] MRP Soft Light Part A

Revision Date: 08.03.2023 Date of last issue: 31.08.2022 Version 4.0

